

FULCAT-22 F

Product code: 000000000000158440

Version 3.0 SDS_APJ_MY

Revision Date 18.11.2022

Print Date 09.08.2023

SECTION 1: Identification of the hazardous chemical and of the supplier**Product identifier**

Product name : FULCAT-22 F

Recommended use : Catalyst

Manufacturer or supplier's details

Company : BYK Additives Ltd.

Address : Moorfield Road
WA8 3AA Widnes

Telephone : +49 281 670-23532

Telefax : +49 281 670-23533

E-mail address : GHS.BYK@altana.com

Emergency telephone number : +60 3 6207 4347 (Malay and English)
+65 3158 1074 (All languages)**SECTION 2: Hazards identification****Classification of the hazardous chemical**

Carcinogenicity : Category 1A

Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H350 May cause cancer.

Precautionary statements :

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P281 Use personal protective equipment as required.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

FULCAT-22 F

Product code: 000000000000158440

Version 3.0 SDS_APJ_MY

Revision Date 18.11.2022

Print Date 09.08.2023

Other hazards which do not result in classification

Contaminated surfaces will be extremely slippery.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Substance
 Chemical nature : Acid leached phyllosilicate

Components

Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO ₂)	14808-60-7	>= 1 -< 3

SECTION 4: First aid measures

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.
 If breathed in, move person into fresh air.

In case of skin contact : Wash off with soap and water.
 Get medical attention if irritation develops and persists.
 If on clothes, remove clothes.
 Wash contaminated clothing before re-use.

In case of eye contact : Flush eyes with water as a precaution.
 Remove contact lenses.
 Protect unharmed eye.
 Keep eye wide open while rinsing.
 If eye irritation persists, consult a specialist.

If swallowed : Induce vomiting immediately and call a physician.
 Keep respiratory tract clear.
 Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.
 Rinse mouth with water.
 If large quantities of this material are swallowed, call a physician immediately.

Most important symptoms and effects, both acute and delayed : No symptoms known or expected.
 Irritating to eyes, respiratory system and skin.

Notes to physician : Treat symptomatically.

FULCAT-22 F

Product code: 000000000000158440

Version 3.0 SDS_APJ_MY

Revision Date 18.11.2022

Print Date 09.08.2023

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Water spray
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Physicochemical hazards arising from the chemical

Specific hazards during firefighting : The product itself does not burn.
Material can be slippery when wet.

Hazardous combustion products : No hazardous combustion products are known

Special protective equipment and precautions for fire-fighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Specific extinguishing methods : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.
Keep people away from and upwind of spill/leak.
Material can create slippery conditions.
Only qualified personnel equipped with suitable protective equipment may intervene.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Pick up and arrange disposal without creating dust.
Use approved industrial vacuum cleaner for removal.
High efficiency particulate air filter (HEPA filter)
Clean-up methods - large spillage
Knock down dust with water spray jet.
Shovel into suitable container for disposal.
After cleaning, flush away traces with water.
Clean-up methods - small spillage

FULCAT-22 F

Product code: 000000000000158440

Version 3.0 SDS_APJ_MY

Revision Date 18.11.2022

Print Date 09.08.2023

Sweep up or vacuum up spillage and collect in suitable container for disposal.

Neutralize with chalk, alkali solution or ammonia.
Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage

Handling

Precautions for safe handling

Advice on protection against fire and explosion : Avoid dust formation.
Provide appropriate exhaust ventilation at places where dust is formed.

Advice on safe handling : Avoid formation of respirable particles.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.

Storage

Conditions for safe storage, including any incompatibilities

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Avoid dust formation.

Further information on storage stability : Keep in a dry place.
No decomposition if stored and applied as directed.

SECTION 8: Exposure controls and personal protection

Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO ₂)	14808-60-7	TWA (Respirable fraction)	0.1 mg/m ³	MY PEL
		TWA (Respirable fraction)	0.025 mg/m ³ (Silica)	ACGIH

FULCAT-22 F

Product code: 000000000000158440

Version 3.0 SDS_APJ_MY

Revision Date 18.11.2022

Print Date 09.08.2023

Appropriate engineering controls : Ensure adequate ventilation.
Maintain air concentrations below occupational exposure standards.
Dust must be extracted directly at the point of origin.

Individual protection measures, such as personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear safety glasses with side shields or goggles.
If the work environment or activity involves dusty conditions, mists or aerosols, wear the appropriate goggles.

Skin protection : Dust impervious protective suit
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Work uniform or laboratory coat.

Hand protection

Remarks : Use protective skin cream before handling the product.
Wear suitable gloves.

Respiratory protection : In the case of dust or aerosol formation use respirator with an approved filter.
Dust safety masks are recommended when the dust concentration is more than 10 mg/m³.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

Appearance : powder

Colour : beige

Odour : odourless

Odour Threshold : Not applicable

pH : 3

Melting point/freezing point : Not applicable

Boiling point/boiling range : Not applicable

Flash point : Not applicable

FULCAT-22 F

Product code: 000000000000158440

Version 3.0 SDS_APJ_MY

Revision Date 18.11.2022

Print Date 09.08.2023

Evaporation rate	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	Not applicable
Relative vapour density	:	Not applicable
Density	:	1 g/cm ³ (20 °C)
Bulk density	:	1,000 kg/m ³
Solubility(ies) Water solubility	:	insoluble
Decomposition temperature	:	Not applicable
Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	Not applicable
Surface tension	:	No data available

SECTION 10: Stability and reactivity

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed.
Conditions to avoid	:	No data available
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Information on likely routes of exposure : None known.

Acute toxicity**Product:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

FULCAT-22 F

Product code: 00000000000158440

Version 3.0 SDS_APJ_MY

Revision Date 18.11.2022

Print Date 09.08.2023

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 50 mg/l
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation**Product:**

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Serious eye damage/eye irritation**Product:**

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
GLP : yes

Respiratory or skin sensitisation**Product:**

Test Type : Mouse Local Lymph Node assay (LLNA)
Exposure routes : Dermal
Species : Mouse
Method : OECD Test Guideline 429
Result : Does not cause skin sensitisation.

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Test Type: reverse mutation assay
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes

Test Type: Chromosome aberration test in vitro
Test system: Human lymphocytes
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative
GLP: yes

Test Type: In vitro mammalian cell gene mutation test (mouse lymphoma)

FULCAT-22 F

Product code: 000000000000158440

Version 3.0 SDS_APJ_MY

Revision Date 18.11.2022

Print Date 09.08.2023

Test system: mouse lymphoma cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative
GLP: yes

Further information**Product:**

Remarks : No data available

SECTION 12: Ecological information**Ecotoxicity****Product:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: Immobilization
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l
Exposure time: 3 h
Test Type: Respiration inhibition
Method: OECD Test Guideline 209

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil**Product:**

Mobility : Remarks: Bentonite is almost insoluble and thus presents a low mobility in most soils

Other adverse effects**Product:**

Additional ecological information : No data available

FULCAT-22 F

Product code: 000000000000158440

Version 3.0 SDS_APJ_MY

Revision Date 18.11.2022

Print Date 09.08.2023

SECTION 13: Disposal information**Disposal methods**

- Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information**International Regulations****UNRTDG**

- UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable

IATA-DGR

- UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo aircraft) : Not applicable
Packing instruction (passenger aircraft) : Not applicable

IMDG-Code

- UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
EmS Code : Not applicable
Marine pollutant : Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

Not applicable

SECTION 15: Regulatory information

FULCAT-22 F

Product code: 00000000000158440

Version 3.0 SDS_APJ_MY

Revision Date 18.11.2022

Print Date 09.08.2023

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

SECTION 16: Other information**Further information**

Training advice : Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

Other information : In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)

In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)

According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits.

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
MY PEL : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

FULCAT-22 F

Product code: 000000000000158440

Version 3.0 SDS_APJ_MY

Revision Date 18.11.2022

Print Date 09.08.2023

ACGIH / TWA : 8-hour, time-weighted average
MY PEL / TWA : Eight-hour time-weighted average airborne concentration

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MY / EN