

PURABYK-P 5541 SATIN XR

Version 1

Revision Date 04/03/2024

Print Date 01/06/2026

SECTION 1. IDENTIFICATION

Product name : PURABYK-P 5541 SATIN XR

Manufacturer or supplier's detailsCompany : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.comE-mail address : BRIEF.BYK.NAFTA@altana.comEmergency telephone number : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Rheology Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Carcinogenicity : Category 1A

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H350 May cause cancer.

Precautionary statements : **Prevention:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

PURABYK-P 5541 SATIN XR

Version 1

Revision Date 04/03/2024

Print Date 01/06/2026

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance
 Chemical nature : Natural phyllosilicate

Hazardous components

Component	CAS-No.	Concentration (%)
Crystalline silica (quartz)	14808-60-7	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.

In case of eye contact : Flush eyes with water as a precaution.
 Remove contact lenses.
 Protect unharmed eye.
 Keep eye wide open while rinsing.
 If eye irritation persists, consult a specialist.

If swallowed : Induce vomiting immediately and call a physician.
 Keep respiratory tract clear.
 Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.
 Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Foam
 Carbon dioxide (CO₂)
 Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : The product itself does not burn.

Hazardous combustion products : No hazardous combustion products are known

Further information : Standard procedure for chemical fires.
 Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

PURABYK-P 5541 SATIN XR

Version 1

Revision Date 04/03/2024

Print Date 01/06/2026

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of respirable particles.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Crystalline silica (quartz)	14808-60-7	TWA (total dust)	30 mg/m ³ / %SiO ₂ +2	OSHA Z-3
Crystalline silica (quartz)		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
Crystalline silica (quartz)		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
Crystalline silica (quartz)		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0

PURABYK-P 5541 SATIN XR

Version 1

Revision Date 04/03/2024

Print Date 01/06/2026

Crystalline silica (quartz)		TWA (Respirable fraction)	0.025 mg/m ³ (Silica)	ACGIH
Crystalline silica (quartz)		TWA (Respirable dust)	0.05 mg/m ³ (Silica)	NIOSH REL

Further occupational exposure limits

Description	Value type	Control parameters	Basis
inert or nuisance dust	TWA	50Million particles per cubic foot total dust	OSHA Z-3
	TWA	15 mg/m ³ total dust	OSHA Z-3
	TWA	5 mg/m ³ respirable fraction	OSHA Z-3
	TWA	15Million particles per cubic foot respirable fraction	OSHA Z-3

Personal protective equipment

- Respiratory protection : In the case of dust or aerosol formation use respirator with an approved filter.
Dust safety masks are recommended when the dust concentration is more than 10 mg/m³.
- Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
- Skin and body protection : Dust impervious protective suit
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : powder
- Colour : off-white
- Odour : odourless
- pH : 7.0 - 8.5, Concentration: 2 %(as a dispersion)
- Melting point/range : Not applicable
- Boiling point/boiling range : Not applicable
- Vapour pressure : Not applicable

PURABYK-P 5541 SATIN XR

Version 1

Revision Date 04/03/2024

Print Date 01/06/2026

Flash point	: Not applicable
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Flammability (solid, gas)	: Does not sustain combustion.
Density	: 2.6 g/cm ³ (68 °F (20 °C))
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: insoluble
Ignition temperature	: Not applicable
Thermal decomposition	: Not applicable
Viscosity	
Viscosity, dynamic	: Not applicable
Viscosity, kinematic	: Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
	Dust may form explosive mixture in air.
Conditions to avoid	: None known.
Incompatible materials	: None known.
Hazardous decomposition products	: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Ingestion
Eye contact
Skin contact

Acute toxicity**Product:**

PURABYK-P 5541 SATIN XR

Version 1

Revision Date 04/03/2024

Print Date 01/06/2026

Acute oral toxicity : Acute toxicity estimate : 2,732 mg/kg
Method: Calculation method

Skin corrosion/irritation

Product:

Remarks: No data available

Serious eye damage/eye irritation

Product:

Remarks: No data available

Respiratory or skin sensitisation

Product:

Remarks: No data available

Carcinogenicity

IARC	Group 1: Carcinogenic to humans	
	Crystalline silica (quartz)	14808-60-7
OSHA	OSHA specifically regulated carcinogen	
	Crystalline silica (quartz)	14808-60-7
NTP	Known to be human carcinogen	
	Crystalline silica (quartz)	14808-60-7

Repeated dose toxicity

Product:

Remarks: No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish :

PURABYK-P 5541 SATIN XR

Version 1

Revision Date 04/03/2024

Print Date 01/06/2026

Remarks: No data available

Toxicity to daphnia and other :
aquatic invertebrates Remarks: No data available

Persistence and degradability**Product:**

Biodegradability : Remarks: No data available

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:Regulation 40 CFR Protection of Environment; Part 82 Protection of
Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a
Class I or Class II ODS as defined by the U.S. Clean Air Act
Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological : No data available
information**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

Not regulated as a dangerous good

PURABYK-P 5541 SATIN XR

Version 1

Revision Date 04/03/2024

Print Date 01/06/2026

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

This material does not contain any components with a CERCLA RQ.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

PURABYK-P 5541 SATIN XR

Version 1

Revision Date 04/03/2024

Print Date 01/06/2026

Massachusetts Right To Know

Crystalline silica (quartz) 14808-60-7

Pennsylvania Right To KnowPhyllosilicate -
Water 7732-18-5**New Jersey Right To Know****New Jersey Trade Secret Registry Number for the product (NJ TSRN)** : 800963-6513**California Prop. 65**

 **WARNING:** This product can expose you to chemicals including Crystalline silica (quartz), which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

Section 5a : No substances are subject to a Significant New Use Rule.

Section 4 / 12(b) : No substances are subject to TSCA 12(b) export notification requirements.

DSL : We certify that all of the components of this product are listed on the DSL.

SECTION 16. OTHER INFORMATION

Revision Date : 04/03/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.