

RHEOBYK-405 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : RHEOBYK-405 SG
Product code : 000000000000130008

Manufacturer or supplier's details

Company : BYK USA LLC
Address : South Cherry Street 524
06492 Wallingford
Telephone : +1 203-265-2086
Telefax :
E-mail address : BRIEF.BYK.NAFTA@altana.com
Emergency telephone number : 18000 74234 (toll –free number, access from Australia only)
+61 2 8014 4558

Importer

Company : IMCD Australia Pty Ltd
Level 1, 352 Wellington Road
Mulgrave
VIC 3170
Australia
Telephone: +61 3 8544 3100

Use of the Sub-
stance/Mixture : Rheology Additive

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3
Skin corrosion/irritation : Category 2
Serious eye damage/eye irritation : Category 1
Carcinogenicity : Category 1B
Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)
Specific target organ toxicity - repeated exposure : Category 2 (hearing organs)
Short-term (acute) aquatic hazard : Category 3

RHEOBYK-405 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

Long-term (chronic) aquatic hazard : Category 3

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H350 May cause cancer.
H373 May cause damage to organs (hearing organs) through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P332 + P313 If skin irritation occurs: Get medical advice/ atten-

RHEOBYK-405 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

tion.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Solution of polyhydroxycarboxylic acid amides

Components

Chemical name	CAS-No.	Concentration (% w/w)
Xylene, mixture of isomers	1330-20-7	≥ 12.5 -< 20
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified	64742-95-6	≥ 12.5 -< 20
iso-butanol	78-83-1	≥ 5 -< 7
ethylbenzene	100-41-4	≥ 3 -< 5
cumene	98-82-8	≥ 0.5 -< 1
toluene	108-88-3	≥ 0.1 -< 0.25

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.

RHEOBYK-405 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

If swallowed	:	Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
		Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	No information available. Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness. May cause cancer. May cause damage to organs through prolonged or repeated exposure.
Notes to physician	:	No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire-fighting	:	Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon oxides Nitrogen oxides (NO _x) Sulphur oxides
Specific extinguishing methods	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Hazchem Code	:	•3Y

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so.

RHEOBYK-405 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national regulations.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

Conditions for safe storage : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Xylene, mixture of isomers	1330-20-7	TWA	80 ppm 350 mg/m ³	AU OEL
		STEL	150 ppm 655 mg/m ³	AU OEL
		TWA	20 ppm	ACGIH

RHEOBYK-405 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

iso-butanol	78-83-1	TWA	50 ppm 152 mg/m ³	AU OEL
		TWA	50 ppm	ACGIH
ethylbenzene	100-41-4	TWA	100 ppm 434 mg/m ³	AU OEL
		STEL	125 ppm 543 mg/m ³	AU OEL
		TWA	20 ppm	ACGIH
cumene	98-82-8	TWA	25 ppm 125 mg/m ³	AU OEL
Further information: Skin absorption				
		STEL	75 ppm 375 mg/m ³	AU OEL
Further information: Skin absorption				
		TWA	5 ppm	ACGIH
toluene	108-88-3	TWA	50 ppm 191 mg/m ³	AU OEL
Further information: Skin absorption				
		STEL	150 ppm 574 mg/m ³	AU OEL
Further information: Skin absorption				
		TWA	20 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Xylene, mixture of iso-mers	1330-20-7	Methylhip-puric acids	Urine	End of shift (As soon as possible after exposure ceases)	0.3 g/g cre-atinine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenyl gly-oxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	150 mg/g creatinine	ACGIH BEI
toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As	0.3 mg/g creatinine	ACGIH BEI

RHEOBYK-405 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

				soon as possible after exposure ceases)		
--	--	--	--	---	--	--

Personal protective equipment

Respiratory protection	:	In the case of vapour formation use a respirator with an approved filter.
Hand protection		
Material	:	Nitrile rubber
Break through time	:	> 480 min
Remarks	:	Wear suitable gloves.
Eye protection	:	Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	light brown
Odour	:	not significant
Odour Threshold	:	No data available
pH	:	6 (20 °C) Concentration: 1 % Method: Universal pH-value indicator
Melting point/ range	:	< 0 °C Method: estimated
Initial boiling point	:	106.00 °C Method: estimated
Flash point	:	29.00 °C Method: 48 (Abel-Pensky) DIN 51755
Evaporation rate	:	No data available
Flammability (liquids)	:	Sustains combustion
Upper explosion limit / Upper flammability limit	:	10.70 %(V)
Lower explosion limit / Lower	:	1.00 %(V)

RHEOBYK-405 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

flammability limit

Vapour pressure : < 7 hPa (20.00 °C)
Method: calculated

Relative vapour density : No data available

Relative density : No data available

Density : 0.9250 g/cm³ (20.00 °C)
Method: 4 (20°C oscillating U-tube)

Bulk density : Not applicable

Solubility(ies)
Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-
octanol/water : No data availableAuto-ignition temperature : > 200.00 °C
Method: DIN 51794

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : 228 mm²/s (40.00 °C)

Surface tension : No data available

SECTION 10. STABILITY AND REACTIVITYReactivity : No decomposition if stored and applied as directed.
Chemical stability : No decomposition if stored and applied as directed.
Possibility of hazardous reac- : No decomposition if stored and applied as directed.
tions Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids
Strong oxidizing agentsHazardous decomposition : No decomposition if stored normally.
products**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified due to lack of data.

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h

RHEOBYK-405 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026Test atmosphere: vapour
Method: Calculation methodAcute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method**Components:****Xylene, mixture of isomers:**Acute oral toxicity : LD50 (Rat): 4,300 mg/kg
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)
GLP: noAcute dermal toxicity : LD50 (Rabbit): > 4,200 mg/kg
GLP: No information available.**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : LD50 (Rabbit, male and female): > 3,160 mg/kg
Method: OECD Test Guideline 402**iso-butanol:**Acute oral toxicity : LD50 (Rat, male): > 2,830 mg/kg
Method: OECD Test Guideline 401
GLP: yesAcute dermal toxicity : LD50 (Rabbit, male): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes**Skin corrosion/irritation**

Causes skin irritation.

Product:Remarks : May irritate skin.
May cause skin irritation in susceptible persons.**Components:****Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes**iso-butanol:**Species : Rabbit
Result : Skin irritation

RHEOBYK-405 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
GLP : yes

iso-butanol:

Species : Rabbit
Result : Eye irritation
Method : OECD Test Guideline 405
GLP : yes

Respiratory or skin sensitisation**Skin sensitisation**

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Product:

Remarks : No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Test Type : Maximisation Test
Exposure routes : Dermal
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.

iso-butanol:

Test Type : Maximisation Test
Exposure routes : Dermal
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.

RHEOBYK-405 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

Chronic toxicity**Germ cell mutagenicity**

Not classified due to lack of data.

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Result: No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Germ cell mutagenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity

May cause cancer.

Product:

Remarks : No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified due to lack of data.

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

Product:

Remarks : No data available

STOT - repeated exposure

May cause damage to organs (hearing organs) through prolonged or repeated exposure.

Product:

Remarks : No data available

Repeated dose toxicity**Product:**

RHEOBYK-405 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

Remarks : No data available

Aspiration toxicity

Not classified due to lack of data.

Product:

No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

iso-butanol:

No aspiration toxicity classification

Further information**Product:**

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Components:**Xylene, mixture of isomers:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1 mg/l
Exposure time: 24 h
Test Type: Immobilization
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 2.2 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.44 mg/l
Exposure time: 72 h

RHEOBYK-405 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026Test Type: Growth inhibition
Method: OECD Test Guideline 201Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l
Exposure time: 56 dToxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia sp. (water flea)): 1.17 mg/l
Exposure time: 7 dNOEC (Daphnia sp. (water flea)): 0.96 mg/l
Exposure time: 7 d**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**Toxicity to fish : LL50 (Fish): 9.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
GLP: yesToxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3.2 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yesToxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata): 2.6 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes**iso-butanol:**Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1,430 mg/l
Exposure time: 96 hToxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 1,100 mg/l
Exposure time: 48 h
Test Type: static testToxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 1,799 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yesToxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 20 mg/l
End point: Reproduction
Exposure time: 21 d
Test Type: semi-static test**Persistence and degradability****Components:****Xylene, mixture of isomers:**

Biodegradability : aerobic

RHEOBYK-405 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

Result: Readily biodegradable.
Method: OECD Test Guideline 301F
GLP: yes

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F

iso-butanol:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301D

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

Components:**Xylene, mixture of isomers:**

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 25.9
Exposure time: 56 d
GLP: no

Partition coefficient: n-octanol/water : Pow: 3.2 (20 °C)
pH: 7

iso-butanol:

Partition coefficient: n-octanol/water : log Pow: 1
Method: OECD Test Guideline 117
GLP: yes

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.

RHEOBYK-405 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

Contaminated packaging : Send to a licensed waste management company.
Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(XYLENE, Isobutanol)
Class : 3
Packing group : III
Labels : 3

IATA-DGR

UN/ID No. : UN 1993
Proper shipping name : Flammable liquid, n.o.s.
(Xylene, Isobutanol)
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(XYLENE, Isobutanol)
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no
Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**ADG**

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(Xylene, Isobutanol)
Class : 3
Packing group : III
Labels : 3
Hazchem Code : •3Y

RHEOBYK-405 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture****SECTION 16. OTHER INFORMATION**

Revision Date : 14.03.2025
Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA : 8-hour, time-weighted average
AU OEL / TWA : Exposure standard - time weighted average
AU OEL / STEL : Exposure standard - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Trans-

RHEOBYK-405 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

portation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN