

BYK-370

Version 8

Revision Date 05/30/2024

Print Date 04/30/2026

SECTION 1. IDENTIFICATION

Product name : BYK-370

Manufacturer or supplier's detailsCompany : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.comE-mail address : BRIEF.BYK.NAFTA@altana.comEmergency telephone number : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Surface Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Serious eye damage : Category 1

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Specific target organ toxicity - repeated exposure : Category 2 (Kidney, Liver)

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

BYK-370

Version 8

Revision Date 05/30/2024

Print Date 04/30/2026

- Hazard statements : H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
- Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.
P281 Use personal protective equipment as required.
Response:
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P331 Do NOT induce vomiting.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
Storage:

BYK-370

Version 8

Revision Date 05/30/2024

Print Date 04/30/2026

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Solution of a polyester modified hydroxy functional polydimethylsiloxane

Hazardous components

Component	CAS-No.	Concentration (%)
Xylene	1330-20-7	>= 30 - < 60
Ethyl benzene	100-41-4	>= 10 - < 20
Solvent naphtha, petroleum, light aromatic	64742-95-6	>= 5 - < 10
Cyclohexanone	108-94-1	>= 5 - < 10
2-Phenoxyethanol	122-99-6	>= 5 - < 10
Octamethylcyclotetrasiloxane	556-67-2	>= 0.1 - < 1
Toluene	108-88-3	>= 0.1 - < 1

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Consult a physician.
 Show this safety data sheet to the doctor in attendance.
 Symptoms of poisoning may appear several hours later.
 Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
 If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician.
 If on skin, rinse well with water.
 If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
 In the case of contact with eyes, rinse immediately with plenty

BYK-370

Version 8

Revision Date 05/30/2024

Print Date 04/30/2026

If swallowed	of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. : Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: No information available.
Notes to physician	: Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon oxides silicone compounds formaldehyde
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains.

BYK-370

Version 8

Revision Date 05/30/2024

Print Date 04/30/2026

Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Keep away from oxidizing agents.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Xylene	1330-20-7	TWA	100 ppm 435 mg/m ³	OSHA Z-1
Xylene		STEL	150 ppm 655 mg/m ³	OSHA P0
Xylene		TWA	100 ppm 435 mg/m ³	OSHA P0
Xylene		TWA	100 ppm	ACGIH
Xylene		STEL	150 ppm	ACGIH

BYK-370

Version 8

Revision Date 05/30/2024

Print Date 04/30/2026

Ethyl benzene	100-41-4	TWA	20 ppm	ACGIH
Ethyl benzene		TWA	100 ppm 435 mg/m ³	OSHA Z-1
Ethyl benzene		TWA	100 ppm 435 mg/m ³	OSHA P0
Ethyl benzene		STEL	125 ppm 545 mg/m ³	OSHA P0
Cyclohexanone	108-94-1	TWA	20 ppm	ACGIH
Cyclohexanone		STEL	50 ppm	ACGIH
Cyclohexanone		TWA	50 ppm 200 mg/m ³	OSHA Z-1
Cyclohexanone		TWA	25 ppm 100 mg/m ³	NIOSH REL
Octamethylcyclotetrasiloxane	556-67-2	TWA	10 ppm	US WEEL
Toluene	108-88-3	TWA	20 ppm	ACGIH
Toluene		TWA	200 ppm	OSHA Z-2
Toluene		CEIL	300 ppm	OSHA Z-2
Toluene		Peak	500 ppm	OSHA Z-2
Toluene		TWA	100 ppm 375 mg/m ³	OSHA P0
Toluene		STEL	150 ppm 560 mg/m ³	OSHA P0

Hazardous components without workplace control parameters

Engineering measures : Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

 Hand protection
 Material : Impervious gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

 Eye protection : Eye wash bottle with pure water
 Tightly fitting safety goggles
 Wear face-shield and protective suit for abnormal processing problems.

 Skin and body protection : Impervious clothing
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

 Hygiene measures : When using do not eat or drink.
 When using do not smoke.
 Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

 Appearance : liquid
 Colour : light yellow

BYK-370

Version 8

Revision Date 05/30/2024

Print Date 04/30/2026

Odour	: aromatic
Odour Threshold	: No data available
pH	: 6, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-value indicator
Melting point/range	: < 32 °F (< 0 °C) Method: derived
Initial boiling point	: 278.60 °F (137.00 °C) Method: derived
Vapour pressure	: 5 hPa (68.00 °F (20.00 °C)) Method: derived
Flash point	: 77.00 °F (25.00 °C) Method: 48 (Abel-Pensky) DIN 51755
Upper explosion limit	: 9.40 %(V)
Lower explosion limit	: 1.00 %(V)
Evaporation rate	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 0.9200 g/cm ³ (68.00 °F (20.00 °C)) Method: 4 (20°C oscillating U-tube)
Bulk density	: Not applicable
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: > 392 °F (> 200 °C) Method: DIN 51 794/ DIN prEN 14 522
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available

BYK-370

Version 8

Revision Date 05/30/2024

Print Date 04/30/2026

Viscosity, kinematic : ca. 1 mm²/s (104 °F (40 °C))**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : No decomposition if stored and applied as directed.
Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.
Incompatible materials : Strong oxidizing agents
Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Skin Absorption
Inhalation
Eyes
Ingestion

Acute toxicity**Product:**Acute oral toxicity : Acute toxicity estimate : 4,357 mg/kg
Method: Calculation methodAcute inhalation toxicity : Acute toxicity estimate : 7821 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: Calculation methodAcute dermal toxicity : Acute toxicity estimate : 3,395 mg/kg
Method: Calculation method**Components:****1330-20-7 Xylene:**Acute oral toxicity : LD50 (Rat): 4,300 mg/kg
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)
GLP: noAcute inhalation toxicity : LC50 (Rat): 5000 ppm
Exposure time: 4 h

BYK-370

Version 8

Revision Date 05/30/2024

Print Date 04/30/2026

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg
LD50 (Rabbit): > 4,200 mg/kg
GLP: No information available.

100-41-4 Ethyl benzene:

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 5,510 mg/kg

64742-95-6 Solvent naphtha, petroleum, light aromatic:

Acute oral toxicity : LD50 (Rat): > 4,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 3670 ppm
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): > 3,480 mg/kg

122-99-6 2-Phenoxyethanol:

Acute oral toxicity : LD50 (Rat): 1,840 mg/kg
Method: OECD Test Guideline 401
GLP: no

Acute dermal toxicity : LD50 (Rabbit): 3,818 mg/kg

108-88-3 Toluene:

Acute oral toxicity : LD50 (Rat): 2,600 mg/kg

Skin corrosion/irritation**Product:**

Remarks: Extremely corrosive and destructive to tissue.

Components:**1330-20-7 Xylene:**

Species: Rabbit
Result: Moderate skin irritation

100-41-4 Ethyl benzene:

Species: Rabbit
Result: Moderate skin irritation

64742-95-6 Solvent naphtha, petroleum, light aromatic:

Species: Rabbit
Result: Moderate skin irritation

108-94-1 Cyclohexanone:

Species: Rabbit
Result: Moderate skin irritation

BYK-370

Version 8

Revision Date 05/30/2024

Print Date 04/30/2026

122-99-6 2-Phenoxyethanol:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

556-67-2 Octamethylcyclotetrasiloxane:

Species: Rabbit

Result: slight irritation

Serious eye damage/eye irritation**Product:**

Remarks: May cause irreversible eye damage.

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**1330-20-7 Xylene:**

Species: Rabbit

Result: Eye irritation

100-41-4 Ethyl benzene:

Species: Rabbit

Result: Moderate eye irritation

64742-95-6 Solvent naphtha, petroleum, light aromatic:

Species: Rabbit

Result: Eye irritation

108-94-1 Cyclohexanone:

Species: Rabbit

Result: Severe eye irritation

122-99-6 2-Phenoxyethanol:

Species: Rabbit

Result: Eye irritation

Method: OECD Test Guideline 405

556-67-2 Octamethylcyclotetrasiloxane:

Species: Rabbit

Result: Mild eye irritation

Respiratory or skin sensitisation**Product:**

Remarks: No data available

Components:**64742-95-6 Solvent naphtha, petroleum, light aromatic:**

BYK-370

Version 8

Revision Date 05/30/2024

Print Date 04/30/2026

Test Type: Maximisation Test
Exposure routes: Dermal
Species: Guinea pig
Method: OECD Test Guideline 406
Result: Does not cause skin sensitisation.

122-99-6 2-Phenoxyethanol:

Species: Guinea pig
Method: OECD Test Guideline 406
Result: Does not cause skin sensitisation.

556-67-2 Octamethylcyclotetrasiloxane:

Species: Guinea pig
Method: OECD Test Guideline 406
Result: Does not cause skin sensitisation.
GLP: yes

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity**Product:**

Remarks: No data available

IARC

Group 2B: Possibly carcinogenic to humans

Ethyl benzene

100-41-4

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Components:

BYK-370

Version 8

Revision Date 05/30/2024

Print Date 04/30/2026

122-99-6 2-Phenoxyethanol:Effects on foetal
development

: Species: Rat
Application Route: Oral
Duration of Single Treatment: 14 d
General Toxicity Maternal: No observed adverse effect level:
300 mg/kg body weight
Teratogenicity: No observed adverse effect level: 1,000 mg/kg
body weight
Method: OECD Test Guideline 414

Species: Rabbit
Application Route: Dermal
Duration of Single Treatment: 14 d
General Toxicity Maternal: No observed adverse effect level:
300 mg/kg body weight
Teratogenicity: No observed adverse effect level: 600 mg/kg
body weight

STOT - single exposure**Product:**

Remarks: No data available

STOT - repeated exposure**Product:**

Remarks: No data available

Repeated dose toxicity**Product:**

Remarks: Absorption of ingredients (solvents) by inhalation and/or repeated skin contact has caused injury to liver, kidney, brain, respiratory system, blood, and/or bone marrow in laboratory animals

Animal studies have shown some components to cause fetotoxic effects at dosage levels at or near maternally toxic levels.

Excessive inhalation of Xylene has caused hearing loss in laboratory animals. Hexane used in conjunction w/Xylene greatly increased this effect. Chronic skin contact w/Xylene has caused dermatitis. Ingestion of Ethanol can increase effects of overexposure to Xylene.

Inhalation of Naphtha has caused fetotoxic effects at maternally toxic doses in laboratory animals.

Ethylbenzene is an IARC Group 2B carcinogen based on animal studies (increased tumors in rats and mice).

The ACGIH has determined cyclohexanone is an animal carcinogen. The relevance to humans is unknown.

Cumene is an IARC 2B and NTP Group 2 Carcinogen. Cumene has caused tumors in rats and mice (lung, liver and kidney). Proposed cancer causing mechanisms for lung and liver tumors are similar to human metabolic pathways. The relevance of kidney tumors in humans is uncertain.

BYK-370

Version 8

Revision Date 05/30/2024

Print Date 04/30/2026

Components:
122-99-6 2-Phenoxyethanol:

Species: Rat

NOAEL: 700 mg/kg

Application Route: Oral

Method: OECD Test Guideline 408

Species: Rat

NOAEL: 0.0482 mg/l

Application Route: Inhalation

Method: OECD Test Guideline 412

Target Organs: Respiratory organs

Aspiration toxicity
Product:

No data available

Components:
64742-95-6 Solvent naphtha, petroleum, light aromatic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Experience with human exposure
Product:

Inhalation:

Symptoms:

High concentrations of vapors may be irritating to the respiratory tract. May cause headaches, dizziness, nausea and vomiting. May cause CNS depression (drowsiness, loss of coordination and fatigue).

Skin contact:

Symptoms:

Contact will probably cause irritation.

Eye contact:

Symptoms:

Contact will probably cause severe irritation.

Ingestion:

Symptoms:

May irritate the digestive tract and cause same symptoms as inhalation; high dosages may result in unconsciousness.

BYK-370

Version 8

Revision Date 05/30/2024

Print Date 04/30/2026

Further information**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Toxicity to fish :
Remarks: No data available

Persistence and degradability**Product:**

Biodegradability : Remarks: No data available

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

EPA Hazardous Waste Code(s) : D001: Ignitable

D018: Benzene

BYK-370

Version 8

Revision Date 05/30/2024

Print Date 04/30/2026

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION
International Regulations
IATA-DGR

UN/ID No. : UN 1993
Proper shipping name : Flammable liquid, n.o.s.
(Xylene, Solvent naphtha)
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(XYLENE, SOLVENT NAPHTHA)
Marine Pollutant : (Siloxanes)
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes
Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations
49 CFR

UN/ID/NA number : UN 1993
Proper shipping name : Flammable liquids, n.o.s.
(Xylene, Solvent naphtha)
Class : 3
Packing group : III
Labels : FLAMMABLE LIQUID

BYK-370

Version 8

Revision Date 05/30/2024

Print Date 04/30/2026

ERG Code : 128
 Marine pollutant : yes (Siloxanes)
 Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples

SECTION 15. REGULATORY INFORMATION
EPCRA - Emergency Planning and Community Right-to-Know Act
US. EPA CERCLA Hazardous Substances (40 CFR 302)

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	250

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Xylene	1330-20-7	40.0 %
Ethyl benzene	100-41-4	16.4 %
2-Phenoxyethanol	122-99-6	5 %

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

Xylene	1330-20-7	40.0 %
Ethyl benzene	100-41-4	16.4 %
2-Phenoxyethanol	122-99-6	5 %

BYK-370

Version 8

Revision Date 05/30/2024

Print Date 04/30/2026

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM1 Intermediate or Final VOC's (40 CFR 60.489):

Xylene	1330-20-7	40.0 %
Ethyl benzene	100-41-4	16.4 %
Cyclohexanone	108-94-1	5 %
2-Phenoxyethanol	122-99-6	5 %

Non-volatile (Wt) : 23.5 - 26.5 %
 Method: 22 (10min/150°C)
 DIN EN ISO 3251
 Non-volatile information is not a specification.

Massachusetts Right To Know

Xylene	1330-20-7
Ethyl benzene	100-41-4
Cyclohexanone	108-94-1
Benzene	71-43-2

Pennsylvania Right To Know

Xylene	1330-20-7
Polyester modified dimethylpolysiloxane	-
Ethyl benzene	100-41-4
Solvent naphtha, petroleum, light aromatic	64742-95-6
Cyclohexanone	108-94-1
2-Phenoxyethanol	122-99-6
Toluene	108-88-3
Cumene	98-82-8

New Jersey Right To Know

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : 800963-5190

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including Ethyl benzene, Cumene, Benzene, Naphthalene, which is/are known to the State of California to cause cancer, and Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

Section 5a : No substances are subject to a Significant New Use Rule.

BYK-370

Version 8

Revision Date 05/30/2024

Print Date 04/30/2026

Section 4 / 12(b) : No substances are subject to TSCA 12(b) export notification requirements.

DSL : We certify that all of the components of this product are listed on the DSL.

SECTION 16. OTHER INFORMATION

Revision Date : 05/30/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.