

BYK-A 555 SG

Version 1

Revision Date 01/07/2026

Print Date 05/21/2026

SECTION 1. IDENTIFICATION

Product name : BYK-A 555 SG

Manufacturer or supplier's detailsCompany : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.comE-mail address : BRIEF.BYK.NAFTA@altana.comEmergency telephone number : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Air Release Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3

Carcinogenicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.
P233 Keep container tightly closed.

BYK-A 555 SG

Version 1

Revision Date 01/07/2026

Print Date 05/21/2026

P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : solution of polyolefin

Hazardous components

Component	CAS-No.	Concentration (%)
Solvent naphtha, petroleum, light aromatic	64742-95-6	>= 60 - < 80
Cumene	98-82-8	>= 1 - < 5

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

BYK-A 555 SG

Version 1

Revision Date 01/07/2026

Print Date 05/21/2026

	<p>Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.</p>
If inhaled	<p>: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.</p>
In case of skin contact	<p>: If on skin, rinse well with water. If on clothes, remove clothes.</p>
In case of eye contact	<p>: Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.</p>
If swallowed	<p>: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.</p>

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	<p>: Alcohol-resistant foam Carbon dioxide (CO₂) Dry chemical</p>
Unsuitable extinguishing media	<p>: High volume water jet</p>
Specific hazards during firefighting	<p>: Cool closed containers exposed to fire with water spray. Will not explode on mechanical impact.</p> <p>Do not allow run-off from fire fighting to enter drains or water courses.</p>
Hazardous combustion products	<p>: Carbon oxides</p>
Further information	<p>: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.</p>
Special protective equipment for firefighters	<p>: Wear self-contained breathing apparatus for firefighting if necessary.</p>

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	<p>: Use personal protective equipment. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.</p>
---	---

BYK-A 555 SG

Version 1

Revision Date 01/07/2026

Print Date 05/21/2026

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Cumene	98-82-8	TWA	5 ppm	ACGIH
Cumene		TWA	50 ppm 245 mg/m ³	OSHA Z-1
Cumene		TWA	50 ppm 245 mg/m ³	OSHA P0

Hazardous components without workplace control parameters

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an

BYK-A 555 SG

Version 1

Revision Date 01/07/2026

Print Date 05/21/2026

Hand protection	approved filter.
Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Colour	: light yellow
Odour	: aromatic
Odour Threshold	: No data available
pH	: 7, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-value indicator
Melting point/ range	: < 32 °F (< 0 °C) Method: derived
Initial boiling point	: 320.00 °F (160.00 °C) Method: derived
Vapour pressure	: 5 hPa (68 °F (20 °C)) Method: derived
Flash point	: 109.40 °F (43.00 °C) Method: 48 (Abel-Pensky) DIN 51755
Upper explosion limit	: 7.50 %(V)
Lower explosion limit	: 1.00 %(V)
Evaporation rate	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 0.8800 g/cm ³ (68.00 °F (20.00 °C)) Method: 4 (20°C oscillating U-tube)

BYK-A 555 SG

Version 1

Revision Date 01/07/2026

Print Date 05/21/2026

Bulk density	:	Not applicable
Solubility(ies)	:	
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Ignition temperature	:	> 392 °F (> 200 °C) Method: DIN 51 794/ DIN prEN 14 522
Thermal decomposition	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	27.000 mm ² /s (68.00 °F (20.00 °C)) 21.500 mm ² /s (104.00 °F (40.00 °C))
Surface tension	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Acids Strong oxidizing agents
Hazardous decomposition products	:	None expected

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Ingestion
Eye contact
Skin contact

BYK-A 555 SG

Version 1

Revision Date 01/07/2026

Print Date 05/21/2026

Acute toxicity**Product:**

Acute oral toxicity : Acute toxicity estimate : 4,157 mg/kg
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 4,157 mg/kg
Method: Calculation method

Components:**64742-95-6 Solvent naphtha, petroleum, light aromatic:**

Acute oral toxicity : LD50 (Rat): > 4,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 3670 ppm
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): > 3,480 mg/kg

98-82-8 Cumene:

Acute oral toxicity : LD50 (Rat): 1,400 mg/kg

Acute inhalation toxicity : LC50 : Remarks: No data available

Acute dermal toxicity : LD50 : Remarks: No data available

Skin corrosion/irritation**Product:**

Remarks: No data available

Components:**64742-95-6 Solvent naphtha, petroleum, light aromatic:**

Species: Rabbit

Result: Moderate skin irritation

Serious eye damage/eye irritation**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**64742-95-6 Solvent naphtha, petroleum, light aromatic:**

Species: Rabbit

Result: Eye irritation

Respiratory or skin sensitisation**Product:**

BYK-A 555 SG

Version 1

Revision Date 01/07/2026

Print Date 05/21/2026

Remarks: No data available

Components:**64742-95-6 Solvent naphtha, petroleum, light aromatic:**

Test Type: Maximisation Test

Exposure routes: Dermal

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity**Product:**

Remarks: No data available

IARC

Group 2B: Possibly carcinogenic to humans

Cumene

98-82-8

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

Reasonably anticipated to be a human carcinogen

Cumene

98-82-8

Reproductive toxicity**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure**Product:**

Remarks: No data available

STOT - repeated exposure**Product:**

BYK-A 555 SG

Version 1

Revision Date 01/07/2026

Print Date 05/21/2026

Remarks: No data available

Repeated dose toxicity**Product:**

Remarks: No data available

Aspiration toxicity**Product:**

No data available

Components:**64742-95-6 Solvent naphtha, petroleum, light aromatic:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Experience with human exposure**Product:**

Inhalation:

Symptoms:	High concentrations of vapors may be irritating to the respiratory tract. May cause headaches, dizziness, nausea and vomiting. May cause CNS depression (drowsiness, loss of coordination and fatigue).
-----------	---

Skin contact:

Symptoms:	Contact will probably cause irritation.
-----------	---

Eye contact:

Symptoms:	Contact will probably cause irritation.
-----------	---

Ingestion:

Symptoms:	Ingestion may irritate the digestive tract; high dosages may cause CNS depression.
-----------	--

Further information**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

BYK-A 555 SG

Version 1

Revision Date 01/07/2026

Print Date 05/21/2026

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity
Product:

Toxicity to fish :
Remarks: No data available

Toxicity to daphnia and other :
aquatic invertebrates : Remarks: No data available

Persistence and degradability
Product:

Biodegradability : Remarks: No data available

Bioaccumulative potential
Product:

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological : No data available
information

SECTION 13. DISPOSAL CONSIDERATIONS
Disposal methods

EPA Hazardous Waste : D018: Benzene
Code(s) : D001: Ignitable

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

BYK-A 555 SG

Version 1

Revision Date 01/07/2026

Print Date 05/21/2026

Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

UN/ID No. : UN 1268
Proper shipping name : Petroleum distillates, n.o.s.
(Solvent naphtha)
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1268
Proper shipping name : PETROLEUM DISTILLATES, N.O.S.
(Solvent naphtha)
Marine Pollutant : (Solvent naphtha)
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes
Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

UN/ID/NA number : UN 1268
Proper shipping name : Petroleum distillates, n.o.s.
(Solvent naphtha)
Class : 3
Packing group : III
Labels : FLAMMABLE LIQUID
ERG Code : 128
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

BYK-A 555 SG

Version 1

Revision Date 01/07/2026

Print Date 05/21/2026

EPCRA - Emergency Planning and Community Right-to-Know Act
US. EPA CERCLA Hazardous Substances (40 CFR 302)

Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

1,2,4-Trimethylbenzene	95-63-6	21.8 %
Cumene	98-82-8	1.5 %

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

Cumene	98-82-8	1.5 %
--------	---------	-------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

Cumene	98-82-8	1.5 %
--------	---------	-------

Non-volatile (Wt) : 36 - 40 %
 Method: 22 (10min/150°C)
 DIN EN ISO 3251
 Non-volatile information is not a specification.

BYK-A 555 SG

Version 1

Revision Date 01/07/2026

Print Date 05/21/2026

US State Regulations
Massachusetts Right To Know

Cumene	98-82-8
--------	---------

Pennsylvania Right To Know

Solvent naphtha, petroleum, light aromatic	64742-95-6
Polymer	-
Cumene	98-82-8
Naphthalene	91-20-3
Ethyl benzene	100-41-4

New Jersey Right To Know

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : 800963-6463

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including Cumene, Naphthalene, Ethyl benzene, Benzene, which is/are known to the State of California to cause cancer, and Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

US TSCA	: All substances listed as active on the TSCA inventory
Section 5a	: No substances are subject to a Significant New Use Rule.
Section 4 / 12(b)	: No substances are subject to TSCA 12(b) export notification requirements.
CA. DSL	: We certify that all of the components of this product are listed on the DSL.

SECTION 16. OTHER INFORMATION

Revision Date : 01/07/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.