

BYK GS-34

Modified alkoxyated nonylphenol formaldehyde resin used in demulsifier formulations for dewatering and desalting crude oil and natural gas condensates.

Product Data

Composition

Alkoxyated nonylphenol formaldehyde resin

Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

| | |
|-----------------------------------|---------------------|
| Appearance: | Dark viscous liquid |
| Flash point: | > 66 °C |
| Viscosity (25 °C): | 7000 mPa·s |
| Relative solubility number (RSN): | 15 |

Applications

Oil & Gas Industry

Special Features and Benefits

BYK GS-34 is a modified alkoxyated nonylphenol formaldehyde resin used in demulsifier formulations for dewatering and desalting crude oil and natural gas condensates. BYK GS-34 is typically blended with other demulsifier bases and/or inhibitors and diluted with aromatic solvents or alcohols. BYK GS-34 is an effective water dropper and interphase treaters; it is cost effective and highly concentrated.

Recommended Use

| | |
|---------------------------|---|
| Demulsifier/water dropper | ■ |
| Desalting | ■ |

■ especially recommended □ recommended

Recommended Levels

Dosage range will typically range from 5-500 ppm evaluated in laboratory or field tests.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.



Additive Guide



BYK-Chemie GmbH
P.O. Box 10 02 45
46462 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735

info@byk.com
www.byk.com

ACTAL®, ADD-MAX®, ADD-VANCE®, ADJUST®, ADVITROL®, ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK®-DYNWET®, BYK®-MAX®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKO2BLOCK®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOÍSITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITÉ®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, MINERAL COLLOID®, MINERPOL®, NANOBYK®, OPTIBENT®, OPTIFLO®, OPTIGEL®, PAPERBYK®, PERMONT®, POLYAD®, PRIEX®, PURE THIX®, RECYCLOBLEND®, RECYCLOBYK®, RECYCLOSSORB®, RECYCLOSTAB®, RHEOBYK®, RHEOCIN®, RHEOTIX®, SCONA®, SILBYK®, TIXOGEL®, VISCOBYK® and Y 25® are registered trademarks of the BYK group.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions – Printed in Germany