

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : BYK-W 908
Product code : 000000000000114851

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Wetting & Dispersing Additive

1.3 Details of the supplier of the safety data sheet

Company : BYK-Chemie GmbH
Abelstrasse 45
46483 Wesel
Telephone : +49 281 670-0
Telefax : +49 281 65735

Information : Regulatory Affairs
Telephone : +49 281 670-23532
Telefax : +49 281 670-23533
E-mail address : GHS.BYK@altana.com

1.4 Emergency telephone number

+44 1235 239670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H226 Flammable liquid and vapour. H315 Causes skin irritation. H318 Causes serious eye damage. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist or vapours. P264 Wash skin thoroughly after handling. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. Response: P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

- 78-83-1 iso-butanol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : solution of modified polyester-polyether

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
iso-butanol	78-83-1 201-148-0 01-2119484609-23	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	>= 50 - <= 100
1-methoxy-2-propanol	107-98-2 203-539-1 01-2119457435-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 25 - < 30

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	: No information available.
Risks	: Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	: No information available.
-----------	-----------------------------

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon oxides Nitrogen oxides (NO _x)

5.3 Advice for firefighters

Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	: Use personal protective equipment. Remove all sources of ignition. Evacuate personnel to safe areas.
----------------------	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
iso-butanol	78-83-1	TWA	50 ppm 154 mg/m3	GB EH40
		STEL	75 ppm 231 mg/m3	GB EH40
1-methoxy-2-propanol	107-98-2	TWA	100 ppm 375 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	150 ppm 568 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	100 ppm 375 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	150 ppm 560 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
iso-butanol	Workers	Inhalation	Long-term local effects	310 mg/m3
	Consumers	Ingestion	Long-term systemic effects	25 mg/kg
	Consumers	Inhalation	Long-term local effects	55 mg/m3
1-methoxy-2-propanol	Workers	Inhalation	Acute local effects	553,5 mg/m3
	Workers	Skin contact	Long-term systemic effects	50,6 mg/kg
	Workers	Inhalation	Long-term systemic effects	369 mg/m3
	Consumers	Skin contact	Long-term systemic effects	18,1 mg/kg
	Consumers	Inhalation	Long-term systemic	43,9 mg/m3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

			effects	
	Consumers	Ingestion	Long-term systemic effects	3,3 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
iso-butanol	Fresh water	0,4 mg/l
	Marine water	0,04 mg/l
	Fresh water sediment	1,56 mg/kg
	Marine sediment	0,156 mg/kg
	Soil	0,0765 mg/kg
	Sewage treatment plant	10 mg/l
1-methoxy-2-propanol	Intermittent releases	11 mg/l
	Fresh water	10 mg/l
	Marine water	1 mg/l
	Intermittent releases	100 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	41,6 mg/kg
	Marine sediment	4,17 mg/kg
	Soil	2,47 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection
Material : butyl-rubber
Break through time : > 480 min
Glove thickness : >= 0,5 mm

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Environmental exposure controls

General advice : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Physical state	:	liquid
Colour	:	yellow - brown
Odour	:	characteristic
Melting point/ range	:	ca. < 0 °C Method: derived
Boiling point/boiling range	:	107 °C Method: derived
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	31 °C Method: 48 (Abel-Pensky) DIN 51755
Auto-ignition temperature	:	> 200 °C Method: DIN 51794
Decomposition temperature	:	No data available
pH	:	7 (20 °C) Concentration: 1 % Method: Universal pH-value indicator
Viscosity Viscosity, dynamic	:	5 mPa.s Method: P/K 20°C
Solubility(ies) Water solubility	:	immiscible
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	ca. 12 hPa (20 °C) Method: derived
Density	:	0,866 g/cm ³ (20 °C, 1.013 hPa) Method: 4 (20°C oscillating U-tube)
Bulk density	:	Not applicable
Relative vapour density	:	No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

9.2 Other information

Flammability (liquids) : Sustains combustion

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents
Strong acids

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Remarks: No data available

Components:

iso-butanol:

Acute oral toxicity : LD50 (Rat, male): > 2.830 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male): > 2.000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

1-methoxy-2-propanol:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Acute oral toxicity : LD50 (Rat, male and female): 4.016 mg/kg
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2.000 mg/kg
Method: Directive 67/548/EEC, Annex V, B.3.
GLP: yes

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May irritate skin.
May cause skin irritation in susceptible persons.

Components:

iso-butanol:

Species : Rabbit
Result : Skin irritation

1-methoxy-2-propanol:

Species : Rabbit
Method : Directive 67/548/EEC, Annex V, B.4.
Result : No skin irritation
GLP : yes

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:

iso-butanol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Eye irritation
GLP : yes

1-methoxy-2-propanol:

Species : Rabbit
Method : Directive 67/548/EEC, Annex V, B.5.
Result : No eye irritation
GLP : yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Product:

Remarks : No data available

Components:

iso-butanol:

Test Type : Maximisation Test
Exposure routes : Dermal
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.

1-methoxy-2-propanol:

Test Type : Maximisation Type
Exposure routes : Dermal
Species : Guinea pig
Method : Directive 67/548/EEC, Annex V, B.6.
Result : Does not cause skin sensitisation.
GLP : yes

Germ cell mutagenicity

Not classified due to lack of data.

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Not classified due to lack of data.

Product:

Remarks : No data available

Reproductive toxicity

Not classified due to lack of data.

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

STOT - single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

Product:

Remarks : No data available

STOT - repeated exposure

Not classified due to lack of data.

Product:

Remarks : No data available

Repeated dose toxicity

Product:

Remarks : No data available

Aspiration toxicity

Not classified due to lack of data.

Product:

No data available

Components:

iso-butanol:

No aspiration toxicity classification

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Components:

iso-butanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1.430 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 1.100 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 1.799 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 20 mg/l
End point: Reproduction
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test

1-methoxy-2-propanol:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 6.812 mg/l
Exposure time: 96 h
Test Type: static test
Method: DIN 38412
GLP: no

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

iso-butanol:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301D

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

1-methoxy-2-propanol:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301
GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

iso-butanol:

Partition coefficient: n-octanol/water : log Pow: 1
Method: OECD Test Guideline 117
GLP: yes

1-methoxy-2-propanol:

Partition coefficient: n-octanol/water : log Pow: 0,37 (20 °C)
pH: 6,8
Method: OECD Test Guideline 117
GLP: No information available.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- | | | |
|------------------------|---|--|
| Product | : | Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company. |
| Contaminated packaging | : | Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum. |

SECTION 14: Transport information

14.1 UN number or ID number

- | | | |
|------|---|---------|
| ADN | : | UN 1987 |
| ADR | : | UN 1987 |
| RID | : | UN 1987 |
| IMDG | : | UN 1987 |
| IATA | : | UN 1987 |

14.2 UN proper shipping name

- | | | |
|------|---|--|
| ADN | : | ALCOHOLS, N.O.S.
(Isobutanol, 1-Methoxy-2-propanol) |
| ADR | : | ALCOHOLS, N.O.S.
(Isobutanol, 1-Methoxy-2-propanol) |
| RID | : | ALCOHOLS, N.O.S.
(Isobutanol, 1-Methoxy-2-propanol) |
| IMDG | : | ALCOHOLS, N.O.S.
(Isobutanol, 1-Methoxy-2-propanol) |
| IATA | : | Alcohols, n.o.s.
(Isobutanol, 1-Methoxy-2-propanol) |

14.3 Transport hazard class(es)

- | | | |
|------|---|---|
| ADN | : | 3 |
| ADR | : | 3 |
| RID | : | 3 |
| IMDG | : | 3 |
| IATA | : | 3 |

14.4 Packing group

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

ADN

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : D/E

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-D

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries must be considered:: Number on list 3
		Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	P5c	FLAMMABLE LIQUIDS

15.2 Chemical safety assessment

For further information see eSDS.

SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H226	:	Flammable liquid and vapour.
H315	:	Causes skin irritation.
H318	:	Causes serious eye damage.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.

Full text of other abbreviations

Eye Dam.	:	Serious eye damage
Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; BGW - Biological Limit Values; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); LSPN - List of Hazardous Notified Substances (Chile); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Dam. 1	H318
STOT SE 3	H336
STOT SE 3	H335

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Annex: Exposure Scenarios

Table of Contents

Number	Title
ES 1	Use as an intermediate; Industrial uses (SU3).
ES 2	Formulation & (re)packing of substances and mixtures; Industrial uses (SU3).
ES 3	Distribution of substance; Industrial uses (SU3).
ES 4	Use in coatings; Industrial uses (SU3).
ES 5	Use in coatings; Professional uses (SU22).
ES 6	Cleaning; Industrial uses (SU3).
ES 7	Cleaning; Professional uses (SU22).
ES 8	Use in laboratories; Professional uses (SU22).
ES 9	Polymerisation; Industrial uses (SU3).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

ES 1: Use as an intermediate; Industrial uses (SU3).

1.1. Title section

Exposure Scenario name	: Use as an intermediate
Structured Short Title	: Use as an intermediate; Industrial uses (SU3).

Environment		
CS 1	Use of intermediate	ERC6a
Worker		
CS 2	Use in closed process, no likelihood of exposure	PROC1
CS 3	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC2
CS 4	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	PROC3
CS 5	Chemical production where opportunity for exposure arises	PROC4
CS 6	Transfer of substance or mixture (charging/discharging) at non dedicated-facilities	PROC8a
CS 7	Transfer of substance or mixture (charging/discharging) at dedicated facilities	PROC8b
CS 8	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)	PROC9

1.2. Conditions of use affecting exposure

1.2.1. Control of environmental exposure: Use of intermediate (ERC6a)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount per site	: 20124 t
Maximum daily site tonnage	: 61 t

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Technical and organisational conditions and measures	
Do not apply industrial sludge to natural soils.	
Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant
STP effluent	: 2.000 m3/d

1.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

1.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

Other conditions affecting workers exposure

Indoor or outdoor use : Covers indoor and outdoor use.

1.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics

Covers concentrations up to 100 %

Physical form of product : Liquid

Amount used (or contained in articles), frequency and duration of use/exposure

Use frequency : Covers exposure up to 480 min/day

Technical and organisational conditions and measures

Provide a basic standard of general ventilation (1 to 3 air changes per hour).

Other conditions affecting workers exposure

Indoor or outdoor use : Covers indoor and outdoor use.

1.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics

Covers concentrations up to 100 %

Physical form of product : Liquid

Amount used (or contained in articles), frequency and duration of use/exposure

Use frequency : Covers exposure up to 480 min/day

Technical and organisational conditions and measures

Provide a basic standard of general ventilation (1 to 3 air changes per hour).

Other conditions affecting workers exposure

Indoor or outdoor use : Covers indoor and outdoor use.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

1.2.6. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

1.2.7. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

1.2.8. Control of worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

1.3. Exposure estimation and reference to its source

1.3.1. Environmental release and exposure: Use of intermediate (ERC6a)

Protection Target	Exposure estimate	RCR
Freshwater	0,079 mg/L	0,197
Freshwater sediment	0,306 mg/kg dry weight	0,197
Marine water	0,00787 mg/L	0,197
Marine sediment	0,031 mg/kg dry weight	0,196
Agricultural soil	0,000888 mg/kg dry weight	0,012
Sewage treatment plant	0,763 mg/L	0,076

1.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		0,031 mg/m ³	< 0,01
inhalative	systemic		0,031 mg/m ³	< 0,01

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

1.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

1.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		30,88 mg/m ³	0,1
inhalative	systemic		30,88 mg/m ³	0,1

1.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		61,77 mg/m ³	0,199
inhalative	systemic		61,77 mg/m ³	0,199

1.3.6. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

1.3.7. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		3,861 mg/m ³	0,012
inhalative	systemic		3,861 mg/m ³	0,012

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

1.3.8. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Data refer to lead substance.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

ES 2: Formulation & (re)packing of substances and mixtures; Industrial uses (SU3).

2.1. Title section

Exposure Scenario name	: Formulation & (re)packing of substances and mixtures
Structured Short Title	: Formulation & (re)packing of substances and mixtures; Industrial uses (SU3).

Environment		
CS 1	Formulation into mixture	ERC2
Worker		
CS 2	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions	PROC1
CS 3	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC2
CS 4	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	PROC3
CS 5	Chemical production where opportunity for exposure arises	PROC4
CS 6	Mixing or blending in batch processes	PROC5
CS 7	Transfer of substance or mixture (charging/discharging) at non dedicated-facilities	PROC8a
CS 8	Transfer of substance or mixture (charging/discharging) at dedicated facilities	PROC8b
CS 9	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)	PROC9
CS 10	Use in closed process, no likelihood of exposure	PROC1

2.2. Conditions of use affecting exposure

2.2.1. Control of environmental exposure: Formulation into mixture (ERC2)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Liquid

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount per site	: 10915 t
Maximum daily site tonnage	: 36,4 t
Technical and organisational conditions and measures	
Do not apply industrial sludge to natural soils.	
Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant
STP effluent	: 2.000 m3/d

2.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

2.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

2.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

2.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

Other conditions affecting workers exposure

Indoor or outdoor use : Covers indoor and outdoor use.

2.2.6. Control of worker exposure: Mixing or blending in batch processes (PROC5)

Product (article) characteristics

Covers concentrations up to 100 %

Physical form of product : Liquid

Amount used (or contained in articles), frequency and duration of use/exposure

Use frequency : Covers exposure up to 480 min/day

Technical and organisational conditions and measures

Provide a basic standard of general ventilation (1 to 3 air changes per hour).

Dermal - minimum efficiency of 0 %

Inhalation - minimum efficiency of 90 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

2.2.7. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Product (article) characteristics

Covers concentrations up to 100 %

Physical form of product : Liquid

Amount used (or contained in articles), frequency and duration of use/exposure

Use frequency : Covers exposure up to 480 min/day

Technical and organisational conditions and measures

Provide a basic standard of general ventilation (1 to 3 air changes per hour).

Dermal - minimum efficiency of 0 %

Inhalation - minimum efficiency of 90 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

2.2.8. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

2.2.9. Control of worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

2.2.10. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

2.3. Exposure estimation and reference to its source

2.3.1. Environmental release and exposure: Formulation into mixture (ERC2)

Protection Target	Exposure estimate	RCR
Freshwater	0,048 mg/L	0,12
Freshwater sediment	0,176 mg/kg dry weight	0,12
Marine water	0,0048 mg/L	0,12
Marine sediment	0,019 mg/kg dry weight	0,12
Agricultural soil	0,00867 mg/kg dry weight	0,113
Sewage treatment plant	0,455 mg/L	0,046

2.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		0,031 mg/m ³	< 0,01
inhalative	systemic		0,031 mg/m ³	< 0,01

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

2.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

2.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		30,88 mg/m ³	0,1
inhalative	systemic		30,88 mg/m ³	0,1

2.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		61,77 mg/m ³	0,199
inhalative	systemic		61,77 mg/m ³	0,199

2.3.6. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

2.3.7. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

2.3.8. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		3,861 mg/m ³	0,012
inhalative	systemic		3,861 mg/m ³	0,012

2.3.9. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

2.3.10. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		30,88 mg/m ³	0,1
inhalative	systemic		30,88 mg/m ³	0,1

2.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Data refer to lead substance.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

ES 3: Distribution of substance; Industrial uses (SU3).

3.1. Title section

Exposure Scenario name	: Distribution of substance
Structured Short Title	: Distribution of substance; Industrial uses (SU3).

Environment		
CS 1	Formulation into mixture	ERC2
Worker		
CS 2	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions	PROC1
CS 3	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC2
CS 4	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	PROC3
CS 5	Chemical production where opportunity for exposure arises	PROC4
CS 6	Transfer of substance or mixture (charging/discharging) at non dedicated-facilities	PROC8a
CS 7	Transfer of substance or mixture (charging/discharging) at dedicated facilities	PROC8b
CS 8	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)	PROC9
CS 9	Use as laboratory reagent	PROC15

3.2. Conditions of use affecting exposure

3.2.1. Control of environmental exposure: Formulation into mixture (ERC2)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount per site	: 42577 t

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

Maximum daily site tonnage	: 0,028 t
Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant
STP effluent	: 2.000 m3/d

3.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

3.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Indoor or outdoor use	: Covers indoor and outdoor use.
-----------------------	----------------------------------

3.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

3.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

3.2.6. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

3.2.7. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

3.2.8. Control of worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Product (article) characteristics

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

3.2.9. Control of worker exposure: Use as laboratory reagent (PROC15)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

3.3. Exposure estimation and reference to its source

3.3.1. Environmental release and exposure: Formulation into mixture (ERC2)

Protection Target	Exposure estimate	RCR
Freshwater	0,0025 mg/L	< 0,01
Freshwater sediment	0,00972 mg/kg dry weight	< 0,01

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Marine water	0,000246 mg/L	< 0,01
Marine sediment	0,000957 mg/kg dry weight	< 0,01
Agricultural soil	0,00344 mg/kg dry weight	0,045
Sewage treatment plant	0,0000177 mg/L	< 0,01

3.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		0,031 mg/m ³	< 0,01
inhalative	systemic		0,031 mg/m ³	< 0,01

3.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

3.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		30,88 mg/m ³	0,1
inhalative	systemic		30,88 mg/m ³	0,1

3.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		61,77 mg/m ³	0,199
inhalative	systemic		61,77 mg/m ³	0,199

3.3.6. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

3.3.7. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		3,861 mg/m ³	0,012
inhalative	systemic		3,861 mg/m ³	0,012

3.3.8. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

3.3.9. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		30,88 mg/m ³	0,1
inhalative	systemic		30,88 mg/m ³	0,1

3.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Data refer to lead substance.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

ES 4: Use in coatings; Industrial uses (SU3).

4.1. Title section

Exposure Scenario name	: Use in coatings
Structured Short Title	: Use in coatings; Industrial uses (SU3).

Environment		
CS 1	Use of non-reactive processing aid at industrial site (no inclusion into or ERC4 onto article)	
Worker		
CS 2	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions	PROC1
CS 3	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC2
CS 4	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	PROC3
CS 5	Chemical production where opportunity for exposure arises	PROC4
CS 6	Mixing or blending in batch processes	PROC5
CS 7	Industrial spraying	PROC7
CS 8	Transfer of substance or mixture (charging/discharging) at non dedicated-facilities	PROC8a
CS 9	Transfer of substance or mixture (charging/discharging) at dedicated facilities	PROC8b
CS 10	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)	PROC9
CS 11	Roller application or brushing	PROC10
CS 12	Treatment of articles by dipping and pouring	PROC13
CS 13	Use as laboratory reagent	PROC15

4.2. Conditions of use affecting exposure

4.2.1. Control of environmental exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount per site	: 3116 t
Maximum daily site tonnage	: 10,39 t
Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant
STP effluent	: 2.000 m3/d

4.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

4.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

4.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

4.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

4.2.6. Control of worker exposure: Mixing or blending in batch processes (PROC5)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

4.2.7. Control of worker exposure: Industrial spraying (PROC7)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Ensure the ventilation system is regularly maintained and tested. Clean equipment and the work area every day.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use
Room size	: > 1000 m3
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Ensure that the distance from worker to task is greater than 1 m. Ensure regular inspection, cleaning and maintenance of equipment and machines. Ensure that a spraying booth is used.	

4.2.8. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

4.2.9. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

4.2.10. Control of worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

4.2.11. Control of worker exposure: Roller application or brushing (PROC10)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

4.2.12. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

4.2.13. Control of worker exposure: Use as laboratory reagent (PROC15)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

4.3. Exposure estimation and reference to its source

4.3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Protection Target	Exposure estimate	RCR
Freshwater	0,00249 mg/L	< 0,01
Freshwater sediment	0,00971 mg/kg dry weight	< 0,01
Marine water	0,000246 mg/L	< 0,01
Marine sediment	0,000956 mg/kg dry weight	< 0,01
Agricultural soil	0,0089 mg/kg dry weight	0,116
Sewage treatment plant	0 mg/L	< 0,01

4.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		0,031 mg/m ³	< 0,01
inhalative	systemic		0,031 mg/m ³	< 0,01

4.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

4.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		30,88 mg/m ³	0,1
inhalative	systemic		30,88 mg/m ³	0,1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

4.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		61,77 mg/m ³	0,199
inhalative	systemic		61,77 mg/m ³	0,199

4.3.6. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

4.3.7. Worker exposure: Industrial spraying (PROC7)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		0 mg/m ³	< 0,01
inhalative	systemic		0 mg/m ³	< 0,01

4.3.8. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

4.3.9. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		3,861 mg/m ³	0,012
inhalative	systemic		3,861 mg/m ³	0,012

4.3.10. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

4.3.11. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

4.3.12. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

4.3.13. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		30,88 mg/m ³	0,1
inhalative	systemic		30,88 mg/m ³	0,1

4.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Data refer to lead substance.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

ES 5: Use in coatings; Professional uses (SU22).

5.1. Title section

Exposure Scenario name	: Use in coatings
Structured Short Title	: Use in coatings; Professional uses (SU22).

Environment		
CS 1	Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)	ERC8d
Worker		
CS 2	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions	PROC1
CS 3	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC2
CS 4	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	PROC3
CS 5	Chemical production where opportunity for exposure arises	PROC4
CS 6	Mixing or blending in batch processes	PROC5
CS 7	Transfer of substance or mixture (charging/discharging) at non dedicated-facilities	PROC8a
CS 8	Transfer of substance or mixture (charging/discharging) at dedicated facilities	PROC8b
CS 9	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)	PROC9
CS 10	Roller application or brushing	PROC10
CS 11	Non-industrial spraying	PROC11
CS 12	Treatment of articles by dipping and pouring	PROC13
CS 13	Use as laboratory reagent	PROC15
CS 14	Manual activities involving hand contact	PROC19

5.2. Conditions of use affecting exposure

5.2.1. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount for wide dispersive uses	: 0,2 kg
Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant

5.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

5.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

5.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

5.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

Other conditions affecting workers exposure

Indoor or outdoor use : Covers indoor and outdoor use.

5.2.6. Control of worker exposure: Mixing or blending in batch processes (PROC5)

Product (article) characteristics

Covers concentrations up to 100 %

Physical form of product : Liquid

Amount used (or contained in articles), frequency and duration of use/exposure

Use frequency : Covers exposure up to 240 min/day

Technical and organisational conditions and measures

Provide a basic standard of general ventilation (1 to 3 air changes per hour).

Dermal - minimum efficiency of 0 %

Inhalation - minimum efficiency of 90 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

5.2.7. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Product (article) characteristics

Covers concentrations up to 100 %

Physical form of product : Liquid

Amount used (or contained in articles), frequency and duration of use/exposure

Use frequency : Covers exposure up to 240 min/day

Technical and organisational conditions and measures

Provide a basic standard of general ventilation (1 to 3 air changes per hour).

Dermal - minimum efficiency of 0 %

Inhalation - minimum efficiency of 90 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

5.2.8. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 240 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

5.2.9. Control of worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

5.2.10. Control of worker exposure: Roller application or brushing (PROC10)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 240 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

5.2.11. Control of worker exposure: Non-industrial spraying (PROC11)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Ensure the ventilation system is regularly maintained and tested. Clean equipment and the work area every day.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use
Room size	: > 1000 m3
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Ensure that the distance from worker to task is greater than 1 m. Ensure regular inspection, cleaning and maintenance of equipment and machines. Ensure that a spraying booth is used.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

5.2.12. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 240 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

5.2.13. Control of worker exposure: Use as laboratory reagent (PROC15)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 240 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

5.2.14. Control of worker exposure: Manual activities involving hand contact (PROC19)

Product (article) characteristics

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 240 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Body parts exposed	: Assumes that potential dermal contact is limited to hands and forearms.
Indoor or outdoor use	: Covers indoor and outdoor use.

5.3. Exposure estimation and reference to its source

5.3.1. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)

Protection Target	Exposure estimate	RCR
Freshwater	0,00251 mg/L	< 0,01
Freshwater sediment	0,00976 mg/kg dry weight	< 0,01
Marine water	0,000247 mg/L	< 0,01
Marine sediment	0,000962 mg/kg dry weight	< 0,01
Agricultural soil	0,0000976 mg/kg dry weight	< 0,01
Sewage treatment plant	0,000135 mg/L	< 0,01

5.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		0,031 mg/m ³	< 0,01
inhalative	systemic		0,031 mg/m ³	< 0,01

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

5.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		61,77 mg/m ³	0,199
inhalative	systemic		61,77 mg/m ³	0,199

5.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		77,21 mg/m ³	0,249
inhalative	systemic		77,21 mg/m ³	0,249

5.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		154,4 mg/m ³	0,498
inhalative	systemic		154,4 mg/m ³	0,498

5.3.6. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		185,3 mg/m ³	0,598
inhalative	systemic		185,3 mg/m ³	0,598

5.3.7. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		185,3 mg/m ³	0,598
inhalative	systemic		185,3 mg/m ³	0,598

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

5.3.8. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		92,65 mg/m ³	0,299
inhalative	systemic		92,65 mg/m ³	0,299

5.3.9. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		185,3 mg/m ³	0,598
inhalative	systemic		185,3 mg/m ³	0,598

5.3.10. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		185,3 mg/m ³	0,598
inhalative	systemic		185,3 mg/m ³	0,598

5.3.11. Worker exposure: Non-industrial spraying (PROC11)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		0 mg/m ³	< 0,01
inhalative	systemic		0 mg/m ³	< 0,01

5.3.12. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		185,3 mg/m ³	0,598
inhalative	systemic		185,3 mg/m ³	0,598

5.3.13. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure	Exposure	RCR
----------------	---------------	----------	----------	-----

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

		indicator	estimate	
inhalative	local		185,3 mg/m ³	0,598
inhalative	systemic		185,3 mg/m ³	0,598

5.3.14. Worker exposure: Manual activities involving hand contact (PROC19)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		185,3 mg/m ³	0,598
inhalative	systemic		185,3 mg/m ³	0,598

5.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Data refer to lead substance.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

ES 6: Cleaning; Industrial uses (SU3).

6.1. Title section

Exposure Scenario name	: Cleaning
Structured Short Title	: Cleaning; Industrial uses (SU3).

Environment		
CS 1	Use of non-reactive processing aid at industrial site (no inclusion into or onto article)	ERC4
Worker		
CS 2	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions	PROC1
CS 3	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC2
CS 4	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	PROC3
CS 5	Chemical production where opportunity for exposure arises	PROC4
CS 6	Industrial spraying	PROC7
CS 7	Transfer of substance or mixture (charging/discharging) at non dedicated-facilities	PROC8a
CS 8	Transfer of substance or mixture (charging/discharging) at dedicated facilities	PROC8b
CS 9	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)	PROC9
CS 10	Roller application or brushing	PROC10
CS 11	Treatment of articles by dipping and pouring	PROC13

6.2. Conditions of use affecting exposure

6.2.1. Control of environmental exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount per site	: 100 t
Maximum daily site tonnage	: 5 t
Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant
STP effluent	: 2.000 m3/d

6.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

6.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

6.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

6.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Other conditions affecting workers exposure

Indoor or outdoor use : Covers indoor and outdoor use.

6.2.6. Control of worker exposure: Industrial spraying (PROC7)

Product (article) characteristics

Covers concentrations up to 100 %

Physical form of product : Liquid

Amount used (or contained in articles), frequency and duration of use/exposure

Use frequency : Covers exposure up to 480 min/day

Technical and organisational conditions and measures

Ensure the ventilation system is regularly maintained and tested.
Clean equipment and the work area every day.

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Room size : > 1000 m³

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply

Ensure that the distance from worker to task is greater than 1 m.
Ensure regular inspection, cleaning and maintenance of equipment and machines.
Ensure that a spraying booth is used.

6.2.7. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Product (article) characteristics

Covers concentrations up to 100 %

Physical form of product : Liquid

Amount used (or contained in articles), frequency and duration of use/exposure

Use frequency : Covers exposure up to 480 min/day

Technical and organisational conditions and measures

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

Provide a basic standard of general ventilation (1 to 3 air changes per hour).

Dermal - minimum efficiency of 0 %

Inhalation - minimum efficiency of 90 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

6.2.8. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Product (article) characteristics

Covers concentrations up to 100 %

Physical form of product : Liquid

Amount used (or contained in articles), frequency and duration of use/exposure

Use frequency : Covers exposure up to 480 min/day

Technical and organisational conditions and measures

Provide a basic standard of general ventilation (1 to 3 air changes per hour).

Dermal - minimum efficiency of 0 %

Inhalation - minimum efficiency of 95 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

6.2.9. Control of worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Product (article) characteristics

Covers concentrations up to 100 %

Physical form of product : Liquid

Amount used (or contained in articles), frequency and duration of use/exposure

Use frequency : Covers exposure up to 480 min/day

Technical and organisational conditions and measures

Provide a basic standard of general ventilation (1 to 3 air changes per hour).

Dermal - minimum efficiency of 0 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

6.2.10. Control of worker exposure: Roller application or brushing (PROC10)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

6.2.11. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

Indoor or outdoor use : Indoor use

6.3. Exposure estimation and reference to its source

6.3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Protection Target	Exposure estimate	RCR
Freshwater	0,00562 mg/L	0,014
Freshwater sediment	0,022 mg/kg dry weight	0,014
Marine water	0,000558 mg/L	0,014
Marine sediment	0,000956 mg/kg dry weight	< 0,01
Agricultural soil	0,00811 mg/kg dry weight	0,106
Sewage treatment plant	0,031 mg/L	< 0,01

6.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		0,031 mg/m ³	< 0,01
inhalative	systemic		0,031 mg/m ³	< 0,01

6.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

6.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		30,88 mg/m ³	0,1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

inhalative	systemic		30,88 mg/m ³	0,1
------------	----------	--	-------------------------	-----

6.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		61,77 mg/m ³	0,199
inhalative	systemic		61,77 mg/m ³	0,199

6.3.6. Worker exposure: Industrial spraying (PROC7)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		0 mg/m ³	< 0,01
inhalative	systemic		0 mg/m ³	< 0,01

6.3.7. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

6.3.8. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		3,861 mg/m ³	0,012
inhalative	systemic		3,861 mg/m ³	0,012

6.3.9. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

6.3.10. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

6.3.11. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

6.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Data refer to lead substance.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

ES 7: Cleaning; Professional uses (SU22).

7.1. Title section

Exposure Scenario name	: Cleaning
Structured Short Title	: Cleaning; Professional uses (SU22).

Environment		
CS 1	Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)	ERC8d
Worker		
CS 2	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions	PROC1
CS 3	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC2
CS 4	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	PROC3
CS 5	Chemical production where opportunity for exposure arises	PROC4
CS 6	Transfer of substance or mixture (charging/discharging) at non dedicated-facilities	PROC8a
CS 7	Transfer of substance or mixture (charging/discharging) at dedicated facilities	PROC8b
CS 8	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)	PROC9
CS 9	Roller application or brushing	PROC10
CS 10	Non-industrial spraying	PROC11
CS 11	Treatment of articles by dipping and pouring	PROC13

7.2. Conditions of use affecting exposure

7.2.1. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount for wide dispersive uses	: 0,024 kg
Emission days	: 365
Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant
STP effluent	: 2.000 m3/d
Other conditions affecting environmental exposure	
Receiving surface water flow	: 18.000 m3/d
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

7.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

7.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics	
--	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

7.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

7.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

7.2.6. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 240 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

7.2.7. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 240 min/day
Technical and organisational conditions and measures	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Provide a basic standard of general ventilation (1 to 3 air changes per hour).
Dermal - minimum efficiency of 0 %
Inhalation - minimum efficiency of 95 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

7.2.8. Control of worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Product (article) characteristics

Covers concentrations up to 100 %

Physical form of product : Liquid

Amount used (or contained in articles), frequency and duration of use/exposure

Use frequency : Covers exposure up to 240 min/day

Technical and organisational conditions and measures

Provide a basic standard of general ventilation (1 to 3 air changes per hour).
Dermal - minimum efficiency of 0 %
Inhalation - minimum efficiency of 90 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

7.2.9. Control of worker exposure: Roller application or brushing (PROC10)

Product (article) characteristics

Covers concentrations up to 100 %

Physical form of product : Liquid

Amount used (or contained in articles), frequency and duration of use/exposure

Use frequency : Covers exposure up to 240 min/day

Technical and organisational conditions and measures

Provide a basic standard of general ventilation (1 to 3 air changes per hour).
Dermal - minimum efficiency of 0 %
Inhalation - minimum efficiency of 90 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

7.2.10. Control of worker exposure: Non-industrial spraying (PROC11)

Product (article) characteristics

Covers concentrations up to 100 %

Physical form of product : Liquid

Amount used (or contained in articles), frequency and duration of use/exposure

Use frequency : Covers exposure up to 480 min/day

Technical and organisational conditions and measures

Clean equipment and the work area every day.
Ensure the ventilation system is regularly maintained and tested.

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

Room size : > 1000 m³

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply

Ensure that the distance from worker to task is greater than 1 m.
Ensure regular inspection, cleaning and maintenance of equipment and machines.
Ensure that a spraying booth is used.

7.2.11. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics

Covers concentrations up to 100 %

Physical form of product : Liquid

Amount used (or contained in articles), frequency and duration of use/exposure

Use frequency : Covers exposure up to 240 min/day

Technical and organisational conditions and measures

Provide a basic standard of general ventilation (1 to 3 air changes per hour).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

Dermal - minimum efficiency of 0 %
Inhalation - minimum efficiency of 90 %

Other conditions affecting workers exposure

Indoor or outdoor use : Indoor use

7.3. Exposure estimation and reference to its source

7.3.1. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)

Protection Target	Exposure estimate	RCR
Freshwater	0,00249 mg/L	< 0,01
Freshwater sediment	0,00971 mg/kg dry weight	< 0,01
Marine water	0,000246 mg/L	< 0,01
Marine sediment	0,000956 mg/kg dry weight	< 0,01
Agricultural soil	0,0000969 mg/kg dry weight	< 0,01
Sewage treatment plant	< 0,00001 mg/L	< 0,01

7.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		0,031 mg/m ³	< 0,01
inhalative	systemic		0,031 mg/m ³	< 0,01

7.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		61,77 mg/m ³	0,199
inhalative	systemic		61,77 mg/m ³	0,199

7.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		77,21 mg/m ³	0,249
inhalative	systemic		77,21 mg/m ³	0,249

7.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		154,4 mg/m ³	0,498
inhalative	systemic		154,4 mg/m ³	0,498

7.3.6. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		185,3 mg/m ³	0,598
inhalative	systemic		185,3 mg/m ³	0,598

7.3.7. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		92,65 mg/m ³	0,299
inhalative	systemic		92,65 mg/m ³	0,299

7.3.8. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		185,3 mg/m ³	0,598
inhalative	systemic		185,3 mg/m ³	0,598

7.3.9. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
----------------	---------------	--------------------	-------------------	-----

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

inhalative	local		185,3 mg/m ³	0,598
inhalative	systemic		185,3 mg/m ³	0,598

7.3.10. Worker exposure: Non-industrial spraying (PROC11)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		0 mg/m ³	< 0,01
inhalative	systemic		0 mg/m ³	< 0,01

7.3.11. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		185,3 mg/m ³	0,598
inhalative	systemic		185,3 mg/m ³	0,598

7.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Data refer to lead substance.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

ES 8: Use in laboratories; Professional uses (SU22).

8.1. Title section

Exposure Scenario name	: Use in laboratories
Structured Short Title	: Use in laboratories; Professional uses (SU22).

Environment		
CS 1	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)	ERC8a
Worker		
CS 2	Roller application or brushing	PROC10
CS 3	Use as laboratory reagent	PROC15

8.2. Conditions of use affecting exposure

8.2.1. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount for wide dispersive uses	: < 0,001 kg
Emission days	: 365
Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant

8.2.2. Control of worker exposure: Roller application or brushing (PROC10)

Product (article) characteristics	
Covers concentrations up to 100 %	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 240 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

8.2.3. Control of worker exposure: Use as laboratory reagent (PROC15)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

8.3. Exposure estimation and reference to its source

8.3.1. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)

Protection Target	Exposure estimate	RCR
Freshwater	0,0025 mg/L	< 0,01
Freshwater sediment	0,00974 mg/kg dry weight	< 0,01

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Marine water	0,000246 mg/L	< 0,01
Marine sediment	0,000959 mg/kg dry weight	< 0,01
Agricultural soil	0,0000973 mg/kg dry weight	< 0,01
Sewage treatment plant	< 0,0000685 mg/L	< 0,01

8.3.2. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		185,25 mg/m ³	0,598
inhalative	systemic		185,25 mg/m ³	0,598

8.3.3. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		30,88 mg/m ³	0,1
inhalative	systemic		30,88 mg/m ³	0,1

8.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Data refer to lead substance.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

ES 9: Polymerisation; Industrial uses (SU3).

9.1. Title section

Exposure Scenario name	: Polymerisation
Structured Short Title	: Polymerisation; Industrial uses (SU3).

Environment		
CS 1	Use of non-reactive processing aid at industrial site (no inclusion into or onto article)	ERC4
Worker		
CS 2	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions	PROC1
CS 3	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	PROC2
CS 4	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	PROC3
CS 5	Chemical production where opportunity for exposure arises	PROC4
CS 6	Transfer of substance or mixture (charging/discharging) at non dedicated-facilities	PROC8a
CS 7	Transfer of substance or mixture (charging/discharging) at dedicated facilities	PROC8b
CS 8	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)	PROC9

9.2. Conditions of use affecting exposure

9.2.1. Control of environmental exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount per site	: 5000 t

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

Maximum daily site tonnage	: 16,67 t
Technical and organisational conditions and measures	
Do not apply industrial sludge to natural soils.	
Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant
STP effluent	: 2.000 m3/d

9.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

9.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

9.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

9.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Covers indoor and outdoor use.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

9.2.6. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

9.2.7. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

9.2.8. Control of worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Product (article) characteristics	
Covers concentrations up to 100 %	
Physical form of product	: Liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Use frequency	: Covers exposure up to 480 min/day
Technical and organisational conditions and measures	
Provide a basic standard of general ventilation (1 to 3 air changes per hour). Dermal - minimum efficiency of 0 % Inhalation - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

9.3. Exposure estimation and reference to its source

9.3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Protection Target	Exposure estimate	RCR
Freshwater	0,00249 mg/L	< 0,01
Freshwater sediment	0,00971 mg/kg dry weight	< 0,01
Marine water	0,000246 mg/L	< 0,01
Marine sediment	0,000956 mg/kg dry weight	< 0,01
Agricultural soil	0,038 mg/kg dry weight	0,542
Sewage treatment plant	0 mg/L	< 0,01

9.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		0,031 mg/m ³	< 0,01

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0

SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025

Print Date: 28.07.2026

inhalative	systemic		0,031 mg/m ³	< 0,01
------------	----------	--	-------------------------	--------

9.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

9.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		30,88 mg/m ³	0,1
inhalative	systemic		30,88 mg/m ³	0,1

9.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		61,77 mg/m ³	0,199
inhalative	systemic		61,77 mg/m ³	0,199

9.3.6. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

9.3.7. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		3,861 mg/m ³	0,012

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 908

Version: 8.0
SDB_GB

Revision Date: 22.07.2026

Date of last issue: 27.08.2025
Print Date: 28.07.2026

inhalative	systemic		3,861 mg/m ³	0,012
------------	----------	--	-------------------------	-------

9.3.8. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	local		15,44 mg/m ³	0,05
inhalative	systemic		15,44 mg/m ³	0,05

9.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Data refer to lead substance.