

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : BYK-W 940 SG
UFI : 4N48-W00T-8009-TG8H
Product code : 000000000000114195

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Wetting & Dispersing Additive

1.3 Details of the supplier of the safety data sheet

Company : BYK USA LLC
South Cherry Street 524
06492 Wallingford
Telephone :
Information : BYK USA Regulatory Affairs
Telephone : +1 203-265-2086
Telefax :
E-mail address : BRIEF.BYK.NAFTA@altana.com

1.4 Emergency telephone number

Europe +44 1235 239670
Middle East/Africa +44 1235 239671
Americas +1 215 207 0061
East/South East Asia +65 3158 1074
(Local India: 000 800 100 7479)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 1B	H350: May cause cancer.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H350 May cause cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe mist or vapours.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

- 85711-46-2 Fatty acids, C14-18 and C16-18-unsatd., maleated
- 1330-20-7 Xylene, mixture of isomers
- 98-82-8 cumene
- 108-31-6 maleic anhydride

Additional Labelling

Restricted to professional users.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Solution of an unsaturated polycarboxylic acid polymer with a polysiloxane copolymer

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Fatty acids, C14-18 and C16-18-unsatd., maleated	85711-46-2 01-2119976378-19-0000	Skin Irrit. 2; H315 Skin Sens. 1; H317	>= 30 - < 50
Xylene, mixture of isomers	1330-20-7 01-2119488216-32	Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Aquatic Chronic 3; H412	>= 30 - < 50
ethylbenzene	100-41-4 202-849-4	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 7 - < 10
2,6-dimethylheptan-4-one	108-83-8 203-620-1 01-2119474441-41	Flam. Liq. 3; H226 STOT SE 3; H335 (Respiratory system) <hr/> specific concentration limit STOT SE 3; H335 >= 10 %	>= 3 - < 5
cumene	98-82-8 202-704-5	Flam. Liq. 3; H226 Carc. 1B; H350	>= 0,25 - < 0,5

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

		STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	
maleic anhydride	108-31-6 203-571-6 01-2119472428-31	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1A; H317 STOT RE 1; H372 (Respiratory system) EUH071 specific concentration limit Skin Sens. 1A; H317 >= 0,001 % Acute toxicity estimate Acute oral toxicity: 1.090 mg/kg	>= 0,25 - < 0,5
toluene	108-88-3 203-625-9	Aquatic Chronic 3; H412 Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 0,1 - < 0,25
octamethylcyclotetrasiloxane [D4]	556-67-2 209-136-7 01-2119529238-36	Repr. 2; H361f Aquatic Chronic 1; H410 PBT; EUH440 vPvB; EUH441 Flam. Liq. 3; H226 M-Factor (Chronic aquatic toxicity): 10	>= 0,025 - < 0,1

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : May cause an allergic skin reaction.
May cause respiratory irritation.
May cause cancer.
May cause damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Neutralize with chalk, alkali solution or ammonia.
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Xylene, mixture of isomers	1330-20-7	TWA	50 ppm 221 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

		STEL	200 ppm 884 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
cumene	98-82-8	TWA	20 ppm 100 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 250 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	10 ppm 50 mg/m ³	2019/1831/E U
	Further information: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin., Indicative			
		STEL	50 ppm 250 mg/m ³	2019/1831/E U
	Further information: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin., Indicative			
toluene	108-88-3	TWA	50 ppm 192 mg/m ³	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		STEL	100 ppm 384 mg/m ³	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
Xylene, mixture of isomers	Workers	Inhalation	Long-term systemic effects	221 mg/m ³
	Workers	Inhalation	Acute local effects	442 mg/m ³
	Workers	Dermal	Long-term systemic effects	212 mg/kg
	Consumers	Inhalation	Long-term systemic effects	65,3 mg/m ³
	Consumers	Dermal	Long-term systemic effects	125 mg/kg
	Consumers	Oral	Long-term systemic effects	1,5 mg/kg
2,6-dimethylheptan-4-one	Consumers	Inhalation	Acute local effects	260 mg/m ³
	Workers	Inhalation	Acute systemic effects, Acute local effects, Long-term local effects	290 mg/m ³
	Workers	Skin contact	Long-term systemic effects	80 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

	Workers	Inhalation	Long-term systemic effects	479 mg/m ³
	Consumers	Inhalation	Acute systemic effects, Acute local effects, Long-term local effects	145 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	28,5 mg/kg
	Consumers	Inhalation	Long-term systemic effects	171 mg/kg
	Consumers	Ingestion	Long-term systemic effects	7,14 mg/kg
maleic anhydride	Workers	Inhalation	Long-term systemic effects, Long-term local effects	0,081 mg/m ³
	Workers	Inhalation	Systemic effects, Acute effects, Local effects	0,2 mg/m ³
octamethylcyclotetrasiloxane [D4]	Consumers	Oral	Acute systemic effects, Long-term systemic effects	3,7 mg/kg
	Consumers	Inhalation	Acute systemic effects, Acute local effects, Long-term systemic effects, Long-term local effects	13 mg/m ³
	Workers	Inhalation	Acute systemic effects, Acute local effects, Long-term systemic effects, Long-term local effects	73 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
Xylene, mixture of isomers	Fresh water	0,327 mg/l
	Marine water	0,327 mg/l
	Fresh water sediment	12,46 mg/kg
	Marine sediment	12,46 mg/kg
	Soil	2,31 mg/kg
	Sewage treatment plant	6,58 mg/l
	Intermittent releases	0,327 mg/l
2,6-dimethylheptan-4-one	Fresh water	0,03 mg/l
	Marine water	0,003 mg/l
	Intermittent releases	0,3 mg/l
	Fresh water sediment	0,46 mg/kg
	Marine sediment	0,046 mg/kg
	Sewage treatment plant	2,55 mg/l
maleic anhydride	Soil	0,0746 mg/kg
	Fresh water	0,038 mg/l
	Marine water	0,0038 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

	Intermittent releases	0,379 mg/l
	Soil	0,037 mg/kg
	Fresh water sediment	0,296 mg/kg
	Marine sediment	0,0296 mg/kg
	Sewage treatment plant	44,6 mg/l
octamethylcyclotetrasiloxane [D4]	Fresh water	1,5 µg/l
	Marine water	0,15 µg/l
	Fresh water sediment	0,64 mg/kg
	Soil	0,84 mg/kg
	Sewage treatment plant	10 mg/l
	Marine sediment	0,064 mg/kg
	Hazard for predators: secondary poisoning	41 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Hand protection

Material : Fluorinated rubber
Break through time : >= 480 min
Glove thickness : 0,4 mm

Remarks : The suitability for a specific workplace should be discussed
with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and
concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an
approved filter.

Environmental exposure controls

General advice : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Colour : light brown
Odour : aromatic
Melting point/ range : < 0 °C
Method: derived
Initial boiling point : 137,00 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

	Method: derived
Flash point	: 28,00 °C Method: 48 (Abel-Pensky) DIN 51755
Auto-ignition temperature	: > 200 °C Method: DIN 51794
pH	: 4 (20 °C) Concentration: 1 % Method: Universal pH-value indicator
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 40 mm ² /s (40 °C)
Solubility(ies)	
Water solubility	: immiscible
Partition coefficient: n-octanol/water	: No data available
Vapour pressure	: 9 hPa (20,00 °C) Method: derived
Density	: 0,9450 g/cm ³ (20,00 °C) Method: 4 (20°C oscillating U-tube)

9.2 Other information

Flammability (liquids) : Sustains combustion

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

Materials to avoid : Strong oxidizing agents
Strong acids

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : LD50 (Rat, male and female): > 3.500,000000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

Fatty acids, C14-18 and C16-18-unsatd., maleated:

Acute oral toxicity : LD50 (Rat, female): > 2.000 mg/kg
Method: OECD Test Guideline 423
GLP: yes

Xylene, mixture of isomers:

Acute oral toxicity : LD50 (Rat): 4.300 mg/kg
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)
GLP: no

Acute dermal toxicity : LD50 (Rabbit): > 4.200 mg/kg
GLP: No information available.

2,6-dimethylheptan-4-one:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 14 mg/l
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: no

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

maleic anhydride:

Acute oral toxicity : LD50 (Rat, male and female): 1.090 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit, female): 2.620 mg/kg
GLP: No information available.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Product:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation

Remarks : May cause skin irritation and/or dermatitis.

Components:

Fatty acids, C14-18 and C16-18-unsatd., maleated:

Species : EPISKIN human epidermis skin constructs
Assessment : Irritating to skin.
Method : OECD Test Guideline 439
Result : Irritating to skin.
GLP : yes

2,6-dimethylheptan-4-one:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

maleic anhydride:

Species : Rabbit
Method : No information available.
Result : Corrosive to skin
GLP : no

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Product:

Species : Rabbit

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation

Remarks : Vapours may cause irritation to the eyes, respiratory system
and the skin.

Components:

Fatty acids, C14-18 and C16-18-unsatd., maleated:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

2,6-dimethylheptan-4-one:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : no

maleic anhydride:

Species : Rabbit
Result : Corrosive to eyes
GLP : yes

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Product:

Remarks : Causes sensitisation.

Components:

Fatty acids, C14-18 and C16-18-unsatd., maleated:

Test Type : Mouse Local Lymph Node assay (LLNA)
Species : Mouse
Assessment : May cause sensitisation by skin contact.
Method : OECD Test Guideline 429
Result : May cause sensitisation by skin contact.
GLP : yes

2,6-dimethylheptan-4-one:

Test Type : Maximisation Test

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Not a skin sensitizer.
GLP : yes

maleic anhydride:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Causes sensitisation.
GLP : yes

octamethylcyclotetrasiloxane [D4]:

Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

Germ cell mutagenicity

Not classified due to lack of data.

Product:

Genotoxicity in vitro : Remarks: No data available
Genotoxicity in vivo : Remarks: No data available

Components:

Fatty acids, C14-18 and C16-18-unsatd., maleated:

Genotoxicity in vitro : Test Type: Ames test
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes

Test Type: In vitro mammalian cell gene mutation test (mouse lymphoma)

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative
GLP: yes

Test Type: Chromosome aberration test in vitro
Metabolic activation: with and without metabolic activation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

Method: OECD Test Guideline 473

Result: negative

GLP: yes

Carcinogenicity

May cause cancer.

Product:

Remarks : No data available

Reproductive toxicity

Not classified due to lack of data.

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure

May cause respiratory irritation.

Product:

Remarks : No data available

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Product:

Remarks : No data available

Repeated dose toxicity

Product:

Remarks : No data available

Remarks : No data available

Components:

Fatty acids, C14-18 and C16-18-unsatd., maleated:

Species : Rat, male and female

NOAEL : 1.000 mg/kg

Application Route : Oral

Method : OECD Test Guideline 422

GLP : yes

Target Organs : Stomach

Aspiration toxicity

Not classified due to lack of data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

Product:

No data available

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Components:

Fatty acids, C14-18 and C16-18-unsatd., maleated:

Toxicity to fish : LL50 (Leuciscus idus (Golden orfe)): > 150 mg/l
Exposure time: 48 h
Test Type: static test
Method: DIN 38412
GLP: no

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: semi-static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : ErL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

GLP: yes

Toxicity to microorganisms : EC50 (activated sludge): > 1.000 mg/l
Exposure time: 3 h
Test Type: static test
Method: OECD Test Guideline 209
GLP: yes

Xylene, mixture of isomers:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1 mg/l
aquatic invertebrates
Exposure time: 24 h
Test Type: Immobilization
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 (Selenastrum capricornutum (green algae)): 2,2 mg/l
plants
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,44 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201

Toxicity to fish (Chronic : NOEC: > 1,3 mg/l
toxicity)
Exposure time: 56 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other : NOEC: 1,17 mg/l
aquatic invertebrates
(Chronic toxicity)
Exposure time: 7 d
Species: Daphnia sp. (water flea)

NOEC: 0,96 mg/l
Exposure time: 7 d
Species: Daphnia sp. (water flea)

2,6-dimethylheptan-4-one:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 30 mg/l
Exposure time: 96 h
Test Type: flow-through test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 37,2 mg/l
aquatic invertebrates
Exposure time: 48 h
Test Type: semi-static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic : (Pseudokirchneriella subcapitata (green algae)): 46,9 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

plants
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

maleic anhydride:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 75 mg/l
Exposure time: 96 h
Test Type: static test
GLP: no

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 42,81 mg/l
aquatic invertebrates
Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata): 74,35 mg/l
plants
Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes

Toxicity to daphnia and other : NOEC: 10 mg/l
aquatic invertebrates
(Chronic toxicity)
Exposure time: 21 d
Species: Daphnia magna (Water flea)
GLP: no

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

Fatty acids, C14-18 and C16-18-unsatd., maleated:

Biodegradability : Result: Not readily biodegradable.
Method: OECD Test Guideline 301
GLP: yes

Xylene, mixture of isomers:

Biodegradability : Test Type: aerobic
Result: Readily biodegradable.
Method: OECD Test Guideline 301F
GLP: yes

2,6-dimethylheptan-4-one:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301D
GLP: no

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

maleic anhydride:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301B
GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

Xylene, mixture of isomers:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Exposure time: 56 d
Bioconcentration factor (BCF): 25,9
GLP: no

Partition coefficient: n-octanol/water : Pow: 3,2 (20 °C)
pH: 7

maleic anhydride:

Partition coefficient: n-octanol/water : log Pow: -2,61 (19,8 °C)
pH: 4 - 9
Method: OECD Test Guideline 107
GLP: yes

12.4 Mobility in soil

Components:

maleic anhydride:

Distribution among environmental compartments : Koc: 42, log Koc: 1,63

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Components:

octamethylcyclotetrasiloxane [D4]:

Assessment : Persistent, Bioaccumulative and Toxic (PBT).
: Very persistent and very bioaccumulative (vPvB).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1993
IMDG : UN 1993
IATA : UN 1993

14.2 UN proper shipping name

ADR : FLAMMABLE LIQUID, N.O.S.
(Xylene, Diisobutyl ketone)
IMDG : FLAMMABLE LIQUID, N.O.S.
(XYLENE, Diisobutyl ketone)
IATA : Flammable liquid, n.o.s.
(Xylene, Diisobutyl ketone)

14.3 Transport hazard class(es)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

ADR : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : D/E

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Remarks : IMDG Code segregation group - none

IATA (Cargo)
Packing instruction (cargo aircraft) : 366
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)
Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR
Environmentally hazardous : no

IMDG
Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

- REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

Number on list 5: benzene

Number on list 28: cumene

Number on list 48: toluene

Number on list 72: benzene

Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.
- REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
- REACH - List of substances subject to authorisation (Annex XIV) : Not applicable
- Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

15.2 Chemical safety assessment

Not applicable

SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

- EUH440 : Accumulates in the environment and living organisms including in humans.
EUH441 : Strongly accumulates in the environment and living organisms including in humans.
H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H302 : Harmful if swallowed.
H304 : May be fatal if swallowed and enters airways.
H312 : Harmful in contact with skin.
H314 : Causes severe skin burns and eye damage.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H350	: May cause cancer.
H361d	: Suspected of damaging the unborn child.
H361f	: Suspected of damaging fertility.
H372	: Causes damage to organs through prolonged or repeated exposure if inhaled.
H373	: May cause damage to organs through prolonged or repeated exposure.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
EUH071	: Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Carc.	: Carcinogenicity
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
PBT	: Persistent, bioaccumulative and toxic
Repr.	: Reproductive toxicity
Resp. Sens.	: Respiratory sensitisation
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
vPvB	: Very persistent and very bioaccumulative
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	: Europe. Indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2006/15/EC / TWA	: Limit Value - eight hours
2006/15/EC / STEL	: Short term exposure limit
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 940 SG

Version: 3.1
SDB_IS

Revision Date: 11.05.2026

Date of last issue: 14.03.2025
Print Date: 12.05.2026

Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Skin Sens. 1	H317
Carc. 1B	H350
STOT SE 3	H335
STOT RE 2	H373
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REG_EU / EN