

BYK-W 940Version 2.3
SDS_AU

Revision Date: 22.01.2026

Date of last issue: 06.12.2024
Print Date 28.01.2026

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : BYK-W 940
Product code : 000000000000101294

Manufacturer or supplier's details

Company : BYK-Chemie GmbH
Address : Abelstrasse 45
46483 Wesel
Telephone : +49 281 670-23532
Telefax : +49 281 670-23533
E-mail address : GHS.BYK@altana.com
Emergency telephone number : 18000 74234 (toll –free number, access from Australia only)
+61 2 8014 4558

Importer

Company : IMCD Australia Pty Ltd
Level 1, 352 Wellington Road
Mulgrave
VIC 3170
Australia
Telephone: +61 3 8544 3100

Use of the Sub-
stance/Mixture : Wetting & Dispersing Additive

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3
Skin sensitisation : Category 1
Specific target organ toxicity - : Category 3 (Respiratory system)
single exposure
Specific target organ toxicity - : Category 2 (hearing organs, hearing organs)
repeated exposure
Long-term (chronic) aquatic : Category 3
hazard




GHS label elements

BYK-W 940

Version 2.3
SDS_AU

Revision Date: 22.01.2026

Date of last issue: 06.12.2024
Print Date 28.01.2026

Hazard pictograms	:	  
Signal word	:	Warning
Hazard statements	:	H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H373 May cause damage to organs (hearing organs, hearing organs) through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P260 Do not breathe mist or vapours. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P314 Get medical advice/ attention if you feel unwell. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

BYK-W 940

Version 2.3
SDS_AU

Revision Date: 22.01.2026

Date of last issue: 06.12.2024
Print Date 28.01.2026**Other hazards which do not result in classification**

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Solution of an unsaturated polycarboxylic acid polymer with a polysiloxane copolymer

Components

Chemical name	CAS-No.	Concentration (% w/w)
Fatty acids, C14-18 and C16-18-unsatd., maleated	85711-46-2	>= 30 -< 50
Xylene, mixture of isomers	1330-20-7	>= 30 -< 50
ethylbenzene	100-41-4	>= 12.5 -< 20
2,6-dimethylheptan-4-one	108-83-8	>= 3 -< 5
maleic anhydride	108-31-6	>= 0.25 -< 0.5

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water.
 If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.
 Remove contact lenses.
 Protect unharmed eye.
 Keep eye wide open while rinsing.
 If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
 Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : No information available.
 May cause an allergic skin reaction.
 May cause respiratory irritation.
 May cause damage to organs through prolonged or repeated exposure.

Notes to physician : No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam
 Carbon dioxide (CO₂)
 Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire- : Do not allow run-off from fire fighting to enter drains or water

BYK-W 940

Version 2.3
SDS_AU

Revision Date: 22.01.2026

Date of last issue: 06.12.2024
Print Date 28.01.2026

fighting	courses.
Hazardous combustion products	: Carbon oxides
Specific extinguishing methods	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.
Hazchem Code	: •3Y

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Neutralize with chalk, alkali solution or ammonia. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	: Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
Advice on safe handling	: Avoid formation of aerosol. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

BYK-W 940

Version 2.3
SDS_AU

Revision Date: 22.01.2026

Date of last issue: 06.12.2024
Print Date 28.01.2026

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Hygiene measures : Wash hands before breaks and at the end of workday.

Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Xylene, mixture of isomers	1330-20-7	TWA	80 ppm 350 mg/m ³	AU OEL
		STEL	150 ppm 655 mg/m ³	AU OEL
ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 434 mg/m ³	AU OEL
2,6-dimethylheptan-4-one	108-83-8	STEL	125 ppm 543 mg/m ³	AU OEL
		TWA	20 ppm	ACGIH
maleic anhydride	108-31-6	TWA	25 ppm 145 mg/m ³	AU OEL
		TWA	25 ppm	ACGIH
Further information: Sensitiser				
		TWA (Inhalable fraction and vapor)	0.01 mg/m ³	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Xylene, mixture of isomers	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	0.3 g/g creatinine	ACGIH BEI
ethylbenzene	100-41-4	Sum of	Urine	End of	150 mg/g	ACGIH

BYK-W 940

Version 2.3
SDS_AU

Revision Date: 22.01.2026

Date of last issue: 06.12.2024
Print Date 28.01.2026

		mandelic acid and phenyl glyoxylic acid		shift (As soon as possible after exposure ceases)	creatinine	BEI
--	--	---	--	---	------------	-----

Personal protective equipment

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- Hand protection
 Material : Fluorinated rubber
 Break through time : > 480 min
 Glove thickness : > 0.45 mm
- Remarks : Wear suitable gloves.
- Eye protection : Eye wash bottle with pure water
 Tightly fitting safety goggles
- Skin and body protection : Impervious clothing
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : light brown
- Odour : aromatic
- Odour Threshold : No data available
- pH : 4 (20 °C)
 Concentration: 1 %
 Method: Universal pH-value indicator
- Melting point/ range : < 0 °C
 Method: derived
- Initial boiling point : 137.00 °C
 Method: derived
- Flash point : 28.00 °C
 Method: 48 (Abel-Pensky) DIN 51755
- Evaporation rate : No data available
- Flammability (liquids) : Sustains combustion
- Upper explosion limit / Upper flammability limit : 7.60 %(V)
- Lower explosion limit / Lower : 0.80 %(V)

BYK-W 940

Version 2.3
SDS_AU

Revision Date: 22.01.2026

Date of last issue: 06.12.2024
Print Date 28.01.2026

flammability limit	
Vapour pressure	: 9 hPa (20.00 °C) Method: derived
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.9450 g/cm ³ (20.00 °C) Method: 4 (20°C oscillating U-tube)
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: > 200 °C Method: DIN 51794
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 40 mm ² /s (40.00 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents Strong acids
Hazardous decomposition products	: No decomposition if stored normally.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified due to lack of data.

Product:

Acute oral toxicity	: LD50 (Rat, male and female): > 3,500.000000 mg/kg Method: OECD Test Guideline 401 GLP: yes
Acute inhalation toxicity	: Acute toxicity estimate: > 20 mg/l Exposure time: 4 h

BYK-W 940

Version 2.3
SDS_AU

Revision Date: 22.01.2026

Date of last issue: 06.12.2024
Print Date 28.01.2026Test atmosphere: vapour
Method: Calculation methodAcute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method**Components:****Fatty acids, C14-18 and C16-18-unsatd., maleated:**Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 423
GLP: yes**Xylene, mixture of isomers:**Acute oral toxicity : LD50 (Rat): 4,300 mg/kg
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)
GLP: noAcute dermal toxicity : LD50 (Rabbit): > 4,200 mg/kg
GLP: No information available.**2,6-dimethylheptan-4-one:**Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401
GLP: yesAcute inhalation toxicity : LC50 (Rat): > 14 mg/l
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: noAcute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes**maleic anhydride:**Acute oral toxicity : LD50 (Rat, male and female): 1,090 mg/kg
Method: OECD Test Guideline 401Acute dermal toxicity : LD50 (Rabbit, female): 2,620 mg/kg
GLP: No information available.**Skin corrosion/irritation**

Based on available data, the classification criteria are not met.

Product:Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation

Remarks : May cause skin irritation and/or dermatitis.

BYK-W 940

Version 2.3
SDS_AU

Revision Date: 22.01.2026

Date of last issue: 06.12.2024
Print Date 28.01.2026

Components:**Fatty acids, C14-18 and C16-18-unsatd., maleated:**

Species : EPISKIN human epidermis skin constructs
Assessment : Irritating to skin.
Method : OECD Test Guideline 439
Result : Irritating to skin.
GLP : yes

2,6-dimethylheptan-4-one:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

maleic anhydride:

Species : Rabbit
Method : No information available.
Result : Corrosive to skin
GLP : no

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Product:

Species : Rabbit
Result : No eye irritation
Assessment : No eye irritation
Method : OECD Test Guideline 405

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**Fatty acids, C14-18 and C16-18-unsatd., maleated:**

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
GLP : yes

2,6-dimethylheptan-4-one:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
GLP : no

maleic anhydride:

Species : Rabbit

BYK-W 940

Version 2.3
SDS_AU

Revision Date: 22.01.2026

Date of last issue: 06.12.2024
Print Date 28.01.2026

Result : Corrosive to eyes
GLP : yes

Respiratory or skin sensitisation**Skin sensitisation**

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Product:

Remarks : Causes sensitisation.

Components:**Fatty acids, C14-18 and C16-18-unsatd., maleated:**

Test Type : Mouse Local Lymph Node assay (LLNA)
Species : Mouse
Assessment : May cause sensitisation by skin contact.
Method : OECD Test Guideline 429
Result : May cause sensitisation by skin contact.
GLP : yes

2,6-dimethylheptan-4-one:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Not a skin sensitizer.
GLP : yes

maleic anhydride:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Causes sensitisation.
GLP : yes

Chronic toxicity**Germ cell mutagenicity**

Not classified due to lack of data.

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Result: No data available

BYK-W 940

Version 2.3
SDS_AU

Revision Date: 22.01.2026

Date of last issue: 06.12.2024
Print Date 28.01.2026

Components:

Fatty acids, C14-18 and C16-18-unsatd., maleated:

Genotoxicity in vitro : Test Type: Ames test
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes

Test Type: In vitro mammalian cell gene mutation test (mouse lymphoma)

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative
GLP: yes

Test Type: Chromosome aberration test in vitro
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative
GLP: yes

Carcinogenicity

Not classified due to lack of data.

Product:

Remarks : No data available

Reproductive toxicity

Not classified due to lack of data.

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure

May cause respiratory irritation.

Product:

Remarks : No data available

STOT - repeated exposure

May cause damage to organs (hearing organs, hearing organs) through prolonged or repeated exposure.

Product:

Remarks : No data available

Repeated dose toxicity

Product:

BYK-W 940

Version 2.3
SDS_AU

Revision Date: 22.01.2026

Date of last issue: 06.12.2024
Print Date 28.01.2026

Remarks : No data available

Components:**Fatty acids, C14-18 and C16-18-unsatd., maleated:**

Species : Rat, male and female
NOAEL : 1,000 mg/kg
Application Route : Oral
Method : OECD Test Guideline 422
GLP : yes
Target Organs : Stomach

Aspiration toxicity

Not classified due to lack of data.

Product:

No data available

Further information**Product:**

Remarks : Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Fatty acids, C14-18 and C16-18-unsatd., maleated:**

Toxicity to fish : LL50 (Leuciscus idus (Golden orfe)): > 150 mg/l
Exposure time: 48 h
Test Type: static test
Method: DIN 38412
GLP: no

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates
Exposure time: 48 h
Test Type: semi-static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic : ErL50 (Pseudokirchneriella subcapitata (green algae)): > 100
plants
mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l
Exposure time: 3 h
Test Type: static test

BYK-W 940

Version 2.3
SDS_AU

Revision Date: 22.01.2026

Date of last issue: 06.12.2024
Print Date 28.01.2026Method: OECD Test Guideline 209
GLP: yes**Xylene, mixture of isomers:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1 mg/l
Exposure time: 24 h
Test Type: Immobilization
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 2.2 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.44 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l
Exposure time: 56 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia sp. (water flea)): 1.17 mg/l
Exposure time: 7 d

NOEC (Daphnia sp. (water flea)): 0.96 mg/l
Exposure time: 7 d

2,6-dimethylheptan-4-one:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 30 mg/l
Exposure time: 96 h
Test Type: flow-through test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 37.2 mg/l
Exposure time: 48 h
Test Type: semi-static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : (Pseudokirchneriella subcapitata (green algae)): 46.9 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

maleic anhydride:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 75 mg/l
Exposure time: 96 h
Test Type: static test

BYK-W 940

Version 2.3
SDS_AU

Revision Date: 22.01.2026

Date of last issue: 06.12.2024
Print Date 28.01.2026

GLP: no

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 42.81 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata): 74.35 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
GLP: no

Persistence and degradability**Components:****Fatty acids, C14-18 and C16-18-unsatd., maleated:**

Biodegradability : Result: Not readily biodegradable.
Method: OECD Test Guideline 301
GLP: yes

Xylene, mixture of isomers:

Biodegradability : aerobic
Result: Readily biodegradable.
Method: OECD Test Guideline 301F
GLP: yes

2,6-dimethylheptan-4-one:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301D
GLP: no

maleic anhydride:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301B
GLP: yes

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

Components:**Xylene, mixture of isomers:**

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 25.9

BYK-W 940

Version 2.3
SDS_AU

Revision Date: 22.01.2026

Date of last issue: 06.12.2024
Print Date 28.01.2026Exposure time: 56 d
GLP: noPartition coefficient: n-
octanol/water : Pow: 3.2 (20 °C)
pH: 7**maleic anhydride:**Partition coefficient: n-
octanol/water : log Pow: -2.61 (19.8 °C)
pH: 4 - 9
Method: OECD Test Guideline 107
GLP: yes**Mobility in soil****Components:****maleic anhydride:**Distribution among environ-
mental compartments : Koc: 42, log Koc: 1.63**Other adverse effects****Product:**Additional ecological infor-
mation : An environmental hazard cannot be excluded in the event of
unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**Waste from residues : The product should not be allowed to enter drains, water
courses or the soil.
Do not contaminate ponds, waterways or ditches with chemi-
cal or used container.
Send to a licensed waste management company.
Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(XYLENE, Diisobutyl ketone)
Class : 3
Packing group : III
Labels : 3**IATA-DGR**

BYK-W 940

Version 2.3
SDS_AU

Revision Date: 22.01.2026

Date of last issue: 06.12.2024
Print Date 28.01.2026

UN/ID No. : UN 1993
 Proper shipping name : Flammable liquid, n.o.s.
 (Xylene, Diisobutyl ketone)
 Class : 3
 Packing group : III
 Labels : Flammable Liquids
 Packing instruction (cargo aircraft) : 366
 Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1993
 Proper shipping name : FLAMMABLE LIQUID, N.O.S.
 (XYLENE, Diisobutyl ketone)
 Class : 3
 Packing group : III
 Labels : 3
 EmS Code : F-E, S-E
 Marine pollutant : no
 Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**ADG**

UN number : UN 1993
 Proper shipping name : FLAMMABLE LIQUID, N.O.S.
 (Xylene, Diisobutyl ketone)
 Class : 3
 Packing group : III
 Labels : 3
 Hazchem Code : •3Y

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

SECTION 16. OTHER INFORMATION

Revision Date : 22.01.2026
 Date format : dd.mm.yyyy

Full text of other abbreviations

BYK-W 940

Version 2.3
SDS_AU

Revision Date: 22.01.2026

Date of last issue: 06.12.2024
Print Date 28.01.2026

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
AU OEL	:	Australia. Workplace Exposure Standards for Airborne Contaminants.
ACGIH / TWA	:	8-hour, time-weighted average
AU OEL / TWA	:	Exposure standard - time weighted average
AU OEL / STEL	:	Exposure standard - short term exposure limit

AIIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN