

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1

SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025

Print Date 05.01.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : BYK-W 995 SG

UFI : JA8A-301G-J00V-VN1V

Product code : 000000000000114226

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Wetting & Dispersing Additive

1.3 Details of the supplier of the safety data sheet

Company : BYK USA LLC
South Cherry Street 524
06492 Wallingford

Telephone :

Information : BYK USA Regulatory Affairs
Telephone : +1 203-265-2086
Telefax :
E-mail address : BRIEF.BYK.NAFTA@altana.com

1.4 Emergency telephone number

+44 1235 239670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Carcinogenicity, Category 1B	H350: May cause cancer.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1
SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025
Print Date 05.01.2026

Hazard pictograms	:	   
Signal word	:	Danger
Hazard statements	:	H226 H314 H335 H336 H350 H412 Flammable liquid and vapour. Causes severe skin burns and eye damage. May cause respiratory irritation. May cause drowsiness or dizziness. May cause cancer. Harmful to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P201 P210 P280 Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. Response: P303 + P361 + P353 P304 + P340 + P310 P305 + P351 + P338 + P310 P308 + P313 P370 + P378 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. IF exposed or concerned: Get medical advice/ attention. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

- 108-65-6 2-methoxy-1-methylethyl acetate
- 64742-95-6 Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified
- 7664-38-2 phosphoric acid
- 98-82-8 cumene

Additional Labelling

Restricted to professional users.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1

SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025

Print Date 05.01.2026

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : solution of polymeric phosphoric acid ester

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Phosphoric acid polyester	-	Eye Irrit. 2; H319	>= 50 - <= 100
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 20 - < 25
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified	64742-95-6 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 20 - < 25
phosphoric acid	7664-38-2 231-633-2 01-2119485924-24	Skin Corr. 1B; H314 Eye Dam. 1; H318 specific concentration limit Skin Irrit. 2; H315 10 - < 25 % Eye Irrit. 2; H319 10 - < 25 % Skin Corr. 1B; H314	>= 1 - < 3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1
SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025
Print Date 05.01.2026

		>= 25 %	
cumene	98-82-8 202-704-5	Flam. Liq. 3; H226 Carc. 1B; H350 STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 0,5 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : Causes serious eye damage.
May cause respiratory irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1
SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025
Print Date 05.01.2026

May cause drowsiness or dizziness.
May cause cancer.
Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides
Sulphur oxides
Oxides of phosphorus

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1
SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025
Print Date 05.01.2026

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Neutralize with chalk, alkali solution or ammonia.
Contain spillage, and then collect with non-combustible
absorbent material, (e.g. sand, earth, diatomaceous earth,
vermiculite) and place in container for disposal according to
local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the
application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national
regulations.

Advice on protection against : Do not spray on a naked flame or any incandescent material.
fire and explosion : Take necessary action to avoid static electricity discharge
(which might cause ignition of organic vapours). Keep away
from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : No smoking. Keep container tightly closed in a dry and well-
areas and containers : ventilated place. Containers which are opened must be
carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with
the technological safety standards.

Store in original container.

Further information on : No decomposition if stored and applied as directed.
storage stability

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1

SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025

Print Date 05.01.2026

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 275 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 550 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m3	MT OEL
	Further information: A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.			
		STEL	100 ppm 550 mg/m3	MT OEL
	Further information: A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.			
phosphoric acid	7664-38-2	TWA	1 mg/m3	2000/39/EC
	Further information: Indicative			
		STEL	2 mg/m3	2000/39/EC
	Further information: Indicative			
		TWA	1 mg/m3	MT OEL
		STEL	2 mg/m3	MT OEL
cumene	98-82-8	TWA	20 ppm 100 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 250 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	10 ppm 50 mg/m3	MT OEL
	Further information: A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.			
		STEL	50 ppm 250 mg/m3	MT OEL
	Further information: A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.			
		TWA	10 ppm	2019/1831/E

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1

SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025

Print Date 05.01.2026

			50 mg/m ³	U
	Further information: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin., Indicative			
		STEL	50 ppm 250 mg/m ³	2019/1831/E U
	Further information: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin., Indicative			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
2-methoxy-1-methylethyl acetate	Workers	Skin contact	Long-term systemic effects	796 mg/kg
	Workers	Inhalation	Long-term systemic effects	275 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	320 mg/kg
	Consumers	Inhalation	Long-term systemic effects	33 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	36 mg/kg
	Workers	Inhalation	Acute local effects	550 mg/m ³
	Consumers	Inhalation	Acute local effects	33 mg/m ³
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified	Workers	Skin contact	Long-term exposure, Systemic effects	25 mg/kg
	Workers	Inhalation	Long-term exposure, Systemic effects	150 mg/m ³
	Consumers	Skin contact	Long-term exposure, Systemic effects	11 mg/kg
	Consumers	Inhalation	Long-term exposure, Systemic effects	32 mg/m ³
	Consumers	Ingestion	Long-term exposure, Systemic effects	11 mg/kg
phosphoric acid	Workers	Inhalation	Long-term local effects	1 mg/m ³
	Workers	Inhalation	Acute local effects	2 mg/m ³
	Consumers	Inhalation	Long-term local effects	0,73 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
2-methoxy-1-methylethyl acetate	Fresh water	0,635 mg/l
	Marine water	0,0635 mg/l
	Intermittent releases	6,35 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	3,29 mg/kg
	Marine sediment	0,329 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1
SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025
Print Date 05.01.2026

	Soil	0,29 mg/kg
--	------	------------

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : butyl-rubber
Break through time : > 480 min
Glove thickness : 0,7 mm

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Environmental exposure controls

General advice : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : light yellow

Odour Threshold : No data available

Melting point/freezing point : < 0 °C
Method: derived

Initial boiling point and boiling range : 146,00 °C
Method: derived

Upper explosion limit / Upper flammability limit : 10,80 %(V)

Lower explosion limit / Lower flammability limit : 1,00 %(V)

Flash point : 42,00 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1
SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025
Print Date 05.01.2026

Method: 48 (Abel-Pensky) DIN 51755

Auto-ignition temperature	:	> 200 °C Method: DIN 51794
Decomposition temperature	:	No data available
pH	:	3 (20 °C) Concentration: 1 % Method: Universal pH-value indicator
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20,000 mm ² /s (20,00 °C) 27,000 mm ² /s (40,00 °C)
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	5 hPa (20,00 °C) Method: derived
Relative density	:	No data available
Density	:	1,0250 g/cm ³ (20,00 °C) Method: 4 (20°C oscillating U-tube)
Bulk density	:	Not applicable
Relative vapour density	:	No data available

9.2 Other information

Flammability (liquids)	:	Sustains combustion
Evaporation rate	:	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1
SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025
Print Date 05.01.2026

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.
Gives off hydrogen by reaction with metals.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents
Metals

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Remarks: No data available

Components:

Phosphoric acid polyester:

Acute oral toxicity : LD50 Oral (Rat, male and female): > 5.000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 (Rat, female): > 5.000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1
SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025
Print Date 05.01.2026

Acute oral toxicity : Remarks: No data available
Acute inhalation toxicity : Remarks: No data available
Acute dermal toxicity : LD50 (Rabbit, male and female): > 3.160 mg/kg
Method: OECD Test Guideline 402

phosphoric acid:

Acute oral toxicity : Remarks: No data available
Acute inhalation toxicity : Remarks: No data available
Acute dermal toxicity : Remarks: No data available

Skin corrosion/irritation

Causes severe burns.

Product:

Species : EPISKIN human epidermis skin constructs
Assessment : Causes burns.
Method : OECD Test Guideline 431
Result : Causes burns.
GLP : yes
Remarks : Extremely corrosive and destructive to tissue.

Components:

Phosphoric acid polyester:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

2-methoxy-1-methylethyl acetate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

phosphoric acid:

Remarks : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1
SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025
Print Date 05.01.2026

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:

Phosphoric acid polyester:

Species : Rabbit
Assessment : Irritating to eyes.
Result : Eye irritation
GLP : yes

2-methoxy-1-methylethyl acetate:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

phosphoric acid:

Remarks : No data available

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Product:

Remarks : No data available

Components:

2-methoxy-1-methylethyl acetate:

Species : Guinea pig
Method : OECD Test Guideline 406
Result : Not a skin sensitizer.
GLP : yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1
SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025
Print Date 05.01.2026

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Test Type	: Maximisation Test
Exposure routes	: Dermal
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified due to lack of data.

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

Phosphoric acid polyester:

Genotoxicity in vitro : Test Type: Ames test
Metabolic activation: with and without metabolic activation
Result: negative
GLP: yes

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse (male and female)
Method: Mutagenicity (micronucleus test)
Result: negative
GLP: yes

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Germ cell mutagenicity- : Classified based on benzene content < 0.1% (Regulation (EC)
Assessment 1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity

May cause cancer.

Product:

Remarks : No data available

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Carcinogenicity - : Classified based on benzene content < 0.1% (Regulation (EC)
Assessment 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified due to lack of data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1
SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025
Print Date 05.01.2026

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified due to lack of data.

Product:

Remarks : No data available

Repeated dose toxicity

Product:

Remarks : No data available

Components:

Phosphoric acid polyester:

Species : Rat, male and female
LOAEL : 4.000 mg/kg
Application Route : Oral
Method : OECD Test Guideline 407
GLP : yes

Aspiration toxicity

Not classified due to lack of data.

Product:

No data available

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1
SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025
Print Date 05.01.2026

levels of 0.1% or higher.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Components:

Phosphoric acid polyester:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 770 mg/l
Exposure time: 48 h
Test Type: static test
Method: DIN 38412
GLP: no

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 130 mg/l
Exposure time: 72 h
GLP: yes

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 500 mg/l
Exposure time: 16 h
Test Type: Cell multiplication inhibition test
Method: DIN 38412, L 8
GLP: no

2-methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Fish): 100 - 180 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: no

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1
SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025
Print Date 05.01.2026

Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: no

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Toxicity to fish : LL50 (Fish): 9,2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 3,2 mg/l
aquatic invertebrates
Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata): 2,6 mg/l
plants
Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes

phosphoric acid:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates
Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic : ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
plants
Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

Phosphoric acid polyester:

Biodegradability : Result: Not readily biodegradable.
Exposure time: 28 d
Method: OECD Test Guideline 301
GLP: no

2-methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F
GLP: yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1

SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025

Print Date 05.01.2026

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

2-methoxy-1-methylethyl acetate:

Partition coefficient: n- : log Pow: 1,2 (20 °C)
octanol/water pH: 6,8
Method: OECD Test Guideline 117
GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1
SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025
Print Date 05.01.2026

courses or the soil.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 2920
IMDG : UN 2920
IATA : UN 2920

14.2 UN proper shipping name

ADR : CORROSIVE LIQUID, FLAMMABLE, N.O.S.
(Orthophosphoric acid, 1-Methoxy-2-propanol acetate)
IMDG : CORROSIVE LIQUID, FLAMMABLE, N.O.S.
(Orthophosphoric acid, 1-Methoxy-2-propanol acetate)
IATA : Corrosive liquid, flammable, n.o.s.
(Orthophosphoric acid, 1-Methoxy-2-propanol acetate)

14.3 Transport hazard class(es)

ADR : 8 (3)
IMDG : 8 (3)
IATA : 8 (3)

14.4 Packing group

ADR
Packing group : II
Classification Code : CF1
Hazard Identification Number : 83
Labels : 8 (3)
Tunnel restriction code : D/E
IMDG
Packing group : II
Labels : 8 (3)
EmS Code : F-E, S-C
Remarks : IMDG Code segregation group 1 - Acids

IATA (Cargo)
Packing instruction (cargo aircraft) : 855

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1

SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025

Print Date 05.01.2026

Packing group : II
Labels : Corrosives, Flammable Liquids

IATA (Passenger)

Packing instruction : 851
(passenger aircraft)
Packing instruction (LQ) : Y840
Packing group : II
Labels : Corrosives, Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

Number on list 28: cumene

Number on list 72: benzene

Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving P5c FLAMMABLE LIQUIDS

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1

SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025

Print Date 05.01.2026

dangerous substances.

15.2 Chemical safety assessment

Not applicable

SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H314	: Causes severe skin burns and eye damage.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H350	: May cause cancer.
H411	: Toxic to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Carc.	: Carcinogenicity
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Corr.	: Skin corrosion
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
MT OEL	: Malta. Occupational Exposure Limits
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
MT OEL / TWA	: Long term exposure limit
MT OEL / STEL	: Occupational exposure limit value Short-term, 15 minute

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1

SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025

Print Date 05.01.2026

Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Skin Corr. 1B	H314
Eye Dam. 1	H318
Carc. 1B	H350
STOT SE 3	H336
STOT SE 3	H335
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Based on product data or assessment
Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MT / EN

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



BYK-W 995 SG

Version 3.1
SDB_MT

Revision Date: 03.07.2025

Date of last issue: 14.03.2025
Print Date 05.01.2026

Annex: Exposure Scenarios

Table of Contents

Number	Title
--------	-------