

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERACOL 609 N

Version: 8.1  
SDB\_IE

Revision Date: 03.12.2025

Date of last issue: 01.02.2023  
Print Date: 09.12.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : CERACOL 609 N  
UFI : JDC5-70AU-E00X-1DMP  
Product code : 000000000000112659

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Wax Additive

#### 1.3 Details of the supplier of the safety data sheet

Company : BYK Netherlands BV  
Danzigweg 23  
7418 EN Deventer  
Telephone : +31 881 220 300  
Information : Regulatory Affairs  
Telephone : +49 281 670-23532  
Telefax : +49 281 670-23533  
E-mail address : GHS.BYK@altana.com

#### 1.4 Emergency telephone

+44 1235 239670

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapor.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERACOL 609 N

Version: 8.1  
SDB\_IE

Revision Date: 03.12.2025

Date of last issue: 01.02.2023  
Print Date: 09.12.2025

Signal Word	:	Danger
Hazard Statements	:	H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
Supplemental Hazard Statements	:	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary Statements	:	<b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P261 Avoid breathing mist or vapors. P273 Avoid release to the environment. <b>Response:</b> P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. P391 Collect spillage.

### Hazardous ingredients which must be listed on the label:

- 67-63-0 propan-2-ol

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Wax modified Lanolin dispersion

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
propan-2-ol	67-63-0 200-661-7	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 30 - < 50

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERACOL 609 N

Version: 8.1  
SDB\_IE

Revision Date: 03.12.2025

Date of last issue: 01.02.2023  
Print Date: 09.12.2025

	01-2119457558-25	STOT SE 3; H336 (Central nervous system)	
Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified	64742-94-5 265-198-5 01-2119463583-34	STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 30 - < 50

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

- General advice : Move out of dangerous area.  
Show this material safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERACOL 609 N

Version: 8.1  
SDB\_IE

Revision Date: 03.12.2025

Date of last issue: 01.02.2023  
Print Date: 09.12.2025

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides

#### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERACOL 609 N

Version: 8.1  
SDB\_IE

Revision Date: 03.12.2025

Date of last issue: 01.02.2023  
Print Date: 09.12.2025

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapors/dust.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep away from heat.
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERACOL 609 N

Version: 8.1  
SDB\_IE

Revision Date: 03.12.2025

Date of last issue: 01.02.2023  
Print Date: 09.12.2025

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
propan-2-ol	67-63-0	OELV - 8 hrs (TWA)	200 ppm	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
		OELV - 15 min (STEL)	400 ppm	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Routes of exposure	Potential health effects	Value
propan-2-ol	Workers	Skin contact	Systemic effects	888 mg/kg
	Workers	Inhalation	Systemic effects	500 mg/m <sup>3</sup>
	Consumers	Skin contact	Systemic effects	319 mg/kg
	Consumers	Inhalation	Systemic effects	89 mg/m <sup>3</sup>
	Consumers	Ingestion	Systemic effects	26 mg/kg
Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified	Workers	Dermal	Long-term systemic effects	12,5 mg/kg
	Workers	Inhalation	Long-term systemic effects	151 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	7,5 mg/kg
	Consumers	Dermal	Long-term systemic effects	7,5 mg/kg
	Consumers	Inhalation	Long-term systemic effects	32 mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
propan-2-ol	Fresh water	140,9 mg/l
	Sea water	140,9 mg/l
	Fresh water sediment	552 mg/kg
	Sea sediment	552 mg/kg
	Soil	28 mg/kg

## 8.2 Exposure controls

### Personal protective equipment

Eye/face protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

### Hand protection

Material : Nitrile rubber  
Break through time : 480 min  
Glove thickness : 0,4 mm  
Protective index : Class 6

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERACOL 609 N

Version: 8.1  
SDB\_IE

Revision Date: 03.12.2025

Date of last issue: 01.02.2023  
Print Date: 09.12.2025

Remarks	:	The information is based on our own tests, on data from literature and information from protective glove producers or is based on data obtained from similar substances. The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	In the case of vapor formation use a respirator with an approved filter.
<b>Environmental exposure controls</b>		
General advice	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	:	dispersion
Color	:	yellow - brown
Odor Threshold	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	82 °C
Upper explosion limit / Upper flammability limit	:	12 %(V)
Lower explosion limit / Lower flammability limit	:	0,8 %(V)
Flash point	:	13 °C Method: 49 (Pensky-Martens), closed cup
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	insoluble

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERACOL 609 N

Version: 8.1  
SDB\_IE

Revision Date: 03.12.2025

Date of last issue: 01.02.2023  
Print Date: 09.12.2025

---

Viscosity		
Viscosity, dynamic	:	< 100 mPa.s Method: No information available.
Viscosity, kinematic	:	> 20,5 mm <sup>2</sup> /s (40 °C)
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Vapor pressure	:	No data available
Relative density	:	No data available
Density	:	0,85 g/cm <sup>3</sup> (20 °C, 1.013 hPa)
Relative vapor density	:	No data available

### 9.2 Other information

Flammability (liquids)	:	Sustains combustion
Evaporation rate	:	No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	No decomposition if stored and applied as directed. Vapors may form explosive mixture with air.
---------------------	---	--

### 10.4 Conditions to avoid

Conditions to avoid	:	Heat, flames and sparks.
---------------------	---	--------------------------

### 10.5 Incompatible materials

Materials to avoid	:	Strong acids and oxidizing agents
--------------------	---	-----------------------------------

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERACOL 609 N

Version: 8.1  
SDB\_IE

Revision Date: 03.12.2025

Date of last issue: 01.02.2023  
Print Date: 09.12.2025

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified due to lack of data.

##### Product:

Acute oral toxicity : Remarks: No data available

##### Components:

##### **propan-2-ol:**

Acute dermal toxicity : LD50 (Rabbit): 12.800 mg/kg

##### **Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

##### **Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

##### Components:

##### **Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Repeated exposure may cause skin dryness or cracking.  
GLP : yes

##### **Serious eye damage/eye irritation**

Causes serious eye irritation.

##### Product:

Remarks : Causes serious eye irritation.

##### Components:

##### **Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERACOL 609 N

Version: 8.1  
SDB\_IE

Revision Date: 03.12.2025

Date of last issue: 01.02.2023  
Print Date: 09.12.2025

---

### Respiratory or skin sensitization

#### Skin sensitization

Not classified due to lack of data.

#### Respiratory sensitization

Not classified due to lack of data.

#### Product:

Remarks : No data available

#### Components:

##### propan-2-ol:

Test Type : Buehler Test  
Routes of exposure : Dermal  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitization.  
GLP : yes

##### Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Not a skin sensitizer.  
GLP : No information available.

### Germ cell mutagenicity

Not classified due to lack of data.

#### Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

### Carcinogenicity

Not classified due to lack of data.

#### Product:

Remarks : No data available

### Reproductive toxicity

Not classified due to lack of data.

#### Product:

Effects on fertility : Remarks: No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERACOL 609 N

Version: 8.1  
SDB\_IE

Revision Date: 03.12.2025

Date of last issue: 01.02.2023  
Print Date: 09.12.2025

Effects on fetal development : Remarks: No data available

### STOT-single exposure

May cause drowsiness or dizziness.

#### Product:

Remarks : No data available

### STOT-repeated exposure

Not classified due to lack of data.

#### Product:

Remarks : No data available

### Repeated dose toxicity

#### Product:

Remarks : No data available

### Aspiration toxicity

Not classified due to lack of data.

#### Product:

No data available

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERACOL 609 N

Version: 8.1  
SDB\_IE

Revision Date: 03.12.2025

Date of last issue: 01.02.2023  
Print Date: 09.12.2025

### SECTION 12: Ecological information

#### 12.1 Toxicity

**Product:**

Toxicity to fish : Remarks: No data available

**Components:**

**Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Method: OECD Test Guideline 203  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 - 10 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata): 11 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
GLP: yes

NOELR (Pseudokirchneriella subcapitata): 2,5 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
GLP: yes

#### 12.2 Persistence and degradability

**Product:**

Biodegradability : Remarks: No data available

**Components:**

**Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:**

Biodegradability : Result: Inherently biodegradable.  
Method: OECD Test Guideline 301F  
GLP: no

#### 12.3 Bioaccumulative potential

**Product:**

Bioaccumulation : Remarks: No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERACOL 609 N

Version: 8.1  
SDB\_IE

Revision Date: 03.12.2025

Date of last issue: 01.02.2023  
Print Date: 09.12.2025

---

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR : UN 1219  
RID : UN 1219

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERACOL 609 N

Version: 8.1  
SDB\_IE

Revision Date: 03.12.2025

Date of last issue: 01.02.2023  
Print Date: 09.12.2025

**IMDG** : UN 1219

**IATA** : UN 1219

### 14.2 UN proper shipping name

**ADR** : ISOPROPANOL, SOLUTION

**RID** : ISOPROPANOL, SOLUTION

**IMDG** : ISOPROPANOL, SOLUTION  
(Alkyl (C3-C5) benzenes)

**IATA** : Isopropanol, solution

### 14.3 Transport hazard class(es)

**ADR** : 3

**RID** : 3

**IMDG** : 3

**IATA** : 3

### 14.4 Packing group

#### **ADR**

Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3  
Tunnel restriction code : D/E

#### **RID**

Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

#### **IMDG**

Packing group : II  
Labels : 3  
EmS Code : F-E, S-D

#### **IATA (Cargo)**

Packing instruction (cargo aircraft) : 364  
Packing group : II  
Labels : Flammable Liquids

#### **IATA (Passenger)**

Packing instruction (passenger aircraft) : 353  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

### 14.5 Environmental hazards

#### **ADR**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERACOL 609 N

Version: 8.1  
SDB\_IE

Revision Date: 03.12.2025

Date of last issue: 01.02.2023  
Print Date: 09.12.2025

Environmentally hazardous : yes

### RID

Environmentally hazardous : yes

### IMDG

Marine pollutant : yes

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3  
Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.
- REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 57).
- REACH - List of substances subject to authorisation (Annex XIV) : Not applicable
- Fire Hazard Class : A I: Flash point less than 69.8 °F, at 59 °F not miscible in water

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

E2 ENVIRONMENTAL HAZARDS

### 15.2 Chemical Safety Assessment

Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERACOL 609 N

Version: 8.1  
SDB\_IE

Revision Date: 03.12.2025

Date of last issue: 01.02.2023  
Print Date: 09.12.2025

### SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

#### Full text of H-Statements

H225	: Highly flammable liquid and vapor.
H304	: May be fatal if swallowed and enters airways.
H319	: Causes serious eye irritation.
H336	: May cause drowsiness or dizziness.
H411	: Toxic to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

#### Full text of other abbreviations

Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
STOT SE	: Specific target organ toxicity - single exposure
IE OEL	: Ireland. List of Chemical Agents and Carcinogens with Occupational Exposure Limit Values - Code of Practice, Schedule 1 and 2
IE OEL / OELV - 8 hrs (TWA)	: Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min (STEL)	: Occupational exposure limit value (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## CERACOL 609 N

Version: 8.1  
SDB\_IE

Revision Date: 03.12.2025

Date of last issue: 01.02.2023  
Print Date: 09.12.2025

Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 2	H225
Eye Irrit. 2	H319
STOT SE 3	H336
Aquatic Chronic 2	H411

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IE / EN