

**CERAFK 117**

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

**SECTION 1. IDENTIFICATION**

Product name : CERAFK 117

**Manufacturer or supplier's details**Company : BYK USA LLC  
524 South Cherry Street  
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : [www.byk.com](http://www.byk.com)E-mail address : [BRIEF.BYK.NAFTA@altana.com](mailto:BRIEF.BYK.NAFTA@altana.com)Emergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1  
number 703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Wax Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable liquids : Category 4

**GHS label elements**

Signal word : Warning

Hazard statements : H227 Combustible liquid.

Precautionary statements : **Prevention:**  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.  
No smoking.

P280 Wear protective gloves/ eye protection/ face protection.

**Response:**P370 + P378 In case of fire: Use dry sand, dry chemical or  
alcohol-resistant foam to extinguish.**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

**Disposal:**P501 Dispose of contents/ container to an approved waste  
disposal plant.**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Modified Fischer Tropsch wax dispersion

## CERAFAK 117

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

### Hazardous components

Component	CAS-No.	Concentration (%)
Distillates (petroleum), hydrotreated light	64742-47-8	>= 60 - < 80
Wax	8002-74-2	>= 10 - < 30
Alcohols, C16-18, ethoxylated	68439-49-6	>= 1 - < 5

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

### SECTION 4. FIRST AID MEASURES

General advice	: Do not leave the victim unattended.
If inhaled	: Remove to fresh air. Get medical aid as soon as possible. If breathing has stopped, trained personnel should administer rescue breathing, and CPR if the heart has stopped. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: Remove contaminated clothing. Wash thoroughly with soap and water. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	: Immediately flush with plenty of water for at least 20 minutes. Get medical aid. Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Do not induce vomiting. Dilute with 1-2 glasses of water. Get medical aid. Never give anything by mouth to an unconscious person. Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: No information available.

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Foam Carbon dioxide (CO <sub>2</sub> ) Dry chemical Carbon dioxide (CO <sub>2</sub> ) Dry chemical
------------------------------	--

## CERAFAK 117

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

Unsuitable extinguishing media	: No information available.
Specific hazards during firefighting	: High volume water jet Will not explode on mechanical impact. Cool closed containers exposed to fire with water spray.
Hazardous combustion products	: Carbon oxides
Further information	: Keep away from heat and sources of ignition. Keep away from oxidizing agents. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparatus.  Wear self-contained breathing apparatus for firefighting if necessary.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Eliminate all sources of ignition. Wear protective equipment: safety glasses, gloves and an appropriate respirator.
Environmental precautions	: Prevent spilled material from entering the ground, water and/or air by using appropriate containment methods.  Prevent further leakage or spillage if safe to do so.
Methods and materials for containment and cleaning up	: Stop leak. Dike and contain spill. Absorb with suitable material and remove with sparkless shovel and/or scoop.  Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Avoid contact with skin and eyes. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Take precautionary measures against static discharges. Containers should be grounded when being emptied. Ensure all equipment is electrically grounded before beginning transfer operations. Vapours may travel to areas away from work site before igniting/flashing back to Vapour source.
-------------------------	--

## CERAFAK 117

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

- Keep container closed when not in use.  
 Handle as an industrial chemical.  
 Avoid formation of aerosol.  
 For personal protection see section 8.  
 Smoking, eating and drinking should be prohibited in the application area.  
 Provide sufficient air exchange and/or exhaust in work rooms.  
 Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep in a dry, cool and well-ventilated place.  
 Keep product and empty container away from heat and sources of ignition.  
 No smoking.  
 Keep container tightly closed in a dry and well-ventilated place.  
 Observe label precautions.  
 Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Keep away from oxidizing agents.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Wax	8002-74-2	TWA (Fumes)	2 mg/m <sup>3</sup>	ACGIH
Wax		TWA (Fumes)	2 mg/m <sup>3</sup>	OSHA P0

Hazardous components without workplace control parameters

**Engineering measures** : Use with local exhaust ventilation.

#### Personal protective equipment

Respiratory protection : Unless air monitoring demonstrates vapor/mist/dust levels are below the PEL/TLV wear a properly fitted respirator (NIOSH approved) or dust mask during exposure.

Hand protection

Material : Nitrile rubber

Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Safety glasses with side-shields  
 Eye wash bottle with pure water  
 Tightly fitting safety goggles

Skin and body protection

: Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**CERAFAK 117**

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

Hygiene measures : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
: Handle in accordance with good industrial hygiene and safety practice.  
Clean long legged, long sleeved work clothes.  
If splashing is possible, wear chemically resistant protective clothing.  
Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state : dispersion  
Colour : light yellow  
Odour : aromatic  
Odour Threshold : No data available

pH : insoluble

Melting point/ range : not determined  
Boiling point/boiling range : 379 °F (193 °C)  
(1,013 hPa)

Vapour pressure : No data available

Flash point : 163 °F (73 °C)  
(1,013 hPa)  
Method: 49 (Pensky-Martens), closed cup

Upper explosion limit : 6.5 %(V)  
Lower explosion limit : 0.6 %(V)

Evaporation rate : No data available

Relative vapour density : No data available

Relative Density/Specific Gravity : No data available  
Density : 0.824 g/cm<sup>3</sup> (68 °F (20 °C))

Solubility(ies)  
Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

**CERAFAK 117**

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

Ignition temperature	:	No data available
Thermal decomposition	:	No data available
Viscosity		
Viscosity, dynamic	:	60 mPa.s (73 °F (23 °C)) Method: No information available.
Viscosity, kinematic	:	124 mm <sup>2</sup> /s (104 °F (40 °C))

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	Not classified as a reactivity hazard. No decomposition if stored and applied as directed.
Chemical stability	:	Stable; polymerization will not occur No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No data available  No decomposition if stored and applied as directed.  Vapours may form explosive mixture with air.
Conditions to avoid	:	No data available Heat, flames and sparks.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	No data available

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Ingestion  
Eyes  
Skin Absorption  
Skin contact

**Acute toxicity****Product:**

Acute oral toxicity : Remarks: No data available

Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

**Components:****64742-47-8 Distillates (petroleum), hydrotreated light:**

**CERAFAK 117**

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

**8002-74-2 Wax:**  
Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

**Skin corrosion/irritation****Product:**

Remarks: No data available

**Components:****64742-47-8 Distillates (petroleum), hydrotreated light:**

Species: Rabbit  
Result: slight irritation

**Serious eye damage/eye irritation****Product:**

Remarks: No data available

**Components:****64742-47-8 Distillates (petroleum), hydrotreated light:**

Species: Rabbit  
Result: No eye irritation  
Method: OECD Test Guideline 405  
GLP: yes

**Respiratory or skin sensitisation****Product:**

Remarks: No data available

**Components:****64742-47-8 Distillates (petroleum), hydrotreated light:**

Test Type: Maximisation Test  
Exposure routes: Skin contact  
Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: Not a skin sensitizer.  
GLP: yes

**Germ cell mutagenicity****Product:**

Genotoxicity in vitro : Remarks: No data available

**CERAFAK 117**

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

Genotoxicity in vivo : Remarks: No data available

**Carcinogenicity****Product:**

Remarks: No data available

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity****Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

**STOT - single exposure****Product:**

Remarks: No data available

**STOT - repeated exposure****Product:**

Remarks: No data available

**Repeated dose toxicity****Product:**

Remarks: No known chronic health effects.

**Aspiration toxicity****Product:**

No data available

**Experience with human exposure****Product:**

Inhalation:

**CERAFAK 117**

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

	Symptoms:	High concentrations of heated vapors may irritate the respiratory tract and mucous membranes.
Skin contact:	Symptoms:	Contact may cause irritation.
Eye contact:	Symptoms:	Contact may cause irritation.
Ingestion:	Symptoms:	Ingestion will probably irritate the digestive tract; high dosages may cause CNS depression.

**Further information****Product:**

Remarks: No data available

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:**

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

**Persistence and degradability****Product:**

Biodegradability : Remarks: No data available

**Bioaccumulative potential****Product:**

Bioaccumulation : Remarks: No data available

**Mobility in soil**

No data available

**CERAFAK 117**

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

**Other adverse effects**

No data available

**Product:**

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : Not available  
No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

EPA Hazardous Waste Code(s) : Not applicable.

Waste from residues : Dispose of in accordance with applicable local/municipal, state/provincial and federal regulations.  
Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****49 CFR**

Not regulated as a dangerous good

Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples

**CERAFAK 117**

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

This material does not contain any components with a CERCLA RQ.

**SARA 304 - Emergency Release Notification**

This material does not contain any components with a section 304 EHS RQ.

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)**

This material does not contain any components with a SARA 302 RQ.

**SARA 311/312 Hazards** : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Non-volatile (Wt) : 25 %  
Method: Not available

Non-volatile information is not a specification.

**Massachusetts Right To Know**

Distillates (petroleum), hydrotreated light 64742-47-8

Wax 8002-74-2

**CERAFAK 117**

Version 3

Revision Date 05/17/2026

Print Date 06/18/2026

**Pennsylvania Right To Know**

Distillates (petroleum), hydrotreated light	64742-47-8
Wax	8002-74-2

**New Jersey Right To Know**

**New Jersey Trade Secret Registry Number for the product (NJ TSRN)** : 800963-5760

**California Prop. 65**

**⚠ WARNING:** This product can expose you to chemicals including 1,4-Dioxane, Ethylene oxide, which is/are known to the State of California to cause cancer, and Ethylene oxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The components of this product are reported in the following inventories:**

TSCA	: All substances listed as active on the TSCA inventory
Section 5a	: The following substance(s) is/are subject to a Significant New Use Rule:
Section 4 / 12(b)	: The following substance(s) is/are subject to TSCA 12(b) export notification requirements:
DSL	: We certify that all of the components of this product are listed on the DSL.

**SECTION 16. OTHER INFORMATION**

Revision Date : 05/17/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.