

**CERAFAK 140 N**

Product code: 00000000000112650

Version 4.1 SDS\_APJ\_MY

Revision Date 28.02.2024

Print Date 06.03.2024

**SECTION 1: Identification of the hazardous chemical and of the supplier****Product identifier**

Product name : CERAFAK 140 N

Recommended use : Wax Additive

**Manufacturer or supplier's details**

Company : BYK Netherlands BV

Address : Danzigweg 23  
7418 EN Deventer

Telephone : +49 281 670-23532

Telefax : +49 281 670-23533

E-mail address : GHS.BYK@altana.com

Emergency telephone number : +60 3 6207 4347 (Malay and English)  
+65 3158 1074 (All languages)**SECTION 2: Hazards identification****Classification of the hazardous chemical**

Flammable liquids : Category 3

Acute toxicity (Oral) : Category 4

Skin corrosion/irritation : Category 2

Serious eye damage/eye  
irritation : Category 1Specific target organ toxicity -  
single exposure : Category 3 (Respiratory system, Central nervous system)Hazardous to the aquatic  
environment - chronic hazard : Category 3**Label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

## CERAFAK 140 N

Product code: 000000000000112650

Version 4.1 SDS\_APJ\_MY

Revision Date 28.02.2024

Print Date 06.03.2024

Precautionary statements

:

**Prevention:**

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.  
No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

**Other hazards which do not result in classification**

None known.

### SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture

: Mixture

Chemical nature

: Carnauba wax dispersion

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
butan-1-ol	71-36-3	>= 50 -<= 100
Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified	64742-94-5	>= 20 -< 25

### SECTION 4: First aid measures

General advice

:

Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled

:

Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical advice.

In case of skin contact

:

If skin irritation persists, call a physician.

If on skin, rinse well with water.

If on clothes, remove clothes.

In case of eye contact

:

Small amounts splashed into eyes can cause irreversible tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

## CERAFAK 140 N

Product code: 00000000000112650

Version 4.1 SDS\_APJ\_MY

Revision Date 28.02.2024

Print Date 06.03.2024

If swallowed	:	Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	No information available. No information available.
Notes to physician	:	No information available.

### SECTION 5: Firefighting measures

#### Extinguishing media

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO <sub>2</sub> ) Dry chemical
Unsuitable extinguishing media	:	High volume water jet

#### Physicochemical hazards arising from the chemical

Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon oxides

#### Special protective equipment and precautions for fire-fighters

Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Specific extinguishing methods	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

### SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

## CERAFAK 140 N

Product code: 00000000000112650

Version 4.1 SDS\_APJ\_MY

Revision Date 28.02.2024

Print Date 06.03.2024

### SECTION 7: Handling and storage

#### Handling

##### Precautions for safe handling

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national regulations.

#### Storage

##### Conditions for safe storage, including any incompatibilities

Conditions for safe storage : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Keep away from heat.

Further information on storage stability : No decomposition if stored and applied as directed.

### SECTION 8: Exposure controls and personal protection

#### Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
butan-1-ol	71-36-3	CEIL	50 ppm 152 mg/m <sup>3</sup>	MY PEL
	Further information: Skin			
		TWA	20 ppm	ACGIH

#### Individual protection measures, such as personal protective equipment

**CERAFAK 140 N**

Product code: 00000000000112650

Version 4.1 SDS\_APJ\_MY

Revision Date 28.02.2024

Print Date 06.03.2024

---

Eye/face protection	:	Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hand protection	:	
Material	:	Polyvinyl alcohol or nitrile- butyl-rubber gloves
Break through time	:	480 min
Protective index	:	Class 6
Remarks	:	Wear suitable gloves.
Respiratory protection	:	In the case of vapour formation use a respirator with an approved filter.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

---

**SECTION 9: Physical and chemical properties**

Appearance	:	dispersion
Colour	:	off-white
Odour Threshold	:	No data available
pH	:	insoluble
Melting point/freezing point	:	85 °C (1,013 hPa)
Initial boiling point and boiling range	:	130 °C (1,013 hPa)
Flash point	:	29 °C (1,013 hPa)
Evaporation rate	:	No data available
Flammability (liquids)	:	Sustains combustion
Upper explosion limit / Upper flammability limit	:	11.3 %(V)
Lower explosion limit / Lower flammability limit	:	0.6 %(V)
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.8 g/cm <sup>3</sup> (20 °C, 1,013 hPa)

**CERAFAK 140 N**

Product code: 00000000000112650

Version 4.1 SDS\_APJ\_MY

Revision Date 28.02.2024

Print Date 06.03.2024

Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: 30 mPa.s Method: No information available.
Viscosity, kinematic	: > 20.5 mm <sup>2</sup> /s ( 40 °C)

**SECTION 10: Stability and reactivity**

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: No decomposition if stored and applied as directed.

**SECTION 11: Toxicological information**

Information on likely routes of exposure : None known.

**Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate: 770 mg/kg  
Method: Calculation method

**Components:****butan-1-ol:**

Acute oral toxicity : LD50 (Rat, female): 2,292 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit, male): 3,430 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

**Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401

**CERAFAK 140 N**

Product code: 000000000000112650

Version 4.1 SDS\_APJ\_MY

Revision Date 28.02.2024

Print Date 06.03.2024

GLP: yes

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

**Skin corrosion/irritation****Product:**

Remarks : May irritate skin.  
May cause skin irritation in susceptible persons.

**Components:****butan-1-ol:**

Species : Rabbit  
Method : Draize Test  
Result : Skin irritation

**Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Repeated exposure may cause skin dryness or cracking.  
GLP : yes

**Serious eye damage/eye irritation****Product:**

Remarks : May cause irreversible eye damage.

**Components:****butan-1-ol:**

Species : Rabbit  
Result : Risk of serious damage to eyes.  
Method : OECD Test Guideline 405  
GLP : yes

**Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
GLP : yes

**Respiratory or skin sensitisation****Product:**

Remarks : No data available

**CERAFAK 140 N**

Product code: 000000000000112650

Version 4.1 SDS\_APJ\_MY

Revision Date 28.02.2024

Print Date 06.03.2024

**Components:****butan-1-ol:**

Test Type : Maximisation Test  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.  
GLP : yes

**Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:**

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Not a skin sensitizer.  
GLP : No information available.

**Germ cell mutagenicity****Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

**Carcinogenicity****Product:**

Remarks : No data available

**Reproductive toxicity****Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

**STOT - single exposure****Product:**

Remarks : No data available

**STOT - repeated exposure****Product:**

Remarks : No data available

**Aspiration toxicity****Product:**

No data available

**CERAFAK 140 N**

Product code: 00000000000112650

Version 4.1 SDS\_APJ\_MY

Revision Date 28.02.2024

Print Date 06.03.2024

**Components:****butan-1-ol:**

No aspiration toxicity classification

**Further information****Product:**

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

**SECTION 12: Ecological information****Ecotoxicity****Components:****butan-1-ol:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1,376 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,328 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic plants : ErC50 (Selenastrum capricornutum (green algae)): 225 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 4.1 mg/l  
End point: Reproduction  
Exposure time: 21 d  
Test Type: semi-static test  
Method: OECD Test Guideline 211  
GLP: yes

**Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Method: OECD Test Guideline 203  
GLP: yes

**CERAFAK 140 N**

Product code: 000000000000112650

Version 4.1 SDS\_APJ\_MY

Revision Date 28.02.2024

Print Date 06.03.2024

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 - 10 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata): 11 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
GLP: yes

NOELR (Pseudokirchneriella subcapitata): 2.5 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
GLP: yes

**Persistence and degradability****Product:**

Biodegradability : Remarks: No data available

**Components:****butan-1-ol:**

Biodegradability : aerobic  
Result: Readily biodegradable.

**Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:**

Biodegradability : Result: Inherently biodegradable.  
Method: OECD Test Guideline 301F  
GLP: no

**Bioaccumulative potential****Product:**

Bioaccumulation : Remarks: No data available

**Components:****butan-1-ol:**

Partition coefficient: n-octanol/water : log Pow: 1 (25 °C)  
pH: 7  
Method: OECD Test Guideline 117  
GLP: yes

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Additional ecological : An environmental hazard cannot be excluded in the event of

**CERAFAK 140 N**

Product code: 000000000000112650

Version 4.1 SDS\_APJ\_MY

Revision Date 28.02.2024

Print Date 06.03.2024

information

unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

**SECTION 13: Disposal information****Disposal methods**

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14: Transport information****International Regulations****IATA-DGR**

- UN/ID No. : UN 1120  
Proper shipping name : Butanols, solution  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

**IMDG-Code**

- UN number : UN 1120  
Proper shipping name : BUTANOLS, solution  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-D  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**SECTION 15: Regulatory information**

## CERAFAK 140 N

Product code: 00000000000112650

Version 4.1 SDS\_APJ\_MY

Revision Date 28.02.2024

Print Date 06.03.2024

### Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

### SECTION 16: Other information

Date format : dd.mm.yyyy

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
 MY PEL : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

ACGIH / TWA : 8-hour, time-weighted average  
 MY PEL / CEIL : Ceiling limit airborne concentration

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is

**CERAFAK 140 N**

Product code: 000000000000112650

Version 4.1 SDS\_APJ\_MY

Revision Date 28.02.2024

Print Date 06.03.2024

not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MY / EN