

# CERAFLOUR 961

Highly effective wax additive for improved degassing of powder coatings on porous substrates.

## Product data

### Composition

Micronized, modified Fischer-Tropsch wax

### Typical properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

|                                 |                        |
|---------------------------------|------------------------|
| Density (20 °C):                | 0.95 g/cm <sup>3</sup> |
| Melting point:                  | 140 °C                 |
| Particle size distribution D50: | 5 µm                   |
| Particle size distribution D90: | 11 µm                  |
| Delivery form:                  | micropowder            |

### Storage and transportation

Product shelf life in unopened original packaging: 24 months

Temperature sensitive. To be stored and transported at a temperature below 50 °C.

## Applications

### Powder coatings

#### Special features and benefits

The additive improves the degassing of powder coatings, which are applied to porous substrates. It reduces the formation of pinholes and air bubbles and optimizes scratch resistance.

#### Recommended use

CERAFLOUR 961 is used in powder coatings based on polyester/TGIC/Beta-HAA/epoxy-functional glycidyl esters, polyester/epoxy, polyurethane, acrylate, and epoxy.

#### Recommended levels

0.5-2 % additive (as supplied) based on the total formulation when extruding with all formulation components.

The above recommended levels can be used for orientation. The optimum dosage should be determined by application-related test series.

#### Incorporation and processing instructions

The product should be mixed with the resin, hardener, pigments and other additives using a high-speed mixer and extruded along with all components.



Your local  
contact

#### BYK-Chemie GmbH

Abelstraße 45  
46483 Wesel  
Germany  
Tel +49 281 670-0  
[info@byk.com](mailto:info@byk.com)  
[www.byk.com](http://www.byk.com)



Download  
our app:  
[byk.com/app](http://byk.com/app)

ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK-AQUAGEL®, BYK®-DYNWET®, BYK-MAX®, BYK®-SILCLEAN®, BYKANOL®, BYKCARE®, BYKETOL®, BYKJET®, BYKONITE®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, NANOBYK®, OPTIBENT®, OPTIGEL®, PURABYK®, RECYCLOBYK®, RHEOBYK®, SCONA®, SILBYK®, TIXOGEL® and VISCOBYK® are registered trademarks of the BYK group.

The information contained herein is based on our current knowledge and experience. No warranties, guarantees and/or assurances of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. Any information about suitability, use or application of the products is non-binding and does not constitute a commitment regarding the products' properties, use or application. Contractual terms and conditions, in particular agreed product specifications, always take precedence. We recommend that you test our products in preliminary trials to determine their suitability for your intended purpose prior to use. We reserve the right to make any changes and to update the information herein without notice.