

CLOISITE-Ca++

Product code: 338-CSCA++25K

Version
2.0 SDS_REG_UNRevision Date:
25.11.2022Date of last issue: 21.12.2016
Date of first issue: 21.12.2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : CLOISITE-Ca++

Type of Application (Use) : Polymer Additive

Manufacturer or supplier's details

Company : BYK-Chemie GmbH

Address : Abelstrasse 45
46483 Wesel

Telephone : +49 281 670-23532

Telefax : +49 281 670-23533

E-mail address : GHS.BYK@altana.com

Emergency telephone number : Europe +44 1235 239670
Middle East/Africa +44 1235 239671
Americas +1 215 207 0061
East/South East Asia +65 3158 1074
(Local India: 000 800 100 7479)

2. HAZARDS IDENTIFICATION**GHS Classification**

Carcinogenicity : Category 1A

Specific target organ toxicity -
repeated exposure : Category 2 (Lungs)**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H350 May cause cancer.
H373 May cause damage to organs (Lungs) through prolonged
or repeated exposure.Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read
and understood.

CLOISITE-Ca++

Product code: 338-CSCA++25K
Version
2.0 SDS_REG_UN

Revision Date:
25.11.2022

Date of last issue: 21.12.2016
Date of first issue: 21.12.2016

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance
Chemical nature : Natural phyllosilicate

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO ₂)	14808-60-7	>= 1 - < 3

4. FIRST AID MEASURES

General advice : Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.

In case of skin contact : Wash off with soap and plenty of water.
If skin irritation persists, call a physician.
Wash contaminated clothing before re-use.

In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Induce vomiting immediately and call a physician.
Keep respiratory tract clear.

CLOISITE-Ca++

Product code: 338-CSCA++25K

Version

2.0 SDS_REG_UN

Revision Date:

25.11.2022

Date of last issue: 21.12.2016

Date of first issue: 21.12.2016

Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.
 Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed : No information available.
 No information available.

Notes to physician : No information available.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water

Foam
 Carbon dioxide (CO₂)
 Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire-fighting : The product itself does not burn.

Hazardous combustion products : No hazardous combustion products are known

Specific extinguishing methods : Standard procedure for chemical fires.
 Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
 Avoid dust formation.
 Avoid breathing dust.

Environmental precautions : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Keep in suitable, closed containers for disposal.

CLOISITE-Ca++

Product code: 338-CSCA++25K

Version
2.0 SDS_REG_UNRevision Date:
25.11.2022Date of last issue: 21.12.2016
Date of first issue: 21.12.2016

7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.

Advice on safe handling : Avoid spillage on floor as the product can become very slippery when wet.

Avoid formation of respirable particles.

Do not breathe vapours/dust.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the application area.

Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO ₂)	14808-60-7	TWA (Respirable fraction)	0,025 mg/m ³ (Silica)	ACGIH

Filter type : Filter type P

Hand protection
Material : Protective gloves

Hygiene measures :

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Colour : off-white

Odour : odourless

Odour Threshold : Not applicable

pH : 4,6 - 7,6 (20 °C)
Concentration: 2 %
Method: DIN 19268 (2% in water)

CLOISITE-Ca++

Product code: 338-CSCA++25K
Version
2.0 SDS_REG_UN

Revision Date:
25.11.2022

Date of last issue: 21.12.2016
Date of first issue: 21.12.2016

II	
Melting point/range	: Not applicable
Boiling point/boiling range	: Not applicable
Flash point	: Not applicable
Evaporation rate	: Not applicable
Flammability (solid, gas)	: Does not sustain combustion.
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Vapour pressure	: Not applicable
Relative vapour density	: Not applicable
Relative density	: No data available
Density	: 2,6 g/cm ³ (20 °C, 1.013 hPa)
Bulk density	: 500 - 1.100 kg/m ³
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: Not applicable
Minimum explosible dust concentration	: Not applicable

10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable
Possibility of hazardous reac-	: No decomposition if stored and applied as directed.

CLOISITE-Ca++

Product code: 338-CSCA++25K
Version
2.0 SDS_REG_UN

Revision Date:
25.11.2022

Date of last issue: 21.12.2016
Date of first issue: 21.12.2016

tions

Incompatible materials : None known.

Hazardous decomposition products : No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

Acute oral toxicity : Remarks: No data available

Skin corrosion/irritation**Product:**

Remarks: No data available

Serious eye damage/eye irritation**Product:**

Remarks: No data available

Respiratory or skin sensitisation**Product:**

Remarks: No data available

Repeated dose toxicity**Product:**

Remarks: No data available

12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Toxicity to fish :
Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates :
Remarks: No data available

CLOISITE-Ca++

Product code: 338-CSCA++25K
Version
2.0 SDS_REG_UN

Revision Date:
25.11.2022

Date of last issue: 21.12.2016
Date of first issue: 21.12.2016

Persistence and degradability**Product:**

Biodegradability : Remarks: No data available

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Contact manufacturer.

16. OTHER INFORMATION**Further information**

Training advice : Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable

CLOISITE-Ca++

Product code: 338-CSCA++25K

Version

2.0 SDS_REG_UN

Revision Date:

25.11.2022

Date of last issue: 21.12.2016

Date of first issue: 21.12.2016

dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

Other information

- : In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)
- In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)
- According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.