

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## DISPERBYK-170 TF

Version 2.0

SDB\_GB

Revision Date: 07.02.2024

Date of last issue: 05.02.2021

Print Date 21.05.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : DISPERBYK-170 TF  
Product code : 000000000000135935

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Wetting & Dispersing Additive

#### 1.3 Details of the supplier of the safety data sheet

Company : BYK-Chemie GmbH  
Abelstrasse 45  
46483 Wesel  
Telephone : +49 281 670-0  
Telefax : +49 281 65735  
  
Information : Regulatory Affairs  
Telephone : +49 281 670-23532  
Telefax : +49 281 670-23533  
E-mail address : GHS.BYK@altana.com

#### 1.4 Emergency telephone number

+44 1235 239670

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.  
Specific target organ toxicity - single exposure, Category 3, Central nervous system H336: May cause drowsiness or dizziness.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.

## DISPERBYK-170 TF

Version 2.0  
SDB\_GB

Revision Date: 07.02.2024

Date of last issue: 05.02.2021  
Print Date 21.05.2025

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing mist or vapours.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

**Hazardous components which must be listed on the label:**

- 108-65-6 2-methoxy-1-methylethyl acetate

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Solution of a polyurethane

**Components**

| Chemical name                   | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number | Classification                                                              | Concentration<br>(% w/w) |
|---------------------------------|-------------------------------------------------------|-----------------------------------------------------------------------------|--------------------------|
| 2-methoxy-1-methylethyl acetate | 108-65-6<br>203-603-9<br>01-2119475791-29             | Flam. Liq. 3; H226<br>STOT SE 3; H336                                       | >= 50 - <= 100           |
| n-butyl acetate                 | 123-86-4<br>204-658-1<br>01-2119485493-29             | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)<br>EUH066 | >= 7 - < 10              |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## DISPERBYK-170 TF

Version 2.0

SDB\_GB

Revision Date: 07.02.2024

Date of last issue: 05.02.2021

Print Date 21.05.2025

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- |                         |   |                                                                                                                                                                                     |
|-------------------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General advice          | : | Move out of dangerous area.<br>Show this safety data sheet to the doctor in attendance.<br>Do not leave the victim unattended.                                                      |
| If inhaled              | : | Consult a physician after significant exposure.<br>If unconscious, place in recovery position and seek medical advice.                                                              |
| In case of skin contact | : | If on skin, rinse well with water.<br>If on clothes, remove clothes.                                                                                                                |
| In case of eye contact  | : | Flush eyes with water as a precaution.<br>Remove contact lenses.<br>Protect unharmed eye.<br>Keep eye wide open while rinsing.<br>If eye irritation persists, consult a specialist. |
| If swallowed            | : | Keep respiratory tract clear.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person.<br>If symptoms persist, call a physician.       |

#### 4.2 Most important symptoms and effects, both acute and delayed

- |          |   |                           |
|----------|---|---------------------------|
| Symptoms | : | No information available. |
| Risks    | : | No information available. |

#### 4.3 Indication of any immediate medical attention and special treatment needed

- |           |   |                           |
|-----------|---|---------------------------|
| Treatment | : | No information available. |
|-----------|---|---------------------------|

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- |                                |   |                                                                             |
|--------------------------------|---|-----------------------------------------------------------------------------|
| Suitable extinguishing media   | : | Alcohol-resistant foam<br>Carbon dioxide (CO <sub>2</sub> )<br>Dry chemical |
| Unsuitable extinguishing media | : | High volume water jet                                                       |

#### 5.2 Special hazards arising from the substance or mixture

- |                                       |   |                                                                           |
|---------------------------------------|---|---------------------------------------------------------------------------|
| Specific hazards during fire-fighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
|---------------------------------------|---|---------------------------------------------------------------------------|

## DISPERBYK-170 TF

Version 2.0  
SDB\_GB

Revision Date: 07.02.2024

Date of last issue: 05.02.2021  
Print Date 21.05.2025

Cool closed containers exposed to fire with water spray.  
Will not explode on mechanical impact.

Hazardous combustion products : Carbon oxides  
Nitrogen oxides (NO<sub>x</sub>)

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.

## DISPERBYK-170 TF

Version 2.0  
SDB\_GB

Revision Date: 07.02.2024

Date of last issue: 05.02.2021  
Print Date 21.05.2025

- Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components                      | CAS-No.                                                                                                                                                                      | Value type (Form of exposure) | Control parameters               | Basis      |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|----------------------------------|------------|
| 2-methoxy-1-methylethyl acetate | 108-65-6                                                                                                                                                                     | TWA                           | 50 ppm<br>275 mg/m <sup>3</sup>  | 2000/39/EC |
|                                 | Further information: Identifies the possibility of significant uptake through the skin, Indicative                                                                           |                               |                                  |            |
|                                 |                                                                                                                                                                              | STEL                          | 100 ppm<br>550 mg/m <sup>3</sup> | 2000/39/EC |
|                                 | Further information: Identifies the possibility of significant uptake through the skin, Indicative                                                                           |                               |                                  |            |
|                                 |                                                                                                                                                                              | TWA                           | 50 ppm<br>274 mg/m <sup>3</sup>  | GB EH40    |
|                                 | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                               |                                  |            |
|                                 |                                                                                                                                                                              | STEL                          | 100 ppm<br>548 mg/m <sup>3</sup> | GB EH40    |
|                                 | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                               |                                  |            |
| n-butyl acetate                 | 123-86-4                                                                                                                                                                     | TWA                           | 150 ppm<br>724 mg/m <sup>3</sup> | GB EH40    |
|                                 |                                                                                                                                                                              | STEL                          | 200 ppm<br>966 mg/m <sup>3</sup> | GB EH40    |

## DISPERBYK-170 TF

Version 2.0  
SDB\_GB

Revision Date: 07.02.2024

Date of last issue: 05.02.2021  
Print Date 21.05.2025

|  |                                 |      |                                  |                  |
|--|---------------------------------|------|----------------------------------|------------------|
|  |                                 | STEL | 150 ppm<br>723 mg/m <sup>3</sup> | 2019/1831/E<br>U |
|  | Further information: Indicative |      |                                  |                  |
|  |                                 | TWA  | 50 ppm<br>241 mg/m <sup>3</sup>  | 2019/1831/E<br>U |
|  | Further information: Indicative |      |                                  |                  |

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name                  | End Use   | Exposure routes | Potential health effects   | Value                  |
|---------------------------------|-----------|-----------------|----------------------------|------------------------|
| 2-methoxy-1-methylethyl acetate | Workers   | Skin contact    | Long-term systemic effects | 796 mg/kg              |
|                                 | Workers   | Inhalation      | Long-term systemic effects | 275 mg/m <sup>3</sup>  |
|                                 | Consumers | Skin contact    | Long-term systemic effects | 320 mg/kg              |
|                                 | Consumers | Inhalation      | Long-term systemic effects | 33 mg/m <sup>3</sup>   |
|                                 | Consumers | Ingestion       | Long-term systemic effects | 36 mg/kg               |
|                                 | Workers   | Inhalation      | Acute local effects        | 550 mg/m <sup>3</sup>  |
|                                 | Consumers | Inhalation      | Acute local effects        | 33 mg/m <sup>3</sup>   |
| n-butyl acetate                 | Workers   | Inhalation      | Acute local effects        | 600 mg/m <sup>3</sup>  |
|                                 | Workers   | Inhalation      | Long-term local effects    | 300 mg/m <sup>3</sup>  |
|                                 | Consumers | Inhalation      | Acute local effects        | 300 mg/m <sup>3</sup>  |
|                                 | Consumers | Inhalation      | Long-term local effects    | 35,7 mg/m <sup>3</sup> |
|                                 | Workers   | Dermal          | Long-term systemic effects | 11 mg/kg               |
|                                 | Workers   | Dermal          | Acute systemic effects     | 11 mg/kg               |
|                                 | Consumers | Dermal          | Long-term systemic effects | 6 mg/kg                |
|                                 | Consumers | Dermal          | Acute systemic effects     | 6 mg/kg                |
|                                 | Consumers | Oral            | Long-term systemic effects | 2 mg/m <sup>3</sup>    |
|                                 | Consumers | Oral            | Acute systemic effects     | 2 mg/m <sup>3</sup>    |

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name                  | Environmental Compartment | Value       |
|---------------------------------|---------------------------|-------------|
| 2-methoxy-1-methylethyl acetate | Fresh water               | 0,635 mg/l  |
|                                 | Marine water              | 0,0635 mg/l |
|                                 | Intermittent releases     | 6,35 mg/l   |
|                                 | Sewage treatment plant    | 100 mg/l    |
|                                 | Fresh water sediment      | 3,29 mg/kg  |
|                                 | Marine sediment           | 0,329 mg/kg |
|                                 | Soil                      | 0,29 mg/kg  |
| n-butyl acetate                 | Fresh water               | 0,18 mg/l   |
|                                 | Marine water              | 0,018 mg/l  |
|                                 | Intermittent releases     | 0,36 mg/l   |
|                                 | Fresh water sediment      | 0,981 mg/kg |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## DISPERBYK-170 TF

Version 2.0

SDB\_GB

Revision Date: 07.02.2024

Date of last issue: 05.02.2021

Print Date 21.05.2025

|  |                        |              |
|--|------------------------|--------------|
|  | Marine sediment        | 0,0981 mg/kg |
|  | Soil                   | 0,0903 mg/kg |
|  | Sewage treatment plant | 35,6 mg/l    |

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles

Hand protection  
Material : butyl-rubber  
Break through time : > 480 min

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

#### Environmental exposure controls

General advice : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid  
Colour : yellow  
Odour : ester-like  
Odour Threshold : No data available

Melting point/freezing point : < 0 °C  
Method: derived

Initial boiling point and boiling range : 127 °C  
Method: derived

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : 39 °C  
Method: 48 (Abel-Pensky) DIN 51755

Auto-ignition temperature : > 200 °C  
Method: M0062 (Analytics Wesel)

Decomposition temperature : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## DISPERBYK-170 TF

Version 2.0

SDB\_GB

Revision Date: 07.02.2024

Date of last issue: 05.02.2021

Print Date 21.05.2025

|                                        |   |                                                                                   |
|----------------------------------------|---|-----------------------------------------------------------------------------------|
| pH                                     | : | 6 (20 °C)<br>Concentration: 1 %<br>Method: Universal pH-value indicator           |
| Viscosity                              |   |                                                                                   |
| Viscosity, dynamic                     | : | No data available                                                                 |
| Viscosity, kinematic                   | : | No data available                                                                 |
| Solubility(ies)                        |   |                                                                                   |
| Water solubility                       | : | insoluble                                                                         |
| Partition coefficient: n-octanol/water | : | No data available                                                                 |
| Vapour pressure                        | : | 10 hPa (20 °C)<br>Method: derived                                                 |
| Density                                | : | 1,020 g/cm <sup>3</sup> (20 °C, 1,013 hPa)<br>Method: 4 (20°C oscillating U-tube) |
| Relative vapour density                | : | No data available                                                                 |

### 9.2 Other information

|                        |   |                     |
|------------------------|---|---------------------|
| Flammability (liquids) | : | Sustains combustion |
| Evaporation rate       | : | No data available   |
| Surface tension        | : | No data available   |

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

|                     |   |                                                     |
|---------------------|---|-----------------------------------------------------|
| Hazardous reactions | : | No decomposition if stored and applied as directed. |
|                     |   | Vapours may form explosive mixture with air.        |

### 10.4 Conditions to avoid

|                     |   |                          |
|---------------------|---|--------------------------|
| Conditions to avoid | : | Heat, flames and sparks. |
|---------------------|---|--------------------------|

### 10.5 Incompatible materials

|                    |   |                   |
|--------------------|---|-------------------|
| Materials to avoid | : | No data available |
|--------------------|---|-------------------|

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## DISPERBYK-170 TF

Version 2.0

SDB\_GB

Revision Date: 07.02.2024

Date of last issue: 05.02.2021

Print Date 21.05.2025

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

###### Product:

Acute oral toxicity : Remarks: No data available

###### Components:

###### **2-methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 (Rat, female): > 5.000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

###### **n-butyl acetate:**

Acute oral toxicity : LD50 (Rat, male): > 10.000 mg/kg  
Method: OECD Test Guideline 423

Acute inhalation toxicity : LC50 (Rat, male and female): > 21,1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): > 14.000 mg/kg  
Method: OECD Test Guideline 402

##### Skin corrosion/irritation

###### Product:

Remarks : No data available

###### Components:

###### **2-methoxy-1-methylethyl acetate:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

###### **n-butyl acetate:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## DISPERBYK-170 TF

Version 2.0

SDB\_GB

Revision Date: 07.02.2024

Date of last issue: 05.02.2021

Print Date 21.05.2025

### Serious eye damage/eye irritation

#### Components:

##### 2-methoxy-1-methylethyl acetate:

|         |   |                         |
|---------|---|-------------------------|
| Species | : | Rabbit                  |
| Method  | : | OECD Test Guideline 405 |
| Result  | : | No eye irritation       |
| GLP     | : | yes                     |

##### n-butyl acetate:

|         |   |                         |
|---------|---|-------------------------|
| Species | : | Rabbit                  |
| Method  | : | OECD Test Guideline 405 |
| Result  | : | No eye irritation       |
| GLP     | : | yes                     |

### Respiratory or skin sensitisation

#### Product:

|         |   |                   |
|---------|---|-------------------|
| Remarks | : | No data available |
|---------|---|-------------------|

#### Components:

##### 2-methoxy-1-methylethyl acetate:

|         |   |                         |
|---------|---|-------------------------|
| Species | : | Guinea pig              |
| Method  | : | OECD Test Guideline 406 |
| Result  | : | Not a skin sensitizer.  |
| GLP     | : | yes                     |

##### n-butyl acetate:

|           |   |                                    |
|-----------|---|------------------------------------|
| Test Type | : | Buehler Test                       |
| Species   | : | Guinea pig                         |
| Method    | : | OECD Test Guideline 406            |
| Result    | : | Does not cause skin sensitisation. |

### Germ cell mutagenicity

#### Product:

|                       |   |                            |
|-----------------------|---|----------------------------|
| Genotoxicity in vitro | : | Remarks: No data available |
|-----------------------|---|----------------------------|

|                      |   |                            |
|----------------------|---|----------------------------|
| Genotoxicity in vivo | : | Remarks: No data available |
|----------------------|---|----------------------------|

### Carcinogenicity

#### Product:

|         |   |                   |
|---------|---|-------------------|
| Remarks | : | No data available |
|---------|---|-------------------|

### Reproductive toxicity

#### Product:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## DISPERBYK-170 TF

Version 2.0

SDB\_GB

Revision Date: 07.02.2024

Date of last issue: 05.02.2021

Print Date 21.05.2025

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

### STOT - single exposure

#### Product:

Remarks : No data available

#### Components:

#### 2-methoxy-1-methylethyl acetate:

Assessment : May cause drowsiness or dizziness.

### STOT - repeated exposure

#### Product:

Remarks : No data available

### Repeated dose toxicity

#### Product:

Remarks : No data available

### Aspiration toxicity

#### Product:

No data available

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## DISPERBYK-170 TF

Version 2.0

SDB\_GB

Revision Date: 07.02.2024

Date of last issue: 05.02.2021

Print Date 21.05.2025

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

##### Components:

##### **2-methoxy-1-methylethyl acetate:**

Toxicity to fish : LC50 (Fish): 100 - 180 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203  
GLP: no

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: no

##### **n-butyl acetate:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 44 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Scenedesmus subspicatus): 675 mg/l  
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23 mg/l  
End point: Reproduction  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

#### 12.2 Persistence and degradability

##### Product:

Biodegradability : Remarks: No data available

##### Components:

##### **2-methoxy-1-methylethyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## DISPERBYK-170 TF

Version 2.0

SDB\_GB

Revision Date: 07.02.2024

Date of last issue: 05.02.2021

Print Date 21.05.2025

GLP: yes

### **n-butyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301D

## 12.3 Bioaccumulative potential

### **Product:**

Bioaccumulation : Remarks: No data available

### **Components:**

#### **2-methoxy-1-methylethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1,2 (20 °C)  
pH: 6,8  
Method: OECD Test Guideline 117  
GLP: yes

#### **n-butyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 2,3 (25 °C)  
pH: 7  
Method: OECD Test Guideline 117  
GLP: yes

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## 12.6 Endocrine disrupting properties

### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## 12.7 Other adverse effects

### **Product:**

Additional ecological information : No data available

## DISPERBYK-170 TF

Version 2.0  
SDB\_GB

Revision Date: 07.02.2024

Date of last issue: 05.02.2021  
Print Date 21.05.2025

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- |                        |   |                                                                                                                                                                        |
|------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product                | : | Do not dispose of waste into sewer.<br>Do not contaminate ponds, waterways or ditches with chemical or used container.<br>Send to a licensed waste management company. |
| Contaminated packaging | : | Empty remaining contents.<br>Dispose of as unused product.<br>Do not re-use empty containers.<br>Do not burn, or use a cutting torch on, the empty drum.               |

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

- |      |   |         |
|------|---|---------|
| ADR  | : | UN 3272 |
| RID  | : | UN 3272 |
| IMDG | : | UN 3272 |
| IATA | : | UN 3272 |

#### 14.2 UN proper shipping name

- |      |   |                                                                  |
|------|---|------------------------------------------------------------------|
| ADR  | : | ESTERS, N.O.S.<br>(1-Methoxy-2-propanol acetate, n-Butylacetate) |
| RID  | : | ESTERS, N.O.S.<br>(1-Methoxy-2-propanol acetate, n-Butylacetate) |
| IMDG | : | ESTERS, N.O.S.<br>(1-Methoxy-2-propanol acetate, BUTYL ACETATE)  |
| IATA | : | Esters, n.o.s.<br>(1-Methoxy-2-propanol acetate, Butyl acetate)  |

#### 14.3 Transport hazard class(es)

- |      |   |   |
|------|---|---|
| ADR  | : | 3 |
| RID  | : | 3 |
| IMDG | : | 3 |
| IATA | : | 3 |

#### 14.4 Packing group

- |                              |   |     |
|------------------------------|---|-----|
| ADR                          |   |     |
| Packing group                | : | III |
| Classification Code          | : | F1  |
| Hazard Identification Number | : | 30  |
| Labels                       | : | 3   |
| Tunnel restriction code      | : | D/E |
| RID                          |   |     |
| Packing group                | : | III |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## DISPERBYK-170 TF

Version 2.0

SDB\_GB

Revision Date: 07.02.2024

Date of last issue: 05.02.2021

Print Date 21.05.2025

Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-D  
Remarks : IMDG Code segregation group - none

### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High : This product does not contain sub-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## DISPERBYK-170 TF

Version 2.0

SDB\_GB

Revision Date: 07.02.2024

Date of last issue: 05.02.2021

Print Date 21.05.2025

Concern for Authorisation (Article 59).

stances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV)

: Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c

FLAMMABLE LIQUIDS

### 15.2 Chemical safety assessment

Not applicable

## SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

### Full text of H-Statements

H226 : Flammable liquid and vapour.  
H336 : May cause drowsiness or dizziness.  
EUH066 : Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

Flam. Liq. : Flammable liquids  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
2000/39/EC / TWA : Limit Value - eight hours  
2000/39/EC / STEL : Short term exposure limit  
2019/1831/EU / TWA : Limit Value - eight hours  
2019/1831/EU / STEL : Short term exposure limit  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)  
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization;

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## DISPERBYK-170 TF

Version 2.0

SDB\_GB

Revision Date: 07.02.2024

Date of last issue: 05.02.2021

Print Date 21.05.2025

KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3

H226

STOT SE 3

H336

#### Classification procedure:

Based on product data or assessment

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN