

## GELWHITE-H XR

High-purity rheology additive based on carefully selected natural bentonite, for use in personal care applications as a thixotropic gelling agent in aqueous systems with excellent anti-settling and stabilizing properties (NATRUE Approved).

Gamma irradiation sterilized version of GELWHITE-H.



NATRUE Approved

### Product data

#### Composition

Highly purified phyllosilicate (INCI: Bentonite)

#### Typical properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Bulk density:	290–434 kg/m <sup>3</sup>
pH value (2 % in H <sub>2</sub> O):	9.5–10.5
Water content:	5–8 %
Sieve residue (200 Mesh/74 µm):	0 %
Swelling (2 g in deionized water):	min. 24 ml
Lead content:	< 40 mg/kg
Arsenic content:	< 5 mg/kg
Total viable count:	< 100 cfu/g
GE brightness:	min. 77
Color:	white
Delivery form:	powder

#### Storage and transportation

GELWHITE-H XR should be transported and stored dry in the unopened original packaging at temperatures between 0 °C and 30 °C.

Vegan

### Applications

#### Personal care

##### Special features and benefits

GELWHITE-H XR is a highly purified bentonite obtained from selectively mined, extremely pure mineral deposits by means of a unique process providing unequalled high purity, whiteness, and brightness. The additive is purely inorganic and stable against diluted acids and bases. It is highly compatible with anionic and nonionic surfactants and can be used to thicken and stabilize oil-in-water emulsions. Gels produced with GELWHITE-H XR are resistant to oxidation and microbial degradation.

**Recommended use**

Creams and lotions	<input checked="" type="checkbox"/>
Sunscreen products	<input checked="" type="checkbox"/>
Antiperspirants/deos	<input checked="" type="checkbox"/>
Facial masks	<input checked="" type="checkbox"/>
Bath and shower gels	<input checked="" type="checkbox"/>
Liquid makeup	<input checked="" type="checkbox"/>
Blush	<input checked="" type="checkbox"/>
Eye makeup	<input checked="" type="checkbox"/>
Hair care products	<input checked="" type="checkbox"/>
Hair styling products	<input checked="" type="checkbox"/>

especially recommended    recommended

**Recommended levels**

1–10 % additive (as supplied) based upon total formulation, depending on the application.

The above recommended levels can be used for orientation. The optimum dosage should be determined by application-related test series.

**Incorporation and processing instructions**

GELWHITE-H XR is hydrophilic and can be easily wetted by water. For maximum efficiency, complete dispersion of the material is required. Warm water can be used to facilitate the dispersion. The additive is added as a powder to pure water while stirring slowly. The stirring speed is then increased (800–3000 rpm) and the powder is dispersed for 15 minutes. GELWHITE-H XR should be completely hydrated (recommended hydration time: 10 minutes) before all other components of the formulation are added to the dispersion. The additive can also be used as a prepared pre-gel (with 5–10 % GELWHITE-H XR). To avoid post-thickening effects, this pre-gel should be allowed to age overnight. It is then slowly added to the water phase of the formulation while stirring at low speed.



Your local  
contact

**BYK-Chemie GmbH**

Abelstraße 45  
46483 Wesel  
Germany  
Tel +49 281 670-0  
Fax +49 281 65735

info@byk.com  
www.byk.com

ADD-MAX®, ADD-VANCE®, ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK-AQUAGEL®, BYK-DYNWET®, BYK-MAX®, BYK®-SILCLEAN®, BYKANOL®, BYKCARE®, BYKETOL®, BYKJET®, BYKO2BLOCK®, BYKONITE®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, MINERPOL®, NANOBYK®, OPTIBENT®, OPTIFLO®, OPTIGEL®, POLYAD®, PRIEX®, PURABYK®, PURE THIX®, RECYCLOBLEND®, RECYCLOBYK®, RECYCLOSSORB®, RECYCLOSTAB®, RHEOBYK®, RHEOCIN®, RHEOTIX®, SCONA®, SILBYK®, TIXOGEL® and VISCOBYK® are registered trademarks of the BYK group.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions.