

OPTIBENT-1056

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

SECTION 1. IDENTIFICATION

Product name : OPTIBENT-1056

Manufacturer or supplier's detailsCompany : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.comE-mail address : BRIEF.BYK.NAFTA@altana.comEmergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
number 703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Rheology Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Carcinogenicity : Category 1A

Specific target organ toxicity : Category 2
- repeated exposure**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H350 May cause cancer.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P281 Use personal protective equipment as required.
Response:
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
Storage:
P405 Store locked up.
Disposal:

OPTIBENT-1056

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Modified / activated phyllosilicate

Hazardous components

Component	CAS-No.	Concentration (%)
Crystalline silica (quartz)	14808-60-7	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice : Show this safety data sheet to the doctor in attendance.
 Move out of dangerous area.
 Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.
 Call a physician or poison control centre immediately.

In case of skin contact : Wash off with soap and plenty of water.
 If skin irritation persists, call a physician.
 Wash contaminated clothing before re-use.
 Remove contaminated clothing. Wash thoroughly with soap and water.

In case of eye contact : Remove contact lenses.
 Protect unharmed eye.
 Keep eye wide open while rinsing.
 Immediately flush with plenty of water for at least 20 minutes.
 Get medical aid.

If swallowed : Induce vomiting immediately and call a physician.
 Keep respiratory tract clear.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.
 Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed : No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

OPTIBENT-1056

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

Unsuitable extinguishing media	: Carbon dioxide (CO2) : No information available.
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses. May release toxic, irritating and/or corrosive gases.
Further information	: Standard procedure for chemical fires. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Prevent fire extinguishing water from contaminating surface water or the ground water system. Immediately evacuate personnel to safe areas.
Special protective equipment for firefighters	: Structural fire-fighting protective clothing provides limited protection in fire situations only. Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Avoid dust formation. Do not touch or walk through spill
Environmental precautions	: Avoid dust formation. Avoid breathing dust. : If the product contaminates rivers and lakes or drains inform respective authorities. Prevent spilled material from entering the ground, water and/or air by using appropriate containment methods. Do not flush into surface water or sanitary sewer system.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Prevent further leakage or spillage if safe to do so. Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Do not breathe vapours/dust. Avoid contact with skin and eyes. Provide sufficient air exchange and/or exhaust in work rooms. Avoid formation of respirable particles. Do not breathe vapours/dust. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the
-------------------------	--

OPTIBENT-1056

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

application area.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Crystalline silica (quartz)	14808-60-7	TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
Crystalline silica (quartz)		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
Crystalline silica (quartz)		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0
Crystalline silica (quartz)		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH
Crystalline silica (quartz)		TWA (Respirable dust)	0.05 mg/m ³ (Silica)	NIOSH REL
Crystalline silica (quartz)		TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
Crystalline silica (quartz)		PEL (respirable)	0.05 mg/m ³	OSHA CARC

Further occupational exposure limits

Description	Value type	Control parameters	Basis
inert or nuisance dust	TWA	50Million particles per cubic foot total dust	OSHA Z-3
	TWA	15 mg/m ³ total dust	OSHA Z-3
	TWA	5 mg/m ³	OSHA Z-3

OPTIBENT-1056

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

		respirable fraction	
	TWA	15Million particles per cubic foot respirable fraction	OSHA Z-3

Engineering measures : Use with local exhaust ventilation.
Engineering and/or work practice controls should be implemented to maintain exposure to respirable crystalline silica below the permissible exposure limit.

Personal protective equipment

Respiratory protection : When using this product at elevated temperatures, wear a respirator with a vapour filter (see section 8).
If there is potential for overexposure, wear a respirator that is appropriate for the state of matter (mist/vapor/aerosol/particulate) and is NIOSH approved and properly fitted in accordance with applicable regulations

In the case of dust or aerosol formation use respirator with an approved filter.

Dust safety masks are recommended when the dust concentration is more than 10 mg/m³.

Hand protection
Material

: Protective gloves

Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Ensure that eyewash stations and safety showers are close to the workstation location.

Wear eye/face protection if there is potential for direct contact of vapors/mists/dusts/aerosol/liquid to the eye or face.

Skin and body protection

Eye wash bottle with pure water
Tightly fitting safety goggles
: Dust impervious protective suit
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : powder
Colour : off-white
Odour : odourless
pH : 9.6, Concentration: 2 % (73 °F (23 °C)) Method: measured

OPTIBENT-1056

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

Melting point/ range	: Not applicable
Boiling point/boiling range	: Not applicable
Vapour pressure	: Not applicable
Flash point	: Not applicable
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Evaporation rate	: Not applicable
Flammability (solid, gas)	: does not ignite
Relative vapour density	: Not applicable
Relative Density/Specific Gravity	: No data available
Particle size	: No data available
Density	: No data available
Bulk density	: 600 - 900 kg/m ³
Solubility(ies)	
Water solubility	: slightly soluble
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Auto-ignition temperature	: Not applicable
Thermal decomposition	: Not applicable
Viscosity	
Viscosity, dynamic	: Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: Stable under recommended storage conditions. No hazards to be specially mentioned.
	No data available

OPTIBENT-1056

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

Dust may form explosive mixture in air.

No data available

Conditions to avoid	:	No data available
Incompatible materials	:	None known.
Hazardous decomposition products	:	No decomposition if stored and applied as directed. No data available

SECTION 11. TOXICOLOGICAL INFORMATION
Information on likely routes of exposure
Acute toxicity
Product:

Acute oral toxicity : Remarks: No data available

Skin corrosion/irritation
Product:

Remarks: No data available

Serious eye damage/eye irritation
Product:

Remarks: No data available

Respiratory or skin sensitisation
Product:

Remarks: No data available

Carcinogenicity

IARC	Group 1: Carcinogenic to humans	
	Crystalline silica (quartz)	14808-60-7
OSHA	OSHA specifically regulated carcinogen	
	Crystalline silica (quartz)	14808-60-7
NTP	Known to be human carcinogen	
	Crystalline silica (quartz)	14808-60-7

OPTIBENT-1056

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

Repeated dose toxicity**Product:**

Remarks: No data available

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**Toxicity to fish :
Remarks: No data availableToxicity to daphnia and other :
aquatic invertebrates Remarks: No data available**Persistence and degradability****Product:**

Biodegradability : Remarks: No data available

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological :
information No data available

OPTIBENT-1056

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

- Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Dispose of in accordance with applicable local/municipal, state/provincial and federal regulations.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

This material does not contain any components with a CERCLA RQ.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

- SARA 311/312 Hazards** : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

OPTIBENT-1056

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM1 Intermediate or Final VOC's (40 CFR 60.489).

Massachusetts Right To Know

Crystalline silica (quartz) 14808-60-7

Pennsylvania Right To Know

Phyllosilicate -

New Jersey Right To Know

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : 800963-6395

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including Crystalline silica (quartz), which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : We certify that all of the components of this product are either listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).

TSCA Inventory Active List : All components of this product are listed active and/or are exempt

DSL : We certify that all of the components of this product are listed on the DSL.

OPTIBENT-1056

Version 1

Revision Date 05/17/2026

Print Date 06/18/2026

SECTION 16. OTHER INFORMATION

Revision Date : 05/17/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.