

**ANTI-TERRA-203 SG**

Version 1

Revision Date 01/07/2026

Print Date 05/07/2026

**SECTION 1. IDENTIFICATION**

Product name : ANTI-TERRA-203 SG

**Manufacturer or supplier's details**Company : BYK USA LLC  
524 South Cherry Street  
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : [www.byk.com](http://www.byk.com)

E-mail address : BRIEF.BYK.NAFTA@altana.com

Emergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1  
number 703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Wetting &amp; Dispersing Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitisation : Category 1

Carcinogenicity : Category 2

Specific target organ toxicity : Category 3 (Respiratory system, Central nervous system)  
- single exposureSpecific target organ toxicity : Category 2 (Gastrointestinal tract)  
- repeated exposure (Oral)**GHS label elements**

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.

**ANTI-TERRA-203 SG**

Version 1

Revision Date 01/07/2026

Print Date 05/07/2026

H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H373 May cause damage to organs (Gastrointestinal tract) through prolonged or repeated exposure if swallowed.

## Precautionary statements

: **Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste

## ANTI-TERRA-203 SG

Version 1

Revision Date 01/07/2026

Print Date 05/07/2026

disposal plant.

### Other hazards

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture  
 Chemical nature : Solution of an alkylammonium salt of a polycarboxylic acid

#### Hazardous components

Component	CAS-No.	Concentration (%)
Solvent naphtha, petroleum, light aromatic	64742-95-6	>= 30 - < 60
Fatty acids, C18-unsatd., trimers compds. with oleylamine	147900-93-4	>= 30 - < 60
Fatty acid, tall-oil, compds with oleylamine	85711-55-3	>= 10 - < 30
Cumene	98-82-8	>= 1 - < 5

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

### SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
 Show this safety data sheet to the doctor in attendance.  
 Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.  
 If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician.  
 If on skin, rinse well with water.  
 If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.  
 Remove contact lenses.  
 Protect unharmed eye.  
 Keep eye wide open while rinsing.  
 If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.  
 Do not give milk or alcoholic beverages.  
 Never give anything by mouth to an unconscious person.  
 If symptoms persist, call a physician.  
 Take victim immediately to hospital.

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam  
 Carbon dioxide (CO<sub>2</sub>)

## ANTI-TERRA-203 SG

Version 1

Revision Date 01/07/2026

Print Date 05/07/2026

Unsuitable extinguishing media	: Dry chemical : High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon oxides : Nitrogen oxides (NOx) : Oxides of phosphorus
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. : For safety reasons in case of fire, cans should be stored separately in closed containments. : Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. : Remove all sources of ignition. : Evacuate personnel to safe areas. : Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. : Prevent further leakage or spillage if safe to do so. : If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Avoid formation of aerosol. : Do not breathe vapours/dust. : Avoid contact with skin and eyes. : For personal protection see section 8. : Smoking, eating and drinking should be prohibited in the application area. : Take precautionary measures against static discharges. : Provide sufficient air exchange and/or exhaust in work rooms. : Open drum carefully as content may be under pressure. : Dispose of rinse water in accordance with local and national
-------------------------	--

## ANTI-TERRA-203 SG

Version 1

Revision Date 01/07/2026

Print Date 05/07/2026

regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage : No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Cumene	98-82-8	TWA	5 ppm	ACGIH
Cumene		TWA	50 ppm 245 mg/m <sup>3</sup>	OSHA Z-1
Cumene		TWA	50 ppm 245 mg/m <sup>3</sup>	OSHA P0

Hazardous components without workplace control parameters

#### Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection  
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid  
Colour : light brown

**ANTI-TERRA-203 SG**

Version 1

Revision Date 01/07/2026

Print Date 05/07/2026

Odour	: solvent-like
Odour Threshold	: No data available
pH	: 5, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-value indicator
Melting point/ range	: < 41 °F (< 5 °C) Method: derived
Initial boiling point	: 329.00 °F (165.00 °C) Method: derived
Vapour pressure	: 5 hPa (68.00 °F (20.00 °C)) Method: derived
Flash point	: 114.80 °F (46.00 °C) Method: 48 (Abel-Pensky) DIN 51755
Upper explosion limit	: 7.50 %(V)
Lower explosion limit	: 1.00 %(V)
Evaporation rate	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 0.8900 g/cm <sup>3</sup> (68.00 °F (20.00 °C)) Method: 4 (20°C oscillating U-tube)
Bulk density	: Not applicable
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: > 392 °F (> 200 °C) Method: DIN 51794
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available

**ANTI-TERRA-203 SG**

Version 1

Revision Date 01/07/2026

Print Date 05/07/2026

Viscosity, kinematic : 182.000 mm<sup>2</sup>/s (104.00 °F (40.00 °C))

Surface tension : No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.  
Chemical stability : No decomposition if stored and applied as directed.  
Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.  
Incompatible materials : Acids  
Strong oxidizing agents  
Hazardous decomposition products : None expected

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Ingestion  
Eye contact  
Skin contact

**Acute toxicity****Product:**Acute oral toxicity : LD50 (Rat, male and female): > 5,000.000000 mg/kg  
GLP: yesAcute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method**Components:****64742-95-6 Solvent naphtha, petroleum, light aromatic:**

Acute oral toxicity : LD50 (Rat): &gt; 4,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 3670 ppm  
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): &gt; 3,480 mg/kg

**147900-93-4 Fatty acids, C18-unsatd., trimers compds. with oleylamine:**Acute oral toxicity : LD50 Oral (Rat, male and female): > 1,570 mg/kg  
GLP: yes

**ANTI-TERRA-203 SG**

Version 1

Revision Date 01/07/2026

Print Date 05/07/2026

**85711-55-3 Fatty acid, tall-oil, compds with oleylamine:**

Acute oral toxicity : LD50 Oral (Rat, female): > 2,000 mg/kg  
Method: OECD Test Guideline 423  
GLP: yes

**98-82-8 Cumene:**

Acute oral toxicity : LD50 (Rat): 1,400 mg/kg

Acute inhalation toxicity : LC50 : Remarks: No data available

Acute dermal toxicity : LD50 : Remarks: No data available

**Skin corrosion/irritation****Product:**

Species: Rabbit  
Assessment: Irritating to skin.  
Result: Skin irritation  
GLP: yes

Remarks: May cause skin irritation and/or dermatitis.

**Components:****64742-95-6 Solvent naphtha, petroleum, light aromatic:**

Species: Rabbit  
Result: Moderate skin irritation

**147900-93-4 Fatty acids, C18-unsatd., trimers compds. with oleylamine:**

Species: EPISKIN human epidermis skin constructs  
Method: OECD Test Guideline 439  
Result: No skin irritation  
GLP: yes

**85711-55-3 Fatty acid, tall-oil, compds with oleylamine:**

Species: EPISKIN human epidermis skin constructs  
Method: OECD Test Guideline 439  
Result: No skin irritation  
GLP: yes

**Serious eye damage/eye irritation****Product:**

Species: Rabbit  
Result: Eye irritation  
Assessment: Irritating to eyes.  
Method: OECD Test Guideline 405  
GLP: yes

**ANTI-TERRA-203 SG**

Version 1

Revision Date 01/07/2026

Print Date 05/07/2026

Remarks: Causes serious eye irritation.

**Components:****64742-95-6 Solvent naphtha, petroleum, light aromatic:**

Species: Rabbit

Result: Eye irritation

**147900-93-4 Fatty acids, C18-unsatd., trimers compds. with oleylamine:**

Species: Bovine corneal opacity and permeability assay (BCOP)

Result: No eye irritation

Method: OECD Test Guideline 437

GLP: yes

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

GLP: yes

**85711-55-3 Fatty acid, tall-oil, compds with oleylamine:**

Species: Rabbit

Result: Risk of serious damage to eyes.

Assessment: Risk of serious damage to eyes.

Method: OECD Test Guideline 405

GLP: yes

**Respiratory or skin sensitisation****Product:**

Remarks: Causes sensitisation.

Species: Mouse

Result: Causes sensitisation.

Remarks: active ingredient

**Components:****64742-95-6 Solvent naphtha, petroleum, light aromatic:**

Test Type: Maximisation Test

Exposure routes: Dermal

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

**147900-93-4 Fatty acids, C18-unsatd., trimers compds. with oleylamine:**

Test Type: Mouse Local Lymph Node assay (LLNA)

Species: Mouse

Assessment: The product is a skin sensitiser, sub-category 1B.

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

**ANTI-TERRA-203 SG**

Version 1

Revision Date 01/07/2026

Print Date 05/07/2026

GLP: yes

**85711-55-3 Fatty acid, tall-oil, compds with oleylamine:**

Test Type: Mouse Local Lymph Node assay (LLNA)

Species: Mouse

Assessment: The product is a skin sensitiser, sub-category 1A.

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

GLP: yes

**Germ cell mutagenicity****Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

**Components:****147900-93-4 Fatty acids, C18-unsatd., trimers compds. with oleylamine:**

Genotoxicity in vitro : Test Type: Ames test  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: negative  
GLP: yes

: Test Type: Chromosome aberration test in vitro  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 473  
Result: negative  
GLP: yes

: Test Type: In vitro mammalian cell gene mutation test (mouse lymphoma)  
  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 476  
Result: negative  
GLP: yes

**85711-55-3 Fatty acid, tall-oil, compds with oleylamine:**

Genotoxicity in vitro : Test Type: Ames test  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: negative  
GLP: yes

: Test Type: Chromosome aberration test in vitro  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 473  
Result: negative

**ANTI-TERRA-203 SG**

Version 1

Revision Date 01/07/2026

Print Date 05/07/2026

GLP: yes

: Test Type: In vitro mammalian cell gene mutation test (mouse lymphoma)

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

GLP: yes

**Carcinogenicity**
**Product:**

Remarks: No data available

**IARC**

Group 2B: Possibly carcinogenic to humans

Cumene

98-82-8

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

Reasonably anticipated to be a human carcinogen

Cumene

98-82-8

**Reproductive toxicity**
**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

**Components:**
**147900-93-4 Fatty acids, C18-unsatd., trimers compds. with oleylamine:**

Effects on fertility :

Species: Rat  
 Sex: male and female  
 Application Route: Oral  
 NOAEL: 75 mg/kg,  
 F1: 75 mg/kg,  
 Method: OECD Test Guideline 422  
 GLP: yes

Effects on foetal development : Species: Rat  
 Application Route: Oral  
 75 mg/kg  
 7.1 mg/kg  
 Method: OECD Test Guideline 422

**ANTI-TERRA-203 SG**

Version 1

Revision Date 01/07/2026

Print Date 05/07/2026

GLP: yes

**85711-55-3 Fatty acid, tall-oil, compds with oleylamine:**

Effects on fertility

:

Species: Rat  
Sex: male and female  
Application Route: Oral  
NOAEL: 75 mg/kg,  
F1: 75 mg/kg,  
Method: OECD Test Guideline 422  
GLP: yes

Effects on foetal  
development

:

Species: Rat  
Application Route: Oral  
75 mg/kg  
7.1 mg/kg  
Method: OECD Test Guideline 422  
GLP: yes

**STOT - single exposure****Product:**

Remarks: No data available

**STOT - repeated exposure****Product:**

Remarks: No data available

**Repeated dose toxicity****Product:**

Remarks: Absorption of ingredients (solvents) by inhalation and/or repeated skin contact may cause injury to the liver/kidney.

Inhalation of Naphtha has caused fetotoxic effects at maternally toxic doses in laboratory animals.

Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage.

Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Cumene is an IARC 2B and NTP Group 2 Carcinogen. Cumene has caused tumors in rats and mice (lung, liver and kidney). Proposed cancer causing mechanisms for lung and liver tumors are similar to human metabolic pathways. The relevance of kidney tumors in humans is uncertain.

**Components:****147900-93-4 Fatty acids, C18-unsatd., trimers compds. with oleylamine:**

Species: Rat, male and female

NOAEL: 7.1 mg/kg

Application Route: Oral

**ANTI-TERRA-203 SG**

Version 1

Revision Date 01/07/2026

Print Date 05/07/2026

Method: OECD Test Guideline 422

GLP: yes

Target Organs: Gastrointestinal tract

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

**85711-55-3 Fatty acid, tall-oil, compds with oleylamine:**

Species: Rat, male and female

NOAEL: 7.1 mg/kg

Application Route: Oral

Method: OECD Test Guideline 422

GLP: yes

Target Organs: Gastrointestinal tract

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

**Aspiration toxicity**
**Product:**

No data available

**Components:**
**64742-95-6 Solvent naphtha, petroleum, light aromatic:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Experience with human exposure**
**Product:**

Inhalation:

Symptoms:

High concentrations of vapors may be irritating to the respiratory tract. May cause headaches, dizziness, nausea and vomiting. May cause CNS depression (drowsiness, loss of coordination and fatigue).

Skin contact:

Symptoms:

Contact will probably cause severe irritation; may cause skin sensitization.

Eye contact:

Symptoms:

Contact will probably cause irritation.

Ingestion:

Symptoms:

Ingestion may irritate the digestive tract; high dosages may cause CNS depression.

**ANTI-TERRA-203 SG**

Version 1

Revision Date 01/07/2026

Print Date 05/07/2026

**Further information**
**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**SECTION 12. ECOLOGICAL INFORMATION**
**Ecotoxicity**
**Product:**

Toxicity to fish :  
Remarks: No data available

Toxicity to daphnia and other :  
aquatic invertebrates : Remarks: No data available

**Persistence and degradability**
**Product:**

Biodegradability : Remarks: No data available

**Bioaccumulative potential**
**Product:**

Bioaccumulation : Remarks: No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological : No data available  
information

**SECTION 13. DISPOSAL CONSIDERATIONS**
**Disposal methods**

EPA Hazardous Waste : D001: Ignitable

**ANTI-TERRA-203 SG**

Version 1

Revision Date 01/07/2026

Print Date 05/07/2026

Code(s)	D018: Benzene
Waste from residues	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION**
**International Regulations**
**IATA-DGR**

UN/ID No.	: UN 1268
Proper shipping name	: Petroleum distillates, n.o.s. (Solvent naphtha)
Class	: 3
Packing group	: III
Labels	: Flammable Liquids
Packing instruction (cargo aircraft)	: 366
Packing instruction (passenger aircraft)	: 355

**IMDG-Code**

UN number	: UN 1268
Proper shipping name	: PETROLEUM DISTILLATES, N.O.S. (Solvent naphtha)
Marine Pollutant	: (Solvent naphtha)
Class	: 3
Packing group	: III
Labels	: 3
EmS Code	: F-E, S-E
Marine pollutant	: yes
Remarks	: IMDG Code segregation group - none

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations**
**49 CFR**

UN/ID/NA number	: UN 1268
Proper shipping name	: Petroleum distillates, n.o.s. (Solvent naphtha)
Class	: 3
Packing group	: III

**ANTI-TERRA-203 SG**

Version 1

Revision Date 01/07/2026

Print Date 05/07/2026

Labels : FLAMMABLE LIQUID  
 ERG Code : 128  
 Marine pollutant : no

**SECTION 15. REGULATORY INFORMATION**
**EPCRA - Emergency Planning and Community Right-to-Know Act**
**US. EPA CERCLA Hazardous Substances (40 CFR 302)**

Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 - Emergency Release Notification**

Calculated RQ exceeds reasonably attainable upper limit.

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)**

Calculated RQ exceeds reasonably attainable upper limit.

**SARA 311/312 Hazards** : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

1,2,4-Trimethylbenzene	95-63-6	16.9 %
Cumene	98-82-8	1.1 %

**Clean Air Act**

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

Cumene	98-82-8	1.1 %
--------	---------	-------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489):

**ANTI-TERRA-203 SG**

Version 1

Revision Date 01/07/2026

Print Date 05/07/2026

Cumene

98-82-8

1.1 %

Non-volatile (Wt) : 48 - 52 %  
 Method: 22 (10min/150°C)  
 DIN EN ISO 3251  
 Non-volatile information is not a specification.

**US State Regulations**
**Massachusetts Right To Know**

Cumene	98-82-8
Phenol	108-95-2

**Pennsylvania Right To Know**

Solvent naphtha, petroleum, light aromatic	64742-95-6
Fatty acids, C18-unsatd., trimers compds. with oleylamine	147900-93-4
Fatty acid, tall-oil, compds with oleylamine	85711-55-3
Cumene	98-82-8
Naphthalene	91-20-3
Ethyl benzene	100-41-4

**New Jersey Right To Know**

**New Jersey Trade Secret Registry Number for the product (NJ TSRN)** : 800963-6467

**California Prop. 65**

**⚠ WARNING:** This product can expose you to chemicals including Cumene, Naphthalene, Ethyl benzene, Benzene, which is/are known to the State of California to cause cancer, and Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The components of this product are reported in the following inventories:**

US TSCA	: All substances listed as active on the TSCA inventory
Section 5a	: No substances are subject to a Significant New Use Rule.
Section 4 / 12(b)	: No substances are subject to TSCA 12(b) export notification requirements.
CA. DSL	: We certify that all of the components of this product are listed on the DSL.

**SECTION 16. OTHER INFORMATION**

Revision Date : 01/07/2026

**ANTI-TERRA-203 SG**

Version 1

Revision Date 01/07/2026

Print Date 05/07/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.