

BYK-301

Version 6

Revision Date 03/25/2026

Print Date 04/23/2026

SECTION 1. IDENTIFICATION

Product name : BYK-301

Manufacturer or supplier's detailsCompany : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.comE-mail address : BRIEF.BYK.NAFTA@altana.comEmergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
number : 703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Surface Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 4

Acute toxicity (Oral) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 3 (Respiratory system, Central nervous system)
- single exposureSpecific target organ toxicity : Category 2 (Kidney)
- repeated exposure**GHS label elements**

Hazard pictograms :



Signal word : Warning

Hazard statements : H227 Combustible liquid.
H302 Harmful if swallowed.
H315 Causes skin irritation.

BYK-301

Version 6

Revision Date 03/25/2026

Print Date 04/23/2026

H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H361f Suspected of damaging fertility.
H373 May cause damage to organs (Kidney) through prolonged or repeated exposure.

Precautionary statements

: **Prevention:**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

BYK-301

Version 6

Revision Date 03/25/2026

Print Date 04/23/2026

Substance / Mixture : Mixture
 Chemical nature : Solution of a polyether modified polydimethylsiloxane

Hazardous components

Component	CAS-No.	Concentration (%)
2-Butoxyethanol	111-76-2	>= 30 - < 60
Octamethylcyclotetrasiloxane	556-67-2	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
 If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician.
 If on skin, rinse well with water.
 If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.
 Remove contact lenses.
 Protect unharmed eye.
 Keep eye wide open while rinsing.
 If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.
 Induce vomiting immediately and call a physician.
 Keep respiratory tract clear.
 Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.
 Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed : No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO₂)
 Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Cool closed containers exposed to fire with water spray.
 Will not explode on mechanical impact.

Do not allow run-off from fire fighting to enter drains or water courses.

BYK-301

Version 6

Revision Date 03/25/2026

Print Date 04/23/2026

Hazardous combustion products	: Carbon oxides silicone compounds formaldehyde
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Avoid formation of aerosol. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	: No smoking. Keep in a well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: Keep away from strong bases. Keep away from oxidizing agents.

BYK-301

Version 6

Revision Date 03/25/2026

Print Date 04/23/2026

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-Butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
2-Butoxyethanol		TWA	50 ppm 240 mg/m ³	OSHA Z-1
2-Butoxyethanol		TWA	5 ppm 24 mg/m ³	NIOSH REL
Octamethylcyclotetrasiloxane	556-67-2	TWA	10 ppm	US WEEL

Engineering measures : Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : Unless air monitoring demonstrates vapor/mist/dust levels are below the PEL/TLV wear a properly fitted respirator (NIOSH approved) or dust mask during exposure.
In the case of vapour formation use a respirator with an approved filter.

Hand protection

Material : Impervious butyl rubber gloves

Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid
Colour : colourless
Odour : not significant
Odour Threshold : No data available

pH : 6, Concentration: 10 % (68 °F (20 °C)) Method: Universal pH-value indicator

BYK-301

Version 6

Revision Date 03/25/2026

Print Date 04/23/2026

Melting point/ range	: No data available
Initial boiling point	: 334.40 °F (168.00 °C) Method: derived
Vapour pressure	: < 1 hPa (68.00 °F (20.00 °C)) Method: derived
Flash point	: 145.40 °F (63.00 °C) Method: 49 (Pensky-Martens)
Upper explosion limit	: 10.60 %(V)
Lower explosion limit	: 1.10 %(V)
Evaporation rate	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 0.9700 g/cm ³ (68.00 °F (20.00 °C)) Method: 4 (20°C oscillating U-tube)
Solubility(ies)	
Water solubility	: completely miscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: > 392 °F (> 200 °C) Method: DIN 51 794/ DIN prEN 14 522
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.

BYK-301

Version 6

Revision Date 03/25/2026

Print Date 04/23/2026

Incompatible materials : Strong oxidizing agents
Alkalis

Hazardous decomposition products : None known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Skin Absorption
Inhalation
Eyes
Ingestion

Acute toxicity**Product:**

Acute oral toxicity : Acute toxicity estimate : 1,047 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 23.02 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 2,302 mg/kg
Method: Calculation method

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation in susceptible persons.

Components:**111-76-2 2-Butoxyethanol:**

Species: Rabbit
Result: Skin irritation

556-67-2 Octamethylcyclotetrasiloxane:

Species: Rabbit
Result: slight irritation

Serious eye damage/eye irritation**Product:**

Remarks: Causes serious eye irritation.

Components:**111-76-2 2-Butoxyethanol:**

BYK-301

Version 6

Revision Date 03/25/2026

Print Date 04/23/2026

Species: Rabbit
Result: Eye irritation
Method: OECD Test Guideline 405
GLP: yes

556-67-2 Octamethylcyclotetrasiloxane:

Species: Rabbit
Result: Mild eye irritation

Respiratory or skin sensitisation**Product:**

Remarks: No data available

Components:**111-76-2 2-Butoxyethanol:**

Test Type: Maximisation Test
Exposure routes: Dermal
Species: Guinea pig
Method: OECD Test Guideline 406
Result: Does not cause skin sensitisation.
GLP: yes

556-67-2 Octamethylcyclotetrasiloxane:

Species: Guinea pig
Method: OECD Test Guideline 406
Result: Does not cause skin sensitisation.
GLP: yes

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity**Product:**

Remarks: No data available

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

BYK-301

Version 6

Revision Date 03/25/2026

Print Date 04/23/2026

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure**Product:**

Remarks: No data available

STOT - repeated exposure**Product:**

Remarks: No data available

Repeated dose toxicity**Product:**

Remarks: Absorption of 2-Butoxyethanol by inhalation and/or repeated skin contact may cause injury to liver, kidney and blood damage.

2-Butoxyethanol is considered fetotoxic; has caused toxic reproductive effects in laboratory animals at maternally toxic doses.

2-Butoxyethanol had both positive and negative results in in vitro mutagenicity studies.

In a 2 yr. cancer study, the NTP has determined 2-butoxyethanol has a potential to cause cancer (potentially carcinogenic to mice) but there is not enough evidence to list 2-butoxyethanol as a carcinogen. The relevance to humans is unknown.

Prolonged exposure to respirable aerosols (mists) of polyalkylene glycol has caused lung damage in rats (90 days; 0.3 mg/m³).

Inhalation (300 ppm)/ingestion (1600 mg/kg) dosages of Octamethylcyclotetrasiloxane has caused liver weight increases in laboratory animals. Liver weight changes via inhalation were reversible. A reproductive study (rats, inhalation: 700 ppm/70 days) showed a statistically significant reduction in mean litter size and implantation sites. The relevance of this data to humans is uncertain.

Aspiration toxicity**Product:**

No data available

Experience with human exposure**Product:**

Inhalation:

Symptoms:

High concentrations of vapors may be irritating to the respiratory tract. May cause

BYK-301

Version 6

Revision Date 03/25/2026

Print Date 04/23/2026

CNS depression (drowsiness, loss of coordination and fatigue); narcosis.

Skin contact:

Symptoms:

Contact will probably cause irritation.

Eye contact:

Symptoms:

Contact will probably cause irritation.

Ingestion:

Symptoms:

Ingestion may irritate the digestive tract and cause same symptoms as inhalation.

Further information
Product:

Remarks: Absorption of 2-Butoxyethanol may cause acute red blood cell damage and kidney effects. Inhalation of 2-Butoxyethanol has damaged the kidneys of laboratory animals. OSHA PEL-TWA for 2-butoxyethanol = 50 ppm (skin)

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity
Product:

Toxicity to fish

:

Remarks: No data available

Persistence and degradability
Product:

Biodegradability

:

Remarks: No data available

Bioaccumulative potential
Product:

Bioaccumulation

:

Remarks: No data available

Mobility in soil

No data available

BYK-301

Version 6

Revision Date 03/25/2026

Print Date 04/23/2026

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

EPA Hazardous Waste Code(s) : Not applicable.

Waste from residues : Dispose of in accordance with applicable local/municipal, state/provincial and federal regulations.
Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

BYK-301

Version 6

Revision Date 03/25/2026

Print Date 04/23/2026

EPCRA - Emergency Planning and Community Right-to-Know Act
US. EPA CERCLA Hazardous Substances (40 CFR 302)

Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 - Emergency Release Notification

Calculated RQ exceeds reasonably attainable upper limit.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

2-Butoxyethanol	111-76-2	47.7 %
-----------------	----------	--------

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

2-Butoxyethanol	111-76-2	47.7 %
-----------------	----------	--------

Massachusetts Right To Know

2-Butoxyethanol	111-76-2
Propylene oxide	75-56-9
Hydrogen Chloride	7647-01-0
Acetaldehyde	75-07-0
Formaldehyde	50-00-0

BYK-301

Version 6

Revision Date 03/25/2026

Print Date 04/23/2026

Ethylene oxide 75-21-8

Pennsylvania Right To Know

2-Butoxyethanol	111-76-2
Oxirane, Me, polymer with oxirane monobutyl ether (polyalkylene glycol)	9038-95-3
Polysiloxanes	-
Polyglycol	-

New Jersey Right To Know

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : 800963-5554

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including Propylene oxide, Acetaldehyde, Formaldehyde, Ethylene oxide, 1,4-Dioxane, which is/are known to the State of California to cause cancer, and Ethylene oxide, Methanol, Chloromethane, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA	: All substances listed as active on the TSCA inventory
Section 5a	: No substances are subject to a Significant New Use Rule.
Section 4 / 12(b)	: No substances are subject to TSCA 12(b) export notification requirements.
DSL	: We certify that all of the components of this product are listed on the DSL.

SECTION 16. OTHER INFORMATION

Revision Date : 03/25/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.