

BYK-301

Product code: 00000000000104211

Version 6.0 SDS_APJ_MY

Revision Date 09.11.2023

Print Date 04.12.2023

SECTION 1: Identification of the hazardous chemical and of the supplier**Product identifier**

Product name : BYK-301
Recommended use : Surface Additive

Manufacturer or supplier's details

Company : BYK-Chemie GmbH
Address : Abelstrasse 45
46483 Wesel
Telephone : +49 281 670-23532
Telefax : +49 281 670-23533
E-mail address : GHS.BYK@altana.com
Emergency telephone number : +60 3 6207 4347 (Malay and English)
+65 3158 1074 (All languages)

SECTION 2: Hazards identification**Classification of the hazardous chemical**

Acute toxicity (Oral) : Category 4
Acute toxicity (Inhalation) : Category 3
Skin corrosion/irritation : Category 2
Serious eye damage/eye irritation : Category 2

Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.

Precautionary statements :

Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P304 + P340 + P311 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a

BYK-301

Product code: 00000000000104211

Version 6.0 SDS_APJ_MY

Revision Date 09.11.2023

Print Date 04.12.2023

POISON CENTER or doctor/ physician.
P337 + P313 If eye irritation persists: Get medical advice/
attention.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container
tightly closed.

Other hazards which do not result in classification

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture
Chemical nature : Solution of a polyether modified polydimethylsiloxane

Components

Chemical name	CAS-No.	Concentration (% w/w)
2-butoxyethanol	111-76-2	>= 30 -< 50
octamethylcyclotetrasiloxane	556-67-2	>= 0.1 -< 0.25

SECTION 4: First aid measures

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.

If inhaled : Call a physician or poison control centre immediately.
If unconscious, place in recovery position and seek medical
advice.

In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.
Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : No information available.
No information available.

Notes to physician : No information available.

BYK-301

Product code: 00000000000104211

Version 6.0 SDS_APJ_MY

Revision Date 09.11.2023

Print Date 04.12.2023

SECTION 5: Firefighting measures**Extinguishing media**

- Suitable extinguishing media : Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet

Physicochemical hazards arising from the chemical

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
silicone compounds

Special protective equipment and precautions for fire-fighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Evacuate personnel to safe areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage**Handling****Precautions for safe handling**

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.

BYK-301

Product code: 00000000000104211

Version 6.0 SDS_APJ_MY

Revision Date 09.11.2023

Print Date 04.12.2023

Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.

Storage
Conditions for safe storage, including any incompatibilities

Conditions for safe storage : Prevent unauthorized access.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8: Exposure controls and personal protection
Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm 96.7 mg/m ³	MY PEL
Further information: Skin				
		TWA	20 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-butoxyethanol	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g creatinine	ACGIH BEI

Individual protection measures, such as personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hand protection

Remarks : Wear suitable gloves.
Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

BYK-301

Product code: 00000000000104211

Version 6.0 SDS_APJ_MY

Revision Date 09.11.2023

Print Date 04.12.2023

Filter type	:	Type A
Hygiene measures	:	Avoid contact with skin, eyes and clothing. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product.

SECTION 9: Physical and chemical properties

Appearance	:	liquid
Colour	:	colourless
Odour	:	not significant
Odour Threshold	:	No data available
pH	:	6 (20 °C) Concentration: 10 % Method: Universal pH-value indicator
Melting point/range	:	No data available
Initial boiling point	:	168.00 °C Method: derived
Flash point	:	63.00 °C Method: 49 (Pensky-Martens)
Evaporation rate	:	No data available
Flammability (liquids)	:	Sustains combustion
Upper explosion limit / Upper flammability limit	:	10.60 %(V)
Lower explosion limit / Lower flammability limit	:	1.10 %(V)
Vapour pressure	:	< 1 hPa (20.00 °C) Method: derived
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.9700 g/cm ³ (20.00 °C, 1,013 hPa) Method: 4 (20°C oscillating U-tube)
Solubility(ies)		
Water solubility	:	completely miscible
Solubility in other solvents	:	No data available
Partition coefficient: n-	:	No data available

BYK-301

Product code: 00000000000104211

Version 6.0 SDS_APJ_MY

Revision Date 09.11.2023

Print Date 04.12.2023

octanol/water
Auto-ignition temperature : > 200 °C
Method: DIN 51 794/ DIN prEN 14 522

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : No data available

SECTION 10: Stability and reactivity

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : No decomposition if stored and applied as directed.
Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Conditions to avoid : No data available
Incompatible materials : Strong oxidizing agents
Strong acids
Strong bases
Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Information on likely routes of exposure : None known.

Acute toxicity**Product:**

Acute oral toxicity : Acute toxicity estimate: 1,047 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 6.28 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:**2-butoxyethanol:**

Acute inhalation toxicity : LC50 (Guinea pig): 11 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Skin corrosion/irritation**Product:**

Remarks : May irritate skin.
May cause skin irritation in susceptible persons.

Components:**2-butoxyethanol:**

BYK-301

Product code: 00000000000104211

Version 6.0 SDS_APJ_MY

Revision Date 09.11.2023

Print Date 04.12.2023

Species : Rabbit
Result : Skin irritation

Serious eye damage/eye irritation**Product:**

Remarks : Causes serious eye irritation.

Components:**2-butoxyethanol:**

Species : Rabbit
Result : Eye irritation
Method : OECD Test Guideline 405
GLP : yes

Respiratory or skin sensitisation**Product:**

Remarks : No data available

Components:**2-butoxyethanol:**

Test Type : Maximisation Test
Exposure routes : Dermal
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

octamethylcyclotetrasiloxane:

Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity**Product:**

Remarks : No data available

BYK-301

Product code: 00000000000104211

Version 6.0 SDS_APJ_MY

Revision Date 09.11.2023

Print Date 04.12.2023

Reproductive toxicity**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure**Product:**

Remarks : No data available

STOT - repeated exposure**Product:**

Remarks : No data available

Repeated dose toxicity**Product:**

Remarks : No data available

Aspiration toxicity**Product:**

No data available

Further information**Product:**

Remarks : No data available

SECTION 12: Ecological information**Ecotoxicity****Product:**

Toxicity to fish : Remarks: No data available

Components:**2-butoxyethanol:**Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1,474 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,550 mg/l
Exposure time: 48 h
Test Type: static test

BYK-301

Product code: 00000000000104211

Version 6.0 SDS_APJ_MY

Revision Date 09.11.2023

Print Date 04.12.2023

Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 1,840 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: > 100 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 204

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 100 mg/l
Exposure time: 21 d
Test Type: semi-static test
Method: OECD Test Guideline 211

Persistence and degradability**Product:**

Biodegradability : Remarks: No data available

Components:**2-butoxyethanol:**

Biodegradability : aerobic
Result: Readily biodegradable.
Method: OECD Test Guideline 301B

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

Components:**2-butoxyethanol:**

Partition coefficient: n-octanol/water : log Pow: 0.81 (25 °C)
pH: 7

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : No data available

BYK-301

Product code: 00000000000104211

Version 6.0 SDS_APJ_MY

Revision Date 09.11.2023

Print Date 04.12.2023

SECTION 13: Disposal information**Disposal methods**

- Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information**International Regulations****UNRTDG**

- UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable

IATA-DGR

- UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo aircraft) : Not applicable
Packing instruction (passenger aircraft) : Not applicable

IMDG-Code

- UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
EmS Code : Not applicable
Marine pollutant : Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

Not applicable

SECTION 15: Regulatory information

BYK-301

Product code: 00000000000104211

Version 6.0 SDS_APJ_MY

Revision Date 09.11.2023

Print Date 04.12.2023

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

SECTION 16: Other information

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

MY PEL : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

ACGIH / TWA : 8-hour, time-weighted average

MY PEL / TWA : Eight-hour time-weighted average airborne concentration

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a

BYK-301

Product code: 000000000000104211

Version 6.0 SDS_APJ_MY

Revision Date 09.11.2023

Print Date 04.12.2023

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MY / EN