

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BYK-330

Version 5.0

SDB_IS

Revision Date: 18.07.2024

Date of last issue: 21.11.2022

Print Date 21.01.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : BYK-330

UFI : D611-40HC-Q00E-4TTU

Product code : 000000000000101403

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Surface Additive

1.3 Details of the supplier of the safety data sheet

Company : BYK-Chemie GmbH
Abelstrasse 45
46483 Wesel

Telephone : +49 281 670-0
Telefax : +49 281 65735

Information : Regulatory Affairs
Telephone : +49 281 670-23532
Telefax : +49 281 670-23533
E-mail address : GHS.BYK@altana.com

1.4 Emergency telephone number

Europe +44 1235 239670
Middle East/Africa +44 1235 239671
Americas +1 215 207 0061
East/South East Asia +65 3158 1074
(Local India: 000 800 100 7479)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.
Specific target organ toxicity - single exposure, Category 3, Central nervous system H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Category 2 H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

BYK-330

Version 5.0
SDB_IS

Revision Date: 18.07.2024

Date of last issue: 21.11.2022
Print Date 21.01.2025

Hazard pictograms

:



Signal word

:

Warning

Hazard statements

:

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

:

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist or vapours.
P273 Avoid release to the environment.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391 Collect spillage.

Hazardous components which must be listed on the label:

- 108-65-6 2-methoxy-1-methylethyl acetate

2.3 Other hazards

This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Solution of a polyether modified polydimethylsiloxane

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 30 - < 50
octamethylcyclotetrasiloxane [D4]	556-67-2	Repr. 2; H361f	>= 0,25 - < 0,5

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BYK-330

Version 5.0

SDB_IS

Revision Date: 18.07.2024

Date of last issue: 21.11.2022

Print Date 21.01.2025

	209-136-7 01-2119529238-36	Aquatic Chronic 1; H410	
		M-Factor (Chronic aquatic toxicity): 10	
PBT and vPvB substance :			
decamethylcyclopentasiloxane	541-02-6 208-764-9		$\geq 0,25$ - $< 0,5$
dodecamethylcyclohexasiloxane	540-97-6 208-762-8		$\geq 0,1$ - $< 0,25$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

BYK-330

Version 5.0
SDB_IS

Revision Date: 18.07.2024

Date of last issue: 21.11.2022
Print Date 21.01.2025

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containment.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

BYK-330

Version 5.0
SDB_IS

Revision Date: 18.07.2024

Date of last issue: 21.11.2022
Print Date 21.01.2025

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 275 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 550 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BYK-330

Version 5.0

SDB_IS

Revision Date: 18.07.2024

Date of last issue: 21.11.2022

Print Date 21.01.2025

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-methoxy-1-methylethyl acetate	Workers	Skin contact	Long-term systemic effects	796 mg/kg
	Workers	Inhalation	Long-term systemic effects	275 mg/m3
	Consumers	Skin contact	Long-term systemic effects	320 mg/kg
	Consumers	Inhalation	Long-term systemic effects	33 mg/m3
	Consumers	Ingestion	Long-term systemic effects	36 mg/kg
	Workers	Inhalation	Acute local effects	550 mg/m3
octamethylcyclotetra-siloxane [D4]	Consumers	Inhalation	Acute local effects	33 mg/m3
	Consumers	Oral	Acute systemic effects, Long-term systemic effects	3,7 mg/kg
	Consumers	Inhalation	Acute systemic effects, Acute local effects, Long-term systemic effects, Long-term local effects	13 mg/m3
	Workers	Inhalation	Acute systemic effects, Acute local effects, Long-term systemic effects, Long-term local effects	73 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2-methoxy-1-methylethyl acetate	Fresh water	0,635 mg/l
	Marine water	0,0635 mg/l
	Intermittent releases	6,35 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	3,29 mg/kg
	Marine sediment	0,329 mg/kg
	Soil	0,29 mg/kg
octamethylcyclotetrasiloxane [D4]	Fresh water	1,5 µg/l
	Marine water	0,15 µg/l
	Fresh water sediment	0,64 mg/kg
	Soil	0,84 mg/kg
	Sewage treatment plant	10 mg/l
	Marine sediment	0,064 mg/kg
	Hazard for predators: secondary poisoning	41 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Hand protection

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BYK-330

Version 5.0

SDB_IS

Revision Date: 18.07.2024

Date of last issue: 21.11.2022

Print Date 21.01.2025

Material : butyl-rubber
Break through time : 120,00 min

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Environmental exposure controls

General advice : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Colour : colourless
Odour : not significant
Odour Threshold : No data available

Melting point/range : < 0 °C
Method: derived

Initial boiling point : 146,00 °C
Method: derived

Upper explosion limit / Upper flammability limit : 12,00 %(V)

Lower explosion limit / Lower flammability limit : 1,50 %(V)

Flash point : 45,00 °C
Method: 48 (Abel-Pensky) DIN 51755

Auto-ignition temperature : > 200 °C
Method: DIN 51 794/ DIN prEN 14 522

Decomposition temperature : No data available

pH : 7 (20 °C)
Concentration: 1 %
Method: Universal pH-value indicator

Viscosity
Viscosity, dynamic : No data available
Viscosity, kinematic : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BYK-330

Version 5.0

SDB_IS

Revision Date: 18.07.2024

Date of last issue: 21.11.2022

Print Date 21.01.2025

Solubility(ies)

Water solubility : immiscible
Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 3 hPa (20,00 °C)
Method: derived

Relative density : No data available

Density : 0,9800 g/cm³ (20,00 °C)
Method: 4 (20°C oscillating U-tube)

Bulk density : Not applicable

Relative vapour density : No data available

9.2 Other information

Evaporation rate : No data available

Surface tension : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BYK-330

Version 5.0

SDB_IS

Revision Date: 18.07.2024

Date of last issue: 21.11.2022

Print Date 21.01.2025

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity : LD50 (Rat): > 10.000,000000 mg/kg
Method: OECD Test Guideline 401

Components:

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 (Rat, female): > 5.000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Skin corrosion/irritation

Product:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Components:

2-methoxy-1-methylethyl acetate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Serious eye damage/eye irritation

Product:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

Components:

2-methoxy-1-methylethyl acetate:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BYK-330

Version 5.0

SDB_IS

Revision Date: 18.07.2024

Date of last issue: 21.11.2022

Print Date 21.01.2025

Respiratory or skin sensitisation

Product:

Remarks : No data available

Components:

2-methoxy-1-methylethyl acetate:

Species : Guinea pig
Method : OECD Test Guideline 406
Result : Not a skin sensitizer.
GLP : yes

octamethylcyclotetrasiloxane [D4]:

Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Product:

Remarks : No data available

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure

Product:

Remarks : No data available

STOT - repeated exposure

Product:

Remarks : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BYK-330

Version 5.0

SDB_IS

Revision Date: 18.07.2024

Date of last issue: 21.11.2022

Print Date 21.01.2025

Repeated dose toxicity

Product:

Remarks : No data available

Aspiration toxicity

Product:

No data available

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Components:

2-methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Fish): 100 - 180 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: no

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: no

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BYK-330

Version 5.0

SDB_IS

Revision Date: 18.07.2024

Date of last issue: 21.11.2022

Print Date 21.01.2025

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Chemical Oxygen Demand (COD) : Remarks: No data available

Components:

2-methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F
GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

2-methoxy-1-methylethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1,2 (20 °C)
pH: 6,8
Method: OECD Test Guideline 117
GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Components:

octamethylcyclotetrasiloxane [D4]:

Assessment : Substance is very persistent and very bioaccumulative (vPvB).
: Substance is persistent, bioaccumulative, and toxic (PBT).

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

BYK-330

Version 5.0
SDB_IS

Revision Date: 18.07.2024

Date of last issue: 21.11.2022
Print Date 21.01.2025

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 3272
IMDG : UN 3272
IATA : UN 3272

14.2 UN proper shipping name

ADR : ESTERS, N.O.S.
(1-Methoxy-2-propanol acetate)
IMDG : ESTERS, N.O.S.
(1-Methoxy-2-propanol acetate, Siloxanes)
IATA : Esters, n.o.s.
(1-Methoxy-2-propanol acetate)

14.3 Transport hazard class(es)

ADR : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR
Packing group : III
Classification Code : F1

BYK-330

Version 5.0
SDB_IS

Revision Date: 18.07.2024

Date of last issue: 21.11.2022
Print Date 21.01.2025

Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : D/E

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-D
Remarks : IMDG Code segregation group - none

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 75, 3 If you intend to use this product as tattoo ink, please contact your vendor. octamethylcyclotetrasiloxane [D4] (Number on list 70) decamethylcyclopentasiloxane (Number on list 70) dodecamethylcyclohexasiloxane (Number on list 70)
---	---	---

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BYK-330

Version 5.0

SDB_IS

Revision Date: 18.07.2024

Date of last issue: 21.11.2022

Print Date 21.01.2025

II

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : octamethylcyclotetrasiloxane [D4]
decamethylcyclopentasiloxane
dodecamethylcyclohexasiloxane

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. E2 ENVIRONMENTAL HAZARDS

P5c FLAMMABLE LIQUIDS

15.2 Chemical safety assessment

Not applicable

SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H226 : Flammable liquid and vapour.
H336 : May cause drowsiness or dizziness.
H361f : Suspected of damaging fertility.
H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good La-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



BYK-330

Version 5.0

SDB_IS

Revision Date: 18.07.2024

Date of last issue: 21.11.2022

Print Date 21.01.2025

laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
STOT SE 3	H336
Aquatic Chronic 2	H411

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REG_EU / EN