

BYK-9730

Silicone and polymer-containing defoamer for all common base oils in industrial lubricant applications.

Product data

Composition

Solution of polyacrylates, containing polysiloxanes

Typical properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density (20 °C): 0.77 g/cm³
 Solvent: aromatic-free hydrocarbons
 Flash point: 42 °C
 Delivery form: liquid

Storage and transportation

Product shelf life in unopened original packaging: 36 months
 To be stored and transported at a temperature below 50 °C.

Applications

Lubricants and mold release

Special features and benefits

BYK-9730 is a versatile defoamer for lubricants. The additive is particularly suitable for the industrial lubricants sector and demonstrates excellent defoaming results in all common base oils, such as mineral oils, polyalphaolefins, naphthenic oils, and ester oils. The targeted combination of active substances ensures BYK-9730 defoams with the greatest efficiency even at low concentrations, and is simultaneously very compatible in the base oil at high concentrations. The additive thereby exhibits good long-term defoaming in the finished product after storage and has no negative impact on the transparency of the oils.

Recommended use

Mineral oils (API I-II)	<input checked="" type="checkbox"/>
Polyalphaolefins	<input checked="" type="checkbox"/>
Naphthenic oils	<input checked="" type="checkbox"/>
Ester oils	<input checked="" type="checkbox"/>

especially recommended recommended

Recommended levels

0.05-0.1 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. The optimum dosage should be determined by application-related test series.

Incorporation and processing instructions

The additive is stirred into the base oil before other components are added.



Your local
contact

BYK-Chemie GmbH

Abelstraße 45
46483 Wesel
Germany
Tel +49 281 670-0
info@byk.com
www.byk.com



Download
our app:
byk.com/app

ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK-AQUAGEL®, BYK-DYNWET®, BYK-MAX®, BYK-SILCLEAN®, BYKANOL®, BYKCARE®, BYKETOL®, BYKJET®, BYKONITE®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFK®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, NANOBYPK®, OPTIBENT®, OPTIGEL®, PURABYPK®, RECYCLOBYPK®, RHEOBYPK®, SCONA®, SILBYPK®, TIXOGEL® and VISCOBYPK® are registered trademarks of the BYK group.

The information contained herein is based on our current knowledge and experience. No warranties, guarantees and/or assurances of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. Any information about suitability, use or application of the products is non-binding and does not constitute a commitment regarding the products' properties, use or application. Contractual terms and conditions, in particular agreed product specifications, always take precedence. We recommend that you test our products in preliminary trials to determine their suitability for your intended purpose prior to use. We reserve the right to make any changes and to update the information herein without notice.