

BYK-A 526

Product code: 000000000000127351

Version 2.1 SDS_APJ_MY

Revision Date 14.10.2024

Print Date 19.02.2025

SECTION 1: Identification of the hazardous chemical and of the supplier**Product identifier**

Product name : BYK-A 526

Recommended use : Air Release Additive

Manufacturer or supplier's details

Company : BYK-Chemie GmbH

Address : Abelstrasse 45
46483 Wesel

Telephone : +49 281 670-23532

Telefax : +49 281 670-23533

E-mail address : GHS.BYK@altana.com

Emergency telephone number : +60 3 6207 4347 (Malay and English)
+65 3158 1074 (All languages)**SECTION 2: Hazards identification****Classification of the hazardous chemical**

Flammable liquids : Category 3

Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

Precautionary statements :

Prevention:P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.
P233 Keep container tightly closed.**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

BYK-A 526

Product code: 00000000000127351

Version 2.1 SDS_APJ_MY

Revision Date 14.10.2024

Print Date 19.02.2025

Other hazards which do not result in classification

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture
 Chemical nature : Solution of a polyether modified polymethylalkylsiloxane

Components

Chemical name	CAS-No.	Concentration (% w/w)
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	>= 30 -< 50
2-methoxy-1-methylethyl acetate	108-65-6	>= 3 -< 5
oct-1-ene	111-66-0	>= 0.1 -< 0.25

SECTION 4: First aid measures

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water.
 If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.
 Remove contact lenses.
 Protect unharmed eye.
 Keep eye wide open while rinsing.
 If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
 Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : No information available.
 No information available.

Notes to physician : No information available.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
 Carbon dioxide (CO₂)
 Dry chemical

Unsuitable extinguishing media : High volume water jet

Physicochemical hazards arising from the chemical

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

BYK-A 526

Product code: 00000000000127351

Version 2.1 SDS_APJ_MY

Revision Date 14.10.2024

Print Date 19.02.2025

Hazardous combustion products : Carbon oxides
formaldehyde
silicone compounds

Special protective equipment and precautions for fire-fighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage**Handling****Precautions for safe handling**

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

BYK-A 526

Product code: 000000000000127351

Version 2.1 SDS_APJ_MY

Revision Date 14.10.2024

Print Date 19.02.2025

Storage

Conditions for safe storage, including any incompatibilities

- Conditions for safe storage : No smoking.
 Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8: Exposure controls and personal protection

Control parameters

Contains no substances with occupational exposure limit values.

Individual protection measures, such as personal protective equipment (PPE)

- Eye/face protection : Eye wash bottle with pure water
 Tightly fitting safety goggles
- Skin protection : Impervious clothing
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hand protection
 Material : butyl-rubber
 Break through time : > 480 min
- Remarks : Wear suitable gloves.
 Hygiene measures : Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

- Appearance : liquid
- Colour : colourless
- Odour : not significant
- Odour Threshold : No data available
- pH : 5 (20 °C)
 Concentration: 1 %
 Method: Universal pH-value indicator
- Melting point/ range : < 0 °C
 Method: derived
- Boiling point/boiling range : 144.0 °C
 Method: derived
- Flash point : ca. 52 °C

BYK-A 526

Product code: 00000000000127351

Version 2.1 SDS_APJ_MY

Revision Date 14.10.2024

Print Date 19.02.2025

	Method: 49 (Pensky-Martens)
Evaporation rate	: No data available
Flammability (liquids)	: Sustains combustion
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: 3.0 hPa (20 °C) Method: derived
Relative vapour density	: No data available
Relative density	: No data available
Density	: ca. 0.867 g/cm ³ (20 °C, 1,013 hPa) Method: 4 (20°C oscillating U-tube) ca. 0.854 g/cm ³ (40 °C, 1,013 hPa) Method: 5 (40°C oscillating U-tube)
Bulk density	: Not applicable
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: ca. > 200 °C Method: M0062 (Analytics Wesel)
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: ca. 66 mPa.s (20 °C) Method: P/K 20°C ca. 44 mPa.s (40 °C) Method: P/K 40°C
Viscosity, kinematic	: ca. 76.12 mm ² /s (20 °C) Method: calculated ca. 51.52 mm ² /s (40 °C) Method: calculated
Surface tension	: No data available

SECTION 10: Stability and reactivity

BYK-A 526

Product code: 00000000000127351

Version 2.1 SDS_APJ_MY

Revision Date 14.10.2024

Print Date 19.02.2025

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : No decomposition if stored and applied as directed.
Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.
Incompatible materials : Strong oxidizing agents
Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Information on likely routes of exposure : None known.

Acute toxicity**Product:**

Acute oral toxicity : Remarks: No data available

Components:**2-methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 (Rat, female): > 5,000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

oct-1-ene:

Acute inhalation toxicity : LC50 (Rat): 40.2 mg/l
Test atmosphere: vapour
Method: OECD Test Guideline 403
GLP: no

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

Skin corrosion/irritation**Product:**

Remarks : No data available

Components:**2-methoxy-1-methylethyl acetate:**

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

BYK-A 526

Product code: 000000000000127351

Version 2.1 SDS_APJ_MY

Revision Date 14.10.2024

Print Date 19.02.2025

oct-1-ene:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Repeated exposure may cause skin dryness or cracking.
GLP : yes

Serious eye damage/eye irritation**Product:**

Remarks : No data available

Components:**2-methoxy-1-methylethyl acetate:**

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
GLP : yes

oct-1-ene:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
GLP : yes

Respiratory or skin sensitisation**Product:**

Remarks : No data available

Components:**2-methoxy-1-methylethyl acetate:**

Species : Guinea pig
Method : OECD Test Guideline 406
Result : Not a skin sensitizer.
GLP : yes

Germ cell mutagenicity**Components:****Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

Germ cell mutagenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity**Components:****Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

Carcinogenicity - : Classified based on benzene content < 0.1% (Regulation (EC)

BYK-A 526

Product code: 000000000000127351

Version 2.1 SDS_APJ_MY

Revision Date 14.10.2024

Print Date 19.02.2025

Assessment 1272/2008, Annex VI, Part 3, Note P)

Repeated dose toxicity**Product:**

Remarks : No data available

Further information**Product:**

Remarks : Solvents may degrease the skin.

SECTION 12: Ecological information**Ecotoxicity****Product:**Toxicity to fish :
Remarks: No data availableToxicity to daphnia and other :
aquatic invertebrates Remarks: No data available**Components:****2-methoxy-1-methylethyl acetate:**Toxicity to fish : LC50 (Fish): 100 - 180 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: noToxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): >
plants 1,000 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: no**oct-1-ene:**Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.87 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
GLP: yesToxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1 mg/l
aquatic invertebrates Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic : (Pseudokirchneriella subcapitata): 1 - 10 mg/l

BYK-A 526

Product code: 00000000000127351

Version 2.1 SDS_APJ_MY

Revision Date 14.10.2024

Print Date 19.02.2025

plants
Exposure time: 96 h
Method: OECD Test Guideline 201
GLP: yes

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

Persistence and degradability**Product:**

Biodegradability : Remarks: No data available

Components:**2-methoxy-1-methylethyl acetate:**

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F
GLP: yes

oct-1-ene:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301C
GLP: No information available.

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

Components:**2-methoxy-1-methylethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1.2 (20 °C)
pH: 6.8
Method: OECD Test Guideline 117
GLP: yes

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : No data available

SECTION 13: Disposal information**Disposal methods**

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with

BYK-A 526

Product code: 000000000000127351

Version 2.1 SDS_APJ_MY

Revision Date 14.10.2024

Print Date 19.02.2025

Contaminated packaging : chemical or used container.
 Send to a licensed waste management company.
 Empty remaining contents.
 Dispose of as unused product.
 Do not re-use empty containers.
 Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

International Regulations

IATA-DGR

UN/ID No. : UN 3272
 Proper shipping name : Esters, n.o.s.
 (1-Methoxy-2-propanol acetate)
 Class : 3
 Packing group : III
 Labels : Flammable Liquids
 Packing instruction (cargo aircraft) : 366
 Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 3272
 Proper shipping name : ESTERS, N.O.S.
 (1-Methoxy-2-propanol acetate)
 Class : 3
 Packing group : III
 Labels : 3
 EmS Code : F-E, S-D
 Marine pollutant : no
 Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15: Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

SECTION 16: Other information

BYK-A 526

Product code: 00000000000127351

Version 2.1 SDS_APJ_MY

Revision Date 14.10.2024

Print Date 19.02.2025

Date format : dd.mm.yyyy

Full text of other abbreviations

AllC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MY / EN