

BYK-A 555 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : BYK-A 555 SG
Product code : 000000000000114187

Manufacturer or supplier's details

Company : BYK USA LLC
Address : South Cherry Street 524
06492 Wallingford
Telephone : +1 203-265-2086
Telefax :
E-mail address : BRIEF.BYK.NAFTA@altana.com
Emergency telephone number : 18000 74234 (toll –free number, access from Australia
only)
+61 2 8014 4558

Importer

Company : IMCD Australia Pty Ltd
Level 1, 352 Wellington Road
Mulgrave
VIC 3170
Australia
Telephone: +61 3 8544 3100

Use of the Sub-
stance/Mixture : Air Release Additive

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3
Carcinogenicity : Category 1B
Specific target organ toxicity - : Category 3 (Respiratory system, Central nervous system)
single exposure
Short-term (acute) aquatic : Category 2
hazard
Long-term (chronic) aquatic : Category 2
hazard

GHS label elements

BYK-A 555 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

Hazard pictograms	:	   
Signal word	:	Danger
Hazard statements	:	H226 Flammable liquid and vapour. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H350 May cause cancer. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P261 Avoid breathing mist or vapours. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. P391 Collect spillage. Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

BYK-A 555 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture
Chemical nature : solution of polyolefin

Components

Chemical name	CAS-No.	Concentration (% w/w)
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified	64742-95-6	≥ 50 - ≤ 100
cumene	98-82-8	≥ 1 - < 3

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : No information available.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause cancer.

Notes to physician : No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides

Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must

BYK-A 555 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

Special protective equipment for firefighters : be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
Wear self-contained breathing apparatus for firefighting if necessary.
Hazchem Code : 3Y

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.

BYK-A 555 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
cumene	98-82-8	TWA	25 ppm 125 mg/m ³	AU OEL
Further information: Skin absorption				
		STEL	75 ppm 375 mg/m ³	AU OEL
Further information: Skin absorption				
		TWA	5 ppm	ACGIH

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Material : Nitrile rubber
Break through time : > 480 min

Remarks : Wear suitable gloves.
Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : light yellow

Odour : aromatic

Odour Threshold : No data available

pH : 7 (20 °C)
Concentration: 1 %
Method: Universal pH-value indicator

Melting point/ range : < 0 °C
Method: derived

Initial boiling point : 160.00 °C
Method: derived

BYK-A 555 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

Flash point	:	43.00 °C
		Method: 48 (Abel-Pensky) DIN 51755
Evaporation rate	:	No data available
Flammability (liquids)	:	Sustains combustion
Upper explosion limit / Upper flammability limit	:	7.50 %(V)
Lower explosion limit / Lower flammability limit	:	1.00 %(V)
Vapour pressure	:	5 hPa (20 °C) Method: derived
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.8800 g/cm ³ (20.00 °C) Method: 4 (20°C oscillating U-tube)
Bulk density	:	Not applicable
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	> 200 °C Method: DIN 51 794/ DIN prEN 14 522
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	27.000 mm ² /s (20.00 °C) 21.500 mm ² /s (40.00 °C)
Surface tension	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.

BYK-A 555 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Acids Strong oxidizing agents
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Remarks: No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : LD50 (Rabbit, male and female): > 3,160 mg/kg
Method: OECD Test Guideline 402**Skin corrosion/irritation**

Not classified due to lack of data.

Product:

Remarks : No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation
GLP	:	yes

Serious eye damage/eye irritation

Not classified due to lack of data.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
GLP	:	yes

BYK-A 555 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

Respiratory or skin sensitisation**Skin sensitisation**

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Product:

Remarks : No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Test Type	: Maximisation Test
Exposure routes	: Dermal
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: Does not cause skin sensitisation.

Chronic toxicity**Germ cell mutagenicity**

Not classified due to lack of data.

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Result: No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Germ cell mutagenicity - Assessment	: Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)
-------------------------------------	--

Carcinogenicity

May cause cancer.

Product:

Remarks : No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Carcinogenicity - Assessment	: Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)
------------------------------	--

Reproductive toxicity

Not classified due to lack of data.

BYK-A 555 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposureMay cause respiratory irritation.
May cause drowsiness or dizziness.**Product:**

Remarks : No data available

STOT - repeated exposure

Not classified due to lack of data.

Product:

Remarks : No data available

Repeated dose toxicity**Product:**

Remarks : No data available

Aspiration toxicity

Not classified due to lack of data.

Product:

No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Further information**Product:**Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Toxicity to fish :

BYK-A 555 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

Remarks: No data available

Toxicity to daphnia and other :
aquatic invertebrates

Remarks: No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**Toxicity to fish : LL50 (Fish): 9.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
GLP: yesToxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 3.2 mg/l
aquatic invertebrates : Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yesToxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata): 2.6 mg/l
plants : Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes**Persistence and degradability****Product:**

Biodegradability : Remarks: No data available

Components:**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F**Bioaccumulative potential****Product:**

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects**Product:**Additional ecological infor- : An environmental hazard cannot be excluded in the event of
mation : unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

BYK-A 555 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
-

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

- UN number : UN 1268
Proper shipping name : PETROLEUM DISTILLATES, N.O.S.
Class : 3
Packing group : III
Labels : 3

IATA-DGR

- UN/ID No. : UN 1268
Proper shipping name : Petroleum distillates, n.o.s.
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

- UN number : UN 1268
Proper shipping name : PETROLEUM DISTILLATES, N.O.S.
(Solvent naphtha)
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes
Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**ADG**

- UN number : UN 1268
Proper shipping name : PETROLEUM DISTILLATES, N.O.S.
Class : 3
Packing group : III

BYK-A 555 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026Labels : 3
Hazchem Code : 3Y**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture****SECTION 16. OTHER INFORMATION**Revision Date : 14.03.2025
Date format : dd.mm.yyyy**Full text of other abbreviations**ACGIH : USA. ACGIH Threshold Limit Values (TLV)
AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.ACGIH / TWA : 8-hour, time-weighted average
AU OEL / TWA : Exposure standard - time weighted average
AU OEL / STEL : Exposure standard - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation,

BYK-A 555 SG

Version 2.0
SDS_AU

Revision Date: 14.03.2025

Date of last issue: 17.12.2024
Print Date 05.01.2026

tion, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN