

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-ES 80

Version 7.0

SDB\_CH

Revision Date: 27.11.2022

Date of last issue: 08.10.2020

Print Date 21.01.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : BYK-ES 80  
Product code : 000000000000102250

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Additive to Increase Conductivity

#### 1.3 Details of the supplier of the safety data sheet

Company : BYK-Chemie GmbH  
Abelstrasse 45  
46483 Wesel  
Telephone : +49 281 670-0  
Telefax : +49 281 65735  
  
Information : Regulatory Affairs  
Telephone : +49 281 670-23532  
Telefax : +49 281 670-23533  
E-mail address : GHS.BYK@altana.com

#### 1.4 Emergency telephone number

+44 1235 239670

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-ES 80

Version 7.0  
SDB\_CH

Revision Date: 27.11.2022

Date of last issue: 08.10.2020  
Print Date 21.01.2025

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H226 Flammable liquid and vapour. H302 Harmful if swallowed. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	:	<b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist or vapours. P264 Wash skin thoroughly after handling. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. <b>Response:</b> P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Hazardous components which must be listed on the label:

- - 2-Butenedioic acid (Z)-, ester with 1,2-propanediol, compd. with 2-(dibutylamino)ethanol
- 78-83-1 iso-butanol

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-ES 80

Version 7.0  
SDB\_CH

Revision Date: 27.11.2022

Date of last issue: 08.10.2020  
Print Date 21.01.2025

Chemical nature : Solution of an alkylammonium salt of an unsaturated acidic carboxylic acid ester

### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-Butenedioic acid (Z)-, ester with 1,2-propanediol, compd. with 2-(dibutylamino)ethanol	- 286-304-6 01-2119979096-24-0000	Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412  Acute toxicity estimate  Acute oral toxicity: 300,03 mg/kg	>= 50 - <= 100
iso-butanol	78-83-1 201-148-0 01-2119484609-23	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	>= 20 - < 25

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-ES 80

Version 7.0  
SDB\_CH

Revision Date: 27.11.2022

Date of last issue: 08.10.2020  
Print Date 21.01.2025

If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.  
Risks : No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.  
Hazardous combustion products : Carbon oxides  
Nitrogen oxides (NO<sub>x</sub>)

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-ES 80

Version 7.0  
SDB\_CH

Revision Date: 27.11.2022

Date of last issue: 08.10.2020  
Print Date 21.01.2025

Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-ES 80

Version 7.0  
SDB\_CH

Revision Date: 27.11.2022

Date of last issue: 08.10.2020  
Print Date 21.01.2025

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
iso-butanol	78-83-1	TWA	50 ppm 150 mg/m <sup>3</sup>	CH SUVA
Further information: National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles, Harm to the unborn child is not to be expected when the OEL-value is respected				
		STEL	50 ppm 150 mg/m <sup>3</sup>	CH SUVA
Further information: National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles, Harm to the unborn child is not to be expected when the OEL-value is respected				

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-Butenedioic acid (Z)-, ester with 1,2-propanediol, compd. with 2-(dibutylamino)ethanol	Workers	Dermal	Long-term systemic effects	1 mg/kg
	Workers	Dermal	Acute systemic effects	6 mg/kg
	Consumers	Dermal	Long-term systemic effects	0,5 mg/kg
	Consumers	Dermal	Acute systemic effects	3 mg/kg
	Consumers	Oral	Long-term systemic effects	0,5 mg/kg
	Consumers	Oral	Acute systemic effects	3 mg/kg
iso-butanol	Workers	Inhalation	Long-term local effects	310 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	25 mg/kg
	Consumers	Inhalation	Long-term local effects	55 mg/m <sup>3</sup>

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
----------------	---------------------------	-------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-ES 80

Version 7.0

SDB\_CH

Revision Date: 27.11.2022

Date of last issue: 08.10.2020

Print Date 21.01.2025

2-Butenedioic acid (Z)-, ester with 1,2-propanediol, compd. with 2-(dibutylamino)ethanol	Fresh water	0,029 mg/l
	Marine water	0,0029 mg/l
	Fresh water sediment	0,136 mg/kg
	Marine sediment	0,014 mg/kg
	Soil	0,009 mg/kg
	Hazard for predators: secondary poisoning	20 mg/kg
iso-butanol	Fresh water	0,4 mg/l
	Marine water	0,04 mg/l
	Fresh water sediment	1,52 mg/kg
	Marine sediment	0,152 mg/kg
	Soil	0,0699 mg/kg
	Sewage treatment plant	10 mg/l
	Intermittent releases	11 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : butyl-rubber  
Break through time : 120,00 min

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

#### Environmental exposure controls

General advice : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid  
Colour : light yellow  
Odour : not significant  
Odour Threshold : No data available

Melting point/freezing point : < 0 °C  
Method: derived

Initial boiling point and boiling range : 106,00 °C  
Method: derived

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-ES 80

Version 7.0  
SDB\_CH

Revision Date: 27.11.2022

Date of last issue: 08.10.2020  
Print Date 21.01.2025

Upper explosion limit / Upper flammability limit	:	10,70 %(V)
Lower explosion limit / Lower flammability limit	:	1,50 %(V)
Flash point	:	40,00 °C Method: 48 (Abel-Pensky)
Auto-ignition temperature	:	> 200 °C Method: DIN 51794
Decomposition temperature	:	No data available
pH	:	7 (20 °C) Concentration: 1 % Method: Universal pH-value indicator
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	12 hPa (20,00 °C) Method: derived
Relative density	:	No data available
Density	:	1,0100 g/cm <sup>3</sup> (20,00 °C) Method: 4 (20°C oscillating U-tube)
Bulk density	:	Not applicable
Relative vapour density	:	No data available

### 9.2 Other information

Flammability (liquids)	:	Sustains combustion
Evaporation rate	:	No data available
Surface tension	:	No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-ES 80

Version 7.0  
SDB\_CH

Revision Date: 27.11.2022

Date of last issue: 08.10.2020  
Print Date 21.01.2025

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.  
Vapours may form explosive mixture with air.

#### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

#### 10.6 Hazardous decomposition products

No data available

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

##### Product:

Acute oral toxicity : Acute toxicity estimate: 625 mg/kg  
Method: Calculation method

##### Components:

##### **2-Butenedioic acid (Z)-, ester with 1,2-propanediol, compd. with 2-(dibutylamino)ethanol:**

Acute oral toxicity : LD50 Oral (Rat, female): > 300 - < 2.000 mg/kg  
Method: OECD Test Guideline 423  
GLP: yes

Acute toxicity estimate: 300,03 mg/kg  
Method: Calculation method

##### **iso-butanol:**

Acute oral toxicity : LD50 (Rat, male): > 2.830 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-ES 80

Version 7.0  
SDB\_CH

Revision Date: 27.11.2022

Date of last issue: 08.10.2020  
Print Date 21.01.2025

### Skin corrosion/irritation

#### Product:

Remarks : May irritate skin.  
May cause skin irritation and/or dermatitis.

#### Components:

##### **2-Butenedioic acid (Z)-, ester with 1,2-propanediol, compd. with 2-(dibutylamino)ethanol:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

##### **iso-butanol:**

Species : Rabbit  
Result : Skin irritation

### Serious eye damage/eye irritation

#### Product:

Remarks : May cause irreversible eye damage.

#### Components:

##### **2-Butenedioic acid (Z)-, ester with 1,2-propanediol, compd. with 2-(dibutylamino)ethanol:**

Species : Rabbit  
Assessment : Risk of serious damage to eyes.  
Method : OECD Test Guideline 405  
Result : Risk of serious damage to eyes.  
GLP : yes

##### **iso-butanol:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Eye irritation  
GLP : yes

### Respiratory or skin sensitisation

#### Product:

Remarks : Causes sensitisation.

#### Components:

##### **2-Butenedioic acid (Z)-, ester with 1,2-propanediol, compd. with 2-(dibutylamino)ethanol:**

Test Type : Mouse Local Lymph Node assay (LLNA)  
Species : Mouse  
Assessment : May cause sensitisation by skin contact.  
Method : OECD Test Guideline 429  
Result : May cause sensitisation by skin contact.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-ES 80

Version 7.0  
SDB\_CH

Revision Date: 27.11.2022

Date of last issue: 08.10.2020  
Print Date 21.01.2025

GLP : yes

### iso-butanol:

Test Type : Maximisation Test  
Exposure routes : Dermal  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.

### Germ cell mutagenicity

#### Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

#### Components:

#### **2-Butenedioic acid (Z)-, ester with 1,2-propanediol, compd. with 2-(dibutylamino)ethanol:**

Genotoxicity in vitro : Test Type: Ames test  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: negative  
GLP: yes

Test Type: In vitro mammalian cell gene mutation test (mouse lymphoma)

Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 476  
Result: positive  
GLP: yes

Test Type: Chromosome aberration test in vitro  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 473  
Result: positive  
GLP: yes

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Rat (male)  
Method: Mutagenicity (micronucleus test)  
Result: negative  
GLP: yes

### Carcinogenicity

#### Product:

Remarks : No data available

## BYK-ES 80

Version 7.0  
SDB\_CH

Revision Date: 27.11.2022

Date of last issue: 08.10.2020  
Print Date 21.01.2025

### Reproductive toxicity

**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

### STOT - single exposure

**Product:**

Remarks : No data available

### STOT - repeated exposure

**Product:**

Remarks : No data available

### Repeated dose toxicity

**Product:**

Remarks : No data available

### Components:

**2-Butenedioic acid (Z)-, ester with 1,2-propanediol, compd. with 2-(dibutylamino)ethanol:**

Species : Rat, male and female  
NOAEL : 300 mg/kg  
Application Route : Oral  
Method : OECD Test Guideline 422  
GLP : yes

### Aspiration toxicity

**Product:**

No data available

### Components:

**iso-butanol:**

No aspiration toxicity classification

## 11.2 Information on other hazards

### Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-ES 80

Version 7.0  
SDB\_CH

Revision Date: 27.11.2022

Date of last issue: 08.10.2020  
Print Date 21.01.2025

### Further information

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

Toxicity to fish : Remarks: No data available

#### Components:

##### **2-Butenedioic acid (Z)-, ester with 1,2-propanediol, compd. with 2-(dibutylamino)ethanol:**

Toxicity to fish : (Danio rerio (zebra fish)): 36 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Method: OECD Test Guideline 203  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 114 mg/l  
Exposure time: 48 h  
Test Type: semi-static test  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 91 mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

Toxicity to microorganisms : EC50 (activated sludge): > 1.000 mg/l  
Test Type: Respiration inhibition  
Method: OECD Test Guideline 209  
GLP: yes

#### **iso-butanol:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1.430 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 1.100 mg/l  
Exposure time: 48 h  
Test Type: static test

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 1.799 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-ES 80

Version 7.0  
SDB\_CH

Revision Date: 27.11.2022

Date of last issue: 08.10.2020  
Print Date 21.01.2025

Exposure time: 72 h  
Method: OECD Test Guideline 201  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 20 mg/l  
End point: Reproduction  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: semi-static test

### 12.2 Persistence and degradability

#### Product:

Biodegradability : Remarks: No data available

#### Components:

##### **2-Butenedioic acid (Z)-, ester with 1,2-propanediol, compd. with 2-(dibutylamino)ethanol:**

Biodegradability : Result: Not readily biodegradable.  
Method: OECD Test Guideline 301D  
GLP: yes

##### **iso-butanol:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301D

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: No data available

#### Components:

##### **iso-butanol:**

Partition coefficient: n-octanol/water : log Pow: 1  
Method: OECD Test Guideline 117  
GLP: yes

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

## BYK-ES 80

Version 7.0  
SDB\_CH

Revision Date: 27.11.2022

Date of last issue: 08.10.2020  
Print Date 21.01.2025

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR : UN 1212  
RID : UN 1212  
IMDG : UN 1212  
IATA : UN 1212

### 14.2 UN proper shipping name

ADR : ISOBUTANOL, SOLUTION  
RID : ISOBUTANOL, SOLUTION  
IMDG : ISOBUTANOL, SOLUTION  
IATA : Isobutyl alcohol, solution

### 14.3 Transport hazard class(es)

ADR : 3  
RID : 3  
IMDG : 3  
IATA : 3

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-ES 80

Version 7.0  
SDB\_CH

Revision Date: 27.11.2022

Date of last issue: 08.10.2020  
Print Date 21.01.2025

### 14.4 Packing group

#### ADR

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : D/E

#### RID

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

#### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-D

#### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing group : III  
Labels : Flammable Liquids

#### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product does not contain substances of very high concern (Regu-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-ES 80

Version 7.0  
SDB\_CH

Revision Date: 27.11.2022

Date of last issue: 08.10.2020  
Print Date 21.01.2025

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable  
Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 20 %

### 15.2 Chemical safety assessment

Not applicable

## SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

### Full text of H-Statements

H226 : Flammable liquid and vapour.  
H302 : Harmful if swallowed.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H412 : Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Eye Dam. : Serious eye damage  
Flam. Liq. : Flammable liquids  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
STOT SE : Specific target organ toxicity - single exposure  
CH SUVA : Switzerland. Limit values at the work place  
CH SUVA / TWA : Time Weighted Average  
CH SUVA / STEL : Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good La-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BYK-ES 80

Version 7.0  
SDB\_CH

Revision Date: 27.11.2022

Date of last issue: 08.10.2020  
Print Date 21.01.2025

laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
Acute Tox. 4	H302
Skin Irrit. 2	H315
Eye Dam. 1	H318
Skin Sens. 1	H317
STOT SE 3	H335
STOT SE 3	H336
Aquatic Chronic 3	H412

#### Classification procedure:

Based on product data or assessment
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CH / EN