

BYK GS-32

Version 1

Revision Date 05/17/2026

Print Date 07/09/2026

SECTION 1. IDENTIFICATION

Product name : BYK GS-32

Manufacturer or supplier's detailsCompany : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.comE-mail address : BRIEF.BYK.NAFTA@altana.comEmergency telephone number : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : oilfield

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Carcinogenicity : Category 2

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H227 Combustible liquid.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.

BYK GS-32

Version 1

Revision Date 05/17/2026

Print Date 07/09/2026

P264 Wash skin thoroughly after handling.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Modified Phenolic Resin Solution

Hazardous components

| Component | CAS-No. | Concentration (%) |
|---|------------|-------------------|
| Solvent naphtha (petroleum), heavy aromatic | 64742-94-5 | >= 10 - < 20 |
| Naphthalene | 91-20-3 | >= 1 - < 5 |

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If symptoms persist, call a physician.
 If skin irritation persists, call a physician.

BYK GS-32

Version 1

Revision Date 05/17/2026

Print Date 07/09/2026

| | |
|------------------------|--|
| In case of eye contact | : If on skin, rinse well with water. If on clothes, remove clothes. Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. |
| If swallowed | : Induce vomiting immediately and call a physician. Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital. |
| Notes to physician | : No information available. |

SECTION 5. FIREFIGHTING MEASURES

| | |
|---|--|
| Suitable extinguishing media | : Water spray Dry powder Foam Carbon dioxide (CO ₂) |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during firefighting | : Handle as an industrial chemical. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : Carbon oxides |
| Further information | : Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment. |
| Environmental precautions | : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods and materials for containment and cleaning up | : Neutralise with acid. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). |

BYK GS-32

Version 1

Revision Date 05/17/2026

Print Date 07/09/2026

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.
 Avoid exposure - obtain special instructions before use.
 Avoid contact with skin and eyes.
 For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Keep away from oxidizing agents.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|-------------|---------|----------------------------------|---|----------|
| Naphthalene | 91-20-3 | TWA | 10 ppm | ACGIH |
| Naphthalene | | TWA | 10 ppm 50 mg/m ³ | OSHA Z-1 |
| Naphthalene | | TWA | 10 ppm 50 mg/m ³ | OSHA P0 |
| Naphthalene | | STEL | 15 ppm 75 mg/m ³ | OSHA P0 |

Hazardous components without workplace control parameters

Engineering measures : Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Material : Impervious gloves

Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Eye wash bottle with pure water
 Tightly fitting safety goggles
 Wear face-shield and protective suit for abnormal processing problems.

BYK GS-32

Version 1

Revision Date 05/17/2026

Print Date 07/09/2026

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid
Colour : amber
Odour : aromatic
Odour Threshold : No data available

pH : 11

Melting point/freezing point : 16 °F (-9 °C)

Initial boiling point and boiling range : > 300 °F (> 149 °C)

Vapour pressure : No data available

Flash point : 165.0 °F (73.9 °C)
Method: closed cup

Upper explosion limit : Upper flammability limit
5.70 %(V)
(77 °F (25 °C))
Medium: Upper flammability limit

Lower explosion limit : Lower flammability limit
0.80 %(V)
Medium: Lower flammability limit

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Relative Density/Specific Gravity : No data available

Density : 1.01 g/cm³ (68 °F (20 °C))

Solubility(ies)
Water solubility : insoluble

Ignition temperature : Greater than
849 °F (454 °C)

BYK GS-32

Version 1

Revision Date 05/17/2026

Print Date 07/09/2026

Viscosity
Viscosity, kinematic : 389.7 mm²/s (104 °F (40 °C))

Surface tension : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable
No decomposition if stored and applied as directed.

Chemical stability : Stable
No decomposition if stored normally.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : Keep away from open flames, hot surfaces and sources of ignition.
Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:**64742-94-5 Solvent naphtha (petroleum), heavy aromatic:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 100 mg/l

Acute dermal toxicity : LD50 (Rabbit): > 2,500 mg/kg

91-20-3 Naphthalene:

Acute oral toxicity : LD50 (Mouse): 316 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 340 ppm
Exposure time: 1.00 h

BYK GS-32

Version 1

Revision Date 05/17/2026

Print Date 07/09/2026

Acute dermal toxicity : LD50 (Rat): > 2,500 mg/kg

Skin corrosion/irritation
Product:

Remarks: May cause skin irritation in susceptible persons.

Components:
91-20-3 Naphthalene:

Species: Rabbit

Method: Draize Test

Result: Severe skin irritation

Serious eye damage/eye irritation
Product:

Remarks: May cause irreversible eye damage.

Components:
91-20-3 Naphthalene:

Species: Rabbit

Result: Mild eye irritation

Method: Draize Test

Respiratory or skin sensitisation
Components:
64742-94-5 Solvent naphtha (petroleum), heavy aromatic:

Test Type: Maximisation Test

Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Not a skin sensitizer.

GLP: No information available.

Carcinogenicity
IARC

Group 2B: Possibly carcinogenic to humans

Naphthalene

91-20-3

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

Reasonably anticipated to be a human carcinogen

Naphthalene

91-20-3

BYK GS-32

Version 1

Revision Date 05/17/2026

Print Date 07/09/2026

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

EPA Hazardous Waste Code(s) : Not applicable.

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.**SECTION 14. TRANSPORT INFORMATION****International Regulations**

BYK GS-32

Version 1

Revision Date 05/17/2026

Print Date 07/09/2026

IATA-DGR

UN/ID No. : UN 3082
 Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
 (Alkyl (C3-C5) benzenes, naphthalene)
 Class : 9
 Packing group : III
 Labels : Miscellaneous Dangerous Goods
 Packing instruction (cargo aircraft) : 964
 Packing instruction (passenger aircraft) : 964

IMDG-Code

UN number : UN 3082
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
 N.O.S.
 (Alkyl (C3-C5) benzenes, naphthalene)
 :)
 Class : 9
 Packing group : III
 Labels : 9
 EmS Code : F-A, S-F
 Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations
49 CFR

UN/ID/NA number : NA 1993
 Proper shipping name : Combustible liquid, n.o.s.
 (Alkyl (C3-C5) benzenes, naphthalene)
 Class : CBL
 Packing group : III
 Labels : Combustible liquid
 Marine pollutant : yes (Alkyl (C3-C5) benzenesnaphthalene)

SECTION 15. REGULATORY INFORMATION
EPCRA - Emergency Planning and Community Right-to-Know Act
US. EPA CERCLA Hazardous Substances (40 CFR 302)

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|-------------|---------|-----------------------|--------------------------------|
| Naphthalene | 91-20-3 | 100 | 6410 |

SARA 304 - Emergency Release Notification

BYK GS-32

Version 1

Revision Date 05/17/2026

Print Date 07/09/2026

Calculated RQ exceeds reasonably attainable upper limit.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

| | | |
|-------------|---------|-------|
| Naphthalene | 91-20-3 | 1.5 % |
|-------------|---------|-------|

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

| | | |
|-------------|---------|-------|
| Naphthalene | 91-20-3 | 1.5 % |
|-------------|---------|-------|

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Massachusetts Right To Know

| | |
|-----------------|----------|
| Naphthalene | 91-20-3 |
| 1,4-Dioxane | 123-91-1 |
| Ethylene oxide | 75-21-8 |
| Propylene oxide | 75-56-9 |

Pennsylvania Right To Know

| | |
|---|------------|
| Solvent naphtha (petroleum), heavy aromatic | 64742-94-5 |
| Naphthalene | 91-20-3 |
| 1,2,4-Trimethylbenzene | 95-63-6 |

Pennsylvania Right To Know

BYK GS-32

Version 1

Revision Date 05/17/2026


Print Date 07/09/2026

| | |
|---|------------|
| Phenolic Resin | - |
| Solvent naphtha (petroleum), heavy aromatic | 64742-94-5 |
| Naphthalene | 91-20-3 |
| 1,2,4-Trimethylbenzene | 95-63-6 |

New Jersey Right To Know

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : 800963-6005

California Prop. 65

 **WARNING:** This product can expose you to chemicals including Naphthalene, 1,4-Dioxane, Ethylene oxide, Propylene oxide, which is/are known to the State of California to cause cancer, and Ethylene oxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

TSCA Inventory Active List : All components of this product are listed active and/or are exempt

DSL : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date : 05/17/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.