

BYK-MAX OR 4206

Granulated anti-odor agent for the use of PE from household waste to reduce unpleasant odors.

Product Data

Composition

Additive concentrate

Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Bulk density: 500-625 kg/m³

Active substance: 30 %

Supplied as: Off-white granulate

Food Contact Legal Status

For the current food contact legal status, please contact our product safety department or visit www.byk.com for further information.

Storage and Transportation

Store in a cool, dry, and well-ventilated location. The additive is not particularly heat-sensitive, but is sensitive to moisture.

Applications

Thermoplastics

Special Features and Benefits

BYK-MAX OR 4206 contains a mixture of odor-absorbing substances that neutralize the odor of substances such as hydrogen sulfide, amines, and ammonia; it is ideally suited for use in polyethylene. As a result of the high content of effective components, the product achieves an exceptional result without any negative impact on other product properties. BYK-MAX OR 4206 is safe and easy to handle.

Recommended Use

PE products with a high recycled content



 especially recommended  recommended

BYK-MAX OR 4206

Data Sheet
Issue 09/2019

Recommended Levels

0.5-2 % additive (as supplied) based upon the total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

Incorporation and Processing Instructions

The additive can be added via volumetric or gravimetric dosing units during processing in standard extrusion, blow, and injection molding machines.

Special Note

The product can be used at processing temperatures of up to 280 °C.



Additive Guide



BYK-Chemie GmbH
P.O. Box 10 02 45
46462 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735

info@byk.com
www.byk.com

ACTAL®, ADD-MAX®, ADD-VANCE®, ADJUST®, ADVITROL®, ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK®-DYNWET®, BYK®-MAX®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKO2BLOCK®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAC®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOÍSITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITÉ®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, MINERAL COLLOID®, MINERPOL®, NANOBYK®, OPTIBENT®, OPTIFLO®, OPTIGEL®, PAPERBYK®, PERMONT®, POLYAD®, PRIEX®, PURE THIX®, RECYCLOBLEND®, RECYCLOBYK®, RECYCLOSSORB®, RECYCLOSTAB®, RHEOBYK®, RHEOCIN®, RHEOTIX®, SCONA®, SILBYK®, TIXOGEL®, VISCOBYK® and Y 25® are registered trademarks of the BYK group.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions – Printed in Germany