

BYK-MAX P 4110

Fluorine- and silicone-free processing aid formulation to reduce the melt viscosity, increase the throughput, and avoid melt fracture and die build-up in various polyolefins.

Product data

Composition

Processing aid composition in a linear low density polyethylene carrier

PFAS-free

Typical properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

MFR (190 °C, 2.16 kg):	60 g/10 min
Color:	dark yellow
Delivery form:	pellet

Storage and transportation

To be stored and transported at a temperature below 45 °C. Store dry.

Applications

Thermoplastics

Special features and benefits

BYK-MAX P 4110 is a highly effective, fluorine- and silicone-free processing aid that lowers the viscosity of the polymer melt during processing by reducing the friction between the melt and the metal surfaces of the processing equipment. As a result, the additive increases production efficiency, reduces die pressure, and prevents melt fracture. It can also reduce die build-up. BYK-MAX P 4110 is particularly suitable for formulations based on polyolefins.

Recommended use

Fibers	<input checked="" type="checkbox"/>
Thick films and sheets	<input checked="" type="checkbox"/>
Thin films	<input checked="" type="checkbox"/>
Extrusion and blow molding parts	<input checked="" type="checkbox"/>
Injection and compression molding parts	<input type="checkbox"/>

especially recommended recommended

Recommended levels

0.5–3 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. The optimum dosage should be determined by application-related test series.

Incorporation and processing instructions

The product can be added via volumetric or gravimetric dosing units during manufacture.



Your local
contact

BYK-Chemie GmbH

Abelstraße 45
46483 Wesel
Germany
Tel +49 281 670-0
info@byk.com
www.byk.com



Download
our app:
byk.com/app

ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK-AQUAGEL®, BYK-DYNWET®, BYK-MAX®, BYK-SILCLEAN®, BYKANOL®, BYKCARE®, BYKETOL®, BYKJET®, BYKONITE®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFK®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, NANOBYPK®, OPTIBENT®, OPTIGEL®, PURABYK®, RECYCLOBYK®, RHEOBYK®, SCONA®, SILBYK®, TIXOGEL® and VISCOBYK® are registered trademarks of the BYK group.

The information contained herein is based on our current knowledge and experience. No warranties, guarantees and/or assurances of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. Any information about suitability, use or application of the products is non-binding and does not constitute a commitment regarding the products' properties, use or application. Contractual terms and conditions, in particular agreed product specifications, always take precedence. We recommend that you test our products in preliminary trials to determine their suitability for your intended purpose prior to use. We reserve the right to make any changes and to update the information herein without notice.