BYK-S 750 N

Version 3 | Revision Date 05/17/2026 | Print Date 08/06/2026

SECTION 1. IDENTIFICATION

Product name : BYK-S 750 N

Manufacturer or supplier's details

Company : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.com

E-mail address : BRIEF.BYK.NAFTA@altana.com

Emergency telephone number : 203-265-2086; CHEMTREC 1-800-424-9300 / +1 703-527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Wax Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin irritation : Category 2

Serious eye damage : Category 1

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Wax dispersion
Hazardous components

Component	CAS-No.	Concentration (%)
Petroleum distillates	64742-55-8	>= 80 - < 100
Waxes	-	>= 10 - < 30
Alcohols, C9-11-iso-, C10-rich, ethoxylated	78330-20-8	>= 10 - < 30

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : Remove to fresh air. Administer artificial respiration if necessary. Get medical aid as soon as possible.
Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.

In case of skin contact : Remove contaminated clothing. Wash thoroughly with soap and water. If irritation develops, get medical aid.

If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Immediately flush with plenty of water for at least 30 minutes.
Get medical aid.
Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting. Dilute with 1-2 glasses of water. Get medical aid.
Never give anything by mouth to an unconscious person.
Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed : No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Foam
Carbon dioxide (CO2)
Dry chemical
Foam
Carbon dioxide (CO2)
Dry chemical
Water mist

Unsuitable extinguishing media : No information available.

High volume water jet

Specific hazards during firefighting : Handle as an industrial chemical.
Will not explode on mechanical impact.
Cool closed containers exposed to fire with water spray.

Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides

Further information : Keep away from heat and sources of ignition.
Keep away from oxidizing agents.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Wear protective equipment: goggles, chemically resistant clothing and gloves, and appropriate respirator if in a confined area.

: Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.

Environmental precautions : Prevent spilled material from entering the ground, water and/or air by using appropriate containment methods.

Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Stop leak. Dike and contain spill.
Absorb with suitable material and remove with sparkless shovel and/or scoop.

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid contact with skin and eyes.
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Keep container closed when not in use.
Handle as an industrial chemical.
Avoid formation of respirable particles.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep in a dry, cool and well-ventilated place.

Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Keep away from oxidizing agents.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hazardous components without workplace control parameters				
Petroleum distillates	64742-55-8	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
Waxes	-	TWA (Fumes)	2 mg/m3	ACGIH
Waxes		TWA (Fumes)	2 mg/m3	NIOSH REL
Waxes		TWA (Fumes)	2 mg/m3	OSHA P0

Engineering measures : Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : Unless air monitoring demonstrates vapor/mist/dust levels are below the PEL/TLV wear a properly fitted respirator (NIOSH approved) or dust mask during exposure.
In the case of dust or aerosol formation use respirator with an approved filter.

Hand protection
Material : Nitrile rubber

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Goggles
Safety glasses with side-shields
Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

Clean long legged, long sleeved work clothes.
If splashing is possible, wear chemically resistant protective clothing.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	:	Wax like
Colour	:	off-white
Odour	:	odourless
Odour Threshold	:	No data available
pH	:	6, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-value indicator
Melting point/freezing point	:	No data available
Initial boiling point	:	> 374 °F (> 190 °C) Method: derived
Vapour pressure	:	< 1 hPa (68 °F (20 °C)) Method: derived
Flash point	:	> 302 °F (> 150 °C) Method: 49 (Pensky-Martens)
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Combustible Solids
Relative vapour density	:	No data available
Relative Density/Specific Gravity	:	No data available
Particle size	:	No data available
Density	:	0.858 g/cm3 (68 °F (20 °C)) Method: 1 (20°C coating pycnometer)
Bulk density	:	Not applicable
Solubility(ies)		

Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Ignition temperature	:	No data available
Thermal decomposition	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	79.719 mm2/s (104 °F (40 °C)) Method: calculated

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard. No decomposition if stored and applied as directed.
Chemical stability	:	Stable; polymerization will not occur No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No data available No decomposition if stored and applied as directed.
Conditions to avoid	:	No data available No data available
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	No data available

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure
Inhalation
Ingestion
Eyes
Skin Absorption
Skin contact

Acute toxicity

Product:

Acute oral toxicity	:	Acute toxicity estimate : 5,000 mg/kg Method: Calculation method

Components:

64742-55-8 Petroleum distillates:

Acute oral toxicity : LD50 (Rat): > 15,000 mg/kg

Acute dermal toxicity : LD50 : > 5,000 mg/kg

Skin corrosion/irritation

Product:

Remarks: No data available

Remarks: Extremely corrosive and destructive to tissue.

Components:

64742-55-8 Petroleum distillates:
Species: Rabbit
Result: slight irritation

- Waxes:
Species: Rabbit
Result: slight irritation

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Remarks: Product dust may be irritating to eyes, skin and respiratory system.

Components:

64742-55-8 Petroleum distillates:
Species: Rabbit
Result: Mild eye irritation

- Waxes:
Species: Rabbit
Result: Mild eye irritation

Respiratory or skin sensitisation

Product:

Remarks: No data available

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Product:

Remarks: No data available

Components:

64742-55-8 Petroleum distillates:

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure

Product:

Remarks: No data available

STOT - repeated exposure

Product:

Remarks: No data available

Repeated dose toxicity

Product:

Remarks: Chronic skin contact with petroleum distillates has caused dermatitis.

Aspiration toxicity

Product:

No data available

Experience with human exposure

Product:

Inhalation:

Symptoms: High concentrations are irritating to the respiratory tract. Has caused headaches, dizziness, nausea, vomiting and CNS depression (drowsiness, loss of coordination and fatigue).

Skin contact:

Symptoms: Contact may cause irritation.

Eye contact:

Symptoms: Contact will probably cause severe irritation and corrosion.

Ingestion:

Symptoms: Ingestion may irritate the digestive tract; cause CNS effects (depression, muscle spasms).

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation		40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks		This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	:	No data available
		No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

EPA Hazardous Waste Code(s)	:	Not applicable.
Waste from residues	:	Dispose of in accordance with applicable local/municipal, state/provincial and federal regulations. Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good
Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

US. EPA CERCLA Hazardous Substances (40 CFR 302)

This material does not contain any components with a CERCLA RQ.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards	:	Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.
SARA 302	:	No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

Non-volatile (Wt)	:	> 95 % Method: 22 (10min/150°C) DIN EN ISO 3251

Non-volatile information is not a specification.

Massachusetts Right To Know

Petroleum distillates	64742-55-8
Waxes	-
1,4-Dioxane	123-91-1
Ethylene oxide	75-21-8

Pennsylvania Right To Know

Petroleum distillates	64742-55-8
Waxes	-
Alcohols, C9-11-iso-, C10-rich, ethoxylated	78330-20-8

New Jersey Right To Know

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : 800963-5838

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including 1,4-Dioxane, Ethylene oxide, which is/are known to the State of California to cause cancer, and Ethylene oxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA	:	All substances listed as active on the TSCA inventory
Section 5a	:	No substances are subject to a Significant New Use Rule.
Section 4 / 12(b)	:	No substances are subject to TSCA 12(b) export notification requirements.
DSL	:	We certify that all of the components of this product are listed on the DSL.

SECTION 16. OTHER INFORMATION

Revision Date : 05/17/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.