

BYK-W 940

Version 7

Revision Date 02/02/2026

Print Date 05/07/2026

SECTION 1. IDENTIFICATION

Product name : BYK-W 940

Manufacturer or supplier's detailsCompany : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.comE-mail address : BRIEF.BYK.NAFTA@altana.comEmergency telephone number : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
703-527-3887**Recommended use of the chemical and restrictions on use**

Recommended use : Wetting & Dispersing Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3

Eye irritation : Category 2B

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ toxicity - repeated exposure : Category 2 (hearing organs, Kidney, Liver)

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

BYK-W 940

Version 7

Revision Date 02/02/2026

Print Date 05/07/2026

H317 May cause an allergic skin reaction.
H320 Causes eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs (hearing organs, Kidney, Liver) through prolonged or repeated exposure.

Precautionary statements

: **Prevention:**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P285 In case of inadequate ventilation wear respiratory protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

BYK-W 940

Version 7

Revision Date 02/02/2026

Print Date 05/07/2026

tightly closed.
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Solution of an unsaturated polycarboxylic acid polymer with a polysiloxane copolymer

Hazardous components

Component	CAS-No.	Concentration (%)
Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids	85711-46-2	>= 30 - < 60
Xylene	1330-20-7	>= 30 - < 60
Ethyl benzene	100-41-4	>= 10 - < 20
2,6-Dimethylheptan-4-one	108-83-8	>= 1 - < 5
Maleic anhydride	108-31-6	>= 0.1 - < 1

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

If inhaled : Call a physician or poison control centre immediately.
 If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If on skin, rinse well with water.
 If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.
 Remove contact lenses.
 Protect unharmed eye.
 Keep eye wide open while rinsing.
 If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
 Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.

BYK-W 940

Version 7

Revision Date 02/02/2026

Print Date 05/07/2026

Most important symptoms and effects, both acute and delayed : If symptoms persist, call a physician.
Take victim immediately to hospital.
: No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Neutralize with chalk, alkali solution or ammonia.
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.

BYK-W 940

Version 7

Revision Date 02/02/2026

Print Date 05/07/2026

Do not breathe vapours/dust.
 Avoid contact with skin and eyes.
 For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Take precautionary measures against static discharges.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Open drum carefully as content may be under pressure.
 Dispose of rinse water in accordance with local and national regulations.
 Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

- Conditions for safe storage : No smoking.
 Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Keep away from oxidizing agents.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Xylene	1330-20-7	TWA	100 ppm 435 mg/m ³	OSHA Z-1
Xylene		STEL	150 ppm 655 mg/m ³	OSHA P0
Xylene		TWA	100 ppm 435 mg/m ³	OSHA P0
Xylene		TWA	20 ppm	ACGIH
Ethyl benzene	100-41-4	TWA	20 ppm	ACGIH
Ethyl benzene		TWA	100 ppm 435 mg/m ³	OSHA Z-1
Ethyl benzene		TWA	100 ppm 435 mg/m ³	OSHA P0
Ethyl benzene		STEL	125 ppm 545 mg/m ³	OSHA P0
Ethyl benzene		ST	125 ppm 545 mg/m ³	NIOSH REL
2,6-Dimethylheptan-4-one	108-83-8	TWA	25 ppm	ACGIH
2,6-Dimethylheptan-4-one		TWA	50 ppm	OSHA Z-1

BYK-W 940

Version 7

Revision Date 02/02/2026

Print Date 05/07/2026

			290 mg/m3	
Maleic anhydride	108-31-6	TWA	0.25 ppm 1 mg/m3	OSHA Z-1
Maleic anhydride		TWA	0.25 ppm 1 mg/m3	NIOSH REL
Maleic anhydride		TWA (Inhalable fraction and vapor)	0.01 mg/m3	ACGIH

Hazardous components without workplace control parameters

Engineering measures : Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

 Hand protection
 Material : Silver Shield gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

 Eye protection : Eye wash bottle with pure water
 Tightly fitting safety goggles

 Skin and body protection : Impervious clothing
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

 Hygiene measures : When using do not eat or drink.
 When using do not smoke.
 Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

 Physical state : liquid
 Colour : light brown
 Odour : aromatic
 Odour Threshold : No data available

pH : 4, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-value indicator

 Melting point/ range : < 32 °F (< 0 °C)
 Method: derived

 Initial boiling point : 278.60 °F (137.00 °C)
 Method: derived

 Vapour pressure : 9 hPa (68.00 °F (20.00 °C))
 Method: derived

BYK-W 940

Version 7

Revision Date 02/02/2026

Print Date 05/07/2026

Flash point	:	82.40 °F (28.00 °C) Method: 48 (Abel-Pensky) DIN 51755
Upper explosion limit	:	7.60 %(V)
Lower explosion limit	:	0.80 %(V)
Evaporation rate	:	No data available
Relative vapour density	:	No data available
Relative Density/Specific Gravity	:	No data available
Density	:	0.9450 g/cm ³ (68.00 °F (20.00 °C)) Method: 4 (20°C oscillating U-tube)
Solubility(ies)	:	
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Ignition temperature	:	> 392 °F (> 200 °C) Method: DIN 51794
Thermal decomposition	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	40 mm ² /s (104.00 °F (40.00 °C))

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong oxidizing agents Strong acids
Hazardous decomposition products	:	None expected

BYK-W 940

Version 7

Revision Date 02/02/2026

Print Date 05/07/2026

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Skin Absorption
Inhalation
Eyes
Ingestion

Acute toxicity**Product:**

Acute oral toxicity : LD50 (Rat, male and female): > 3,500.000000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : Acute toxicity estimate : 24.52 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 4,923 mg/kg
Method: Calculation method

Components:**85711-46-2 Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids:**

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 423
GLP: yes

1330-20-7 Xylene:

Acute oral toxicity : LD50 (Rat): 4,300 mg/kg
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)
GLP: no

Acute inhalation toxicity : LC50 (Rat): 5000 ppm
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg

LD50 (Rabbit): > 4,200 mg/kg
GLP: No information available.

100-41-4 Ethyl benzene:

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 5,510 mg/kg

BYK-W 940

Version 7

Revision Date 02/02/2026

Print Date 05/07/2026

108-83-8 2,6-Dimethylheptan-4-one:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 14 mg/l
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: no

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

108-31-6 Maleic anhydride:

Acute oral toxicity : LD50 (Rat, male and female): 1,090 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): 398 mg/kg

LD50 (Rabbit, female): 2,620 mg/kg
GLP: No information available.

Skin corrosion/irritation**Product:**

Species: Rabbit
Assessment: No skin irritation
Method: OECD Test Guideline 404
Result: No skin irritation

Remarks: May cause skin irritation and/or dermatitis.

Components:**85711-46-2 Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids:**

Species: EPISKIN human epidermis skin constructs
Assessment: Irritating to skin.
Method: OECD Test Guideline 439
Result: Irritating to skin.
GLP: yes

1330-20-7 Xylene:

Species: Rabbit
Result: Moderate skin irritation

100-41-4 Ethyl benzene:

Species: Rabbit
Result: Moderate skin irritation

BYK-W 940

Version 7

Revision Date 02/02/2026

Print Date 05/07/2026

108-83-8 2,6-Dimethylheptan-4-one:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation
GLP: yes

108-31-6 Maleic anhydride:

Species: Rabbit
Method: No information available.
Result: Corrosive to skin
GLP: no

Serious eye damage/eye irritation**Product:**

Species: Rabbit
Result: Mild eye irritation
Method: OECD Test Guideline 405

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**85711-46-2 Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids:**

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405
GLP: yes

1330-20-7 Xylene:

Species: Rabbit
Result: Eye irritation

100-41-4 Ethyl benzene:

Species: Rabbit
Result: Moderate eye irritation

108-83-8 2,6-Dimethylheptan-4-one:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405
GLP: no

108-31-6 Maleic anhydride:

Species: Rabbit
Result: Corrosive to eyes
GLP: yes

BYK-W 940

Version 7

Revision Date 02/02/2026

Print Date 05/07/2026

Respiratory or skin sensitisation**Product:**

Remarks: Causes sensitisation.

Components:**85711-46-2 Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids:**

Test Type: Mouse Local Lymph Node assay (LLNA)

Species: Mouse

Assessment: May cause sensitisation by skin contact.

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

GLP: yes

108-83-8 2,6-Dimethylheptan-4-one:

Test Type: Maximisation Test

Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Not a skin sensitizer.

GLP: yes

108-31-6 Maleic anhydride:

Test Type: Buehler Test

Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Causes sensitisation.

GLP: yes

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:**85711-46-2 Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids:**

Genotoxicity in vitro : Test Type: Ames test
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes

: Test Type: In vitro mammalian cell gene mutation test (mouse lymphoma)

BYK-W 940

Version 7

Revision Date 02/02/2026

Print Date 05/07/2026

Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 476
 Result: negative
 GLP: yes

: Test Type: Chromosome aberration test in vitro
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 473
 Result: negative
 GLP: yes

Carcinogenicity
Product:

Remarks: No data available

IARC

Group 2B: Possibly carcinogenic to humans

Ethyl benzene

100-41-4

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity
Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Components:

85711-46-2 Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids:

Effects on fertility :
 Species: Rat
 Sex: male and female
 Application Route: Oral
 NOAEL: 1,000 mg/kg,
 F1: > 1,000 mg/kg,
 Method: OECD Test Guideline 422
 GLP: yes

Effects on foetal development : Species: Rat
 Application Route: Oral
 > 1,000 mg/kg

BYK-W 940

Version 7

Revision Date 02/02/2026

Print Date 05/07/2026

1,000 mg/kg
Method: OECD Test Guideline 422
GLP: yes

STOT - single exposure**Product:**

Remarks: No data available

STOT - repeated exposure**Product:**

Remarks: No data available

Repeated dose toxicity**Product:**

Remarks: Absorption of ingredients (solvents) by inhalation and/or repeated skin contact has caused injury to liver, kidney, brain, respiratory system, blood, and/or bone marrow in laboratory animals

Animal studies have shown Xylene to cause fetotoxic effects at dosage levels at or near maternal toxicity levels.

Excessive inhalation of Xylene has caused hearing loss in laboratory animals. Hexane used in conjunction w/Xylene greatly increased this effect. Chronic skin contact w/Xylene has caused dermatitis. Ingestion of Ethanol can increase effects of overexposure to Xylene.

Prolonged exposure to respirable aerosols (mists) of polyalkylene glycol has caused lung damage in rats (90 days; 0.3 mg/m³).

Ethylbenzene is an IARC Group 2B carcinogen based on animal studies (increased tumors in rats and mice).

Components:**85711-46-2 Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids:**

Species: Rat, male and female

NOAEL: 1,000 mg/kg

Application Route: Oral

Method: OECD Test Guideline 422

GLP: yes

Target Organs: Stomach

Aspiration toxicity**Product:**

No data available

Experience with human exposure**Product:**

Inhalation:

Symptoms:

High concentrations of vapors may be

BYK-W 940

Version 7

Revision Date 02/02/2026

Print Date 05/07/2026

irritating to the respiratory tract. May cause headaches, dizziness, nausea and vomiting. May cause CNS depression (drowsiness, loss of coordination and fatigue)., May cause respiratory tract sensitization.

Skin contact:

Symptoms:

Contact may cause irritation and sensitization.

Eye contact:

Symptoms:

Contact will probably cause irritation.

Ingestion:

Symptoms:

May irritate the digestive tract and cause same symptoms as inhalation; high dosages may result in unconsciousness.

Further information
Product:

Remarks: Solvents may degrease the skin.

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential
Product:

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

BYK-W 940

Version 7

Revision Date 02/02/2026

Print Date 05/07/2026

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS
Disposal methods

EPA Hazardous Waste Code(s) : D001: Ignitable
D018: Benzene

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION
International Regulations
IATA-DGR

UN/ID No. : UN 1993
Proper shipping name : Flammable liquid, n.o.s.
(Xylene, Diisobutyl ketone)

Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(XYLENE, Diisobutyl ketone)

:)
Class : 3
Packing group : III

BYK-W 940

Version 7

Revision Date 02/02/2026

Print Date 05/07/2026

Labels : 3
 EmS Code : F-E, S-E
 Marine pollutant : no
 Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations
49 CFR

UN/ID/NA number : UN 1993
 Proper shipping name : Flammable liquids, n.o.s.
 (Xylene, Diisobutyl ketone)
 Class : 3
 Packing group : III
 Labels : FLAMMABLE LIQUID
 ERG Code : 128
 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION
EPCRA - Emergency Planning and Community Right-to-Know Act
US. EPA CERCLA Hazardous Substances (40 CFR 302)

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	314

SARA 304 - Emergency Release Notification

Calculated RQ exceeds reasonably attainable upper limit.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

BYK-W 940

Version 7

Revision Date 02/02/2026

Print Date 05/07/2026

SARA 313

: This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Xylene	1330-20-7	31.8 %
Ethyl benzene	100-41-4	13.0 %

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

Xylene	1330-20-7	31.8 %
Ethyl benzene	100-41-4	13.0 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

Xylene	1330-20-7	31.8 %
Ethyl benzene	100-41-4	13.0 %

Non-volatile (Wt)

: 48 - 52 %

Method: 22 (10min/150°C)

DIN EN ISO 3251

Non-volatile information is not a specification.

Massachusetts Right To Know

Xylene	1330-20-7
Ethyl benzene	100-41-4
2,6-Dimethylheptan-4-one	108-83-8
Benzene	71-43-2
Propylene oxide	75-56-9

Pennsylvania Right To Know

Fatty acids, sunflower-oil, conjugated, reaction products with maleic anhydride and tall-oil fatty acids	85711-46-2
Xylene	1330-20-7
Ethyl benzene	100-41-4
Oxirane, Me, polymer with oxirane monobutyl ether (polyalkylene glycol)	9038-95-3
2,6-Dimethylheptan-4-one	108-83-8
Maleic anhydride	108-31-6
Toluene	108-88-3
Cumene	98-82-8

BYK-W 940

Version 7

Revision Date 02/02/2026

Print Date 05/07/2026

New Jersey Right To Know

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : Not applicable

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including Ethyl benzene, Cumene, Benzene, Propylene oxide, Acetaldehyde, Formaldehyde, Ethylene oxide, 1,4-Dioxane, which is/are known to the State of California to cause cancer, and Toluene, Benzene, Ethylene oxide, Methanol, Chloromethane, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

Section 5a : No substances are subject to a Significant New Use Rule.

Section 4 / 12(b) : No substances are subject to TSCA 12(b) export notification requirements.

DSL : We certify that all of the components of this product are listed on the DSL.

SECTION 16. OTHER INFORMATION

Revision Date : 02/02/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.