

BYKETOL-AQ

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

SECTION 1. IDENTIFICATION

Product name : BYKETOL-AQ

Manufacturer or supplier's details

Company : BYK USA LLC
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086
Visit our web site : www.byk.com
E-mail address : BRIEF.BYK.NAFTA@altana.com

Emergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1
number 703-527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Leveling Additive
Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.

Precautionary statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting
equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON

BYKETOL-AQ

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Chemical nature

: Combination of surface active substances and polymers

Hazardous components

Component	CAS-No.	Concentration (%)
Paraffins, petroleum, normal C5-20	64771-72-8	>= 80 - < 100
1-Methoxy-2-propanol	107-98-2	>= 5 - < 10

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

SECTION 4. FIRST AID MEASURES

General advice

: Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.

If inhaled

: If unconscious, place in recovery position and seek medical advice.

In case of skin contact

: If symptoms persist, call a physician.
If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact

: Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed

: Keep respiratory tract clear.

BYKETOL-AQ

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

Most important symptoms
and effects, both acute and
delayed

Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
: No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Will not explode on mechanical impact.
Cool closed containers exposed to fire with water spray.

Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth,

BYKETOL-AQ

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Keep away from oxidizing agents.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1-Methoxy-2-propanol	107-98-2	TWA	50 ppm	ACGIH
1-Methoxy-2-propanol		STEL	100 ppm	ACGIH
1-Methoxy-2-propanol		TWA	100 ppm 360 mg/m ³	NIOSH REL
1-Methoxy-2-propanol		ST	150 ppm 540 mg/m ³	NIOSH REL

Hazardous components without workplace control parameters

Engineering measures : Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : Unless air monitoring demonstrates vapor/mist/dust levels are below the PEL/TLV wear a properly fitted respirator (NIOSH approved) or dust mask during exposure.

Hand protection
Material : Impervious gloves

BYKETOL-AQ

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Colour	: colourless
Odour	: not significant
Odour Threshold	: No data available
pH	: 7, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-value indicator
Melting point/freezing point	: < 32 °F (< 0 °C) Method: derived
Initial boiling point and boiling range	: 248 °F (120 °C) Method: derived
Vapour pressure	: ca. 13 hPa (68 °F (20 °C)) Method: derived
Flash point	: 104 °F (40 °C) Method: 48 (Abel-Pensky) DIN 51755
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Evaporation rate	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 0.775 g/cm ³ (68 °F (20 °C)) Method: 4 (20°C oscillating U-tube)

BYKETOL-AQ

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

Bulk density	: Not applicable
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: > 392 °F (> 200 °C) Method: DIN 51794
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: 2 mPa.s (68 °F (20 °C))
Viscosity, kinematic	: No data available
Surface tension	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
	Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: None expected

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Eyes
Skin Absorption
Skin contact
Ingestion

Acute toxicity**Product:**

BYKETOL-AQ

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 2,841 mg/kg
Method: Calculation method

Components:**64771-72-8 Paraffins, petroleum, normal C5-20:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.1 mg/l
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg

107-98-2 1-Methoxy-2-propanol:

Acute oral toxicity : LD50 (Rat, male and female): 4,016 mg/kg
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)
GLP: yes

Acute inhalation toxicity : LC50 (Rat): 1500 ppm

Acute dermal toxicity : LD50 (Rabbit): 13,000 mg/kg

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation and/or dermatitis.

Components:**64771-72-8 Paraffins, petroleum, normal C5-20:**

Species: Rabbit

Result: slight irritation

107-98-2 1-Methoxy-2-propanol:

Species: Rabbit

Method: Directive 67/548/EEC, Annex V, B.4.

Result: No skin irritation

GLP: yes

Serious eye damage/eye irritation**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**64771-72-8 Paraffins, petroleum, normal C5-20:**

Species: Rabbit

BYKETOL-AQ

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

Result: Mild eye irritation

107-98-2 1-Methoxy-2-propanol:

Species: Rabbit

Result: No eye irritation

Method: Directive 67/548/EEC, Annex V, B.5.

GLP: yes

Respiratory or skin sensitisation**Product:**

Remarks: No data available

Components:**107-98-2 1-Methoxy-2-propanol:**

Test Type: Maximisation Test

Exposure routes: Dermal

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.

Result: Does not cause skin sensitisation.

GLP: yes

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity**Product:**

Remarks: No data available

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Product:**

BYKETOL-AQ

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure**Product:**

Remarks: No data available

STOT - repeated exposure**Product:**

Remarks: No data available

Repeated dose toxicity**Product:**

Remarks: Solvent absorption by inhalation and/or repeated skin contact may cause injury to liver, kidney and respiratory system.

Prolonged skin contact with ingredients may cause dermatitis.

Aspiration toxicity**Product:**

No data available

Experience with human exposure**Product:**

Inhalation:

Symptoms:

High concentrations of vapors may be irritating to the respiratory tract. May cause headaches, dizziness, nausea and vomiting. May cause CNS depression (drowsiness, loss of coordination and fatigue).

Skin contact:

Symptoms:

Contact will probably cause irritation.

Eye contact:

Symptoms:

Contact will probably cause irritation.

Ingestion:

Symptoms:

Ingestion may irritate the digestive tract; high dosages may cause CNS depression.

BYKETOL-AQ

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

Further information**Product:**

Remarks: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Toxicity to fish :
Remarks: No data available

Persistence and degradability**Product:**

Biodegradability : Remarks: No data available

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

EPA Hazardous Waste Code(s) : D001: D001: Ignitability

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.

BYKETOL-AQ

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

Contaminated packaging : Send to a licensed waste management company.
: Empty remaining contents.
: Dispose of as unused product.
: Do not re-use empty containers.
: Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

UN/ID No. : UN 3092
Proper shipping name : 1-Methoxy-2-propanol, solution
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 3092
Proper shipping name : 1-METHOXY-2-PROPANOL, SOLUTION
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

UN/ID/NA number : UN 3092
Proper shipping name : 1-Methoxy-2-propanol, solution
Class : 3
Packing group : III
Labels : FLAMMABLE LIQUID
ERG Code : 129
Marine pollutant : no
Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

BYKETOL-AQ

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

US. EPA CERCLA Hazardous Substances (40 CFR 302)

This material does not contain any components with a CERCLA RQ.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

Non-volatile (Wt) : 4.0 %
Method: 22 (10min/150°C)
DIN EN ISO 3251
Non-volatile information is not a specification.

Massachusetts Right To Know

1-Methoxy-2-propanol	107-98-2
----------------------	----------

Pennsylvania Right To Know

Paraffins, petroleum, normal C5-20	64771-72-8
1-Methoxy-2-propanol	107-98-2
Polymer	-

New Jersey Right To Know

BYKETOL-AQ

Version 7

Revision Date 05/17/2026

Print Date 08/06/2026

**New Jersey Trade Secret
Registry Number for the
product (NJ TSRN)** : 800963-5272

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA	: All substances listed as active on the TSCA inventory
Section 4 / 12(b)	: Not applicable
TSCA Inventory Active List	: All components of this product are listed active and/or are exempt
Section 5a	: No substances are subject to a Significant New Use Rule.
Section 4 / 12(b)	: No substances are subject to TSCA 12(b) export notification requirements.
DSL	: We certify that all of the components of this product are listed on the DSL.

SECTION 16. OTHER INFORMATION

Revision Date : 05/17/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.