

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0

SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024

Print Date 05.01.2026

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : BYKETOL-SPECIAL SG

Product code : 000000000000114213

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Leveling Additive

#### 1.3 Details of the supplier of the safety data sheet

Company : BYK USA LLC  
South Cherry Street 524  
06492 Wallingford

Telephone :

Information : BYK USA Regulatory Affairs  
Telephone : +1 203-265-2086  
Telefax :  
E-mail address : BRIEF.BYK.NAFTA@altana.com

#### 1.4 Emergency telephone number

+44 1235 239670

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

|                                                                                      |                                                        |
|--------------------------------------------------------------------------------------|--------------------------------------------------------|
| Flammable liquids, Category 3                                                        | H226: Flammable liquid and vapour.                     |
| Carcinogenicity, Category 1B                                                         | H350: May cause cancer.                                |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness.               |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system     | H335: May cause respiratory irritation.                |
| Aspiration hazard, Category 1                                                        | H304: May be fatal if swallowed and enters airways.    |
| Long-term (chronic) aquatic hazard, Category 2                                       | H411: Toxic to aquatic life with long lasting effects. |

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0  
SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024  
Print Date 05.01.2026

|                                |   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hazard pictograms              | : |                                                                                                                                                                                                                                                                                                                            |
| Signal word                    | : | Danger                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Hazard statements              | : | H226 Flammable liquid and vapour.<br>H304 May be fatal if swallowed and enters airways.<br>H335 May cause respiratory irritation.<br>H336 May cause drowsiness or dizziness.<br>H350 May cause cancer.<br>H411 Toxic to aquatic life with long lasting effects.                                                                                                                                                                                                                                                                                                                                                                                                   |
| Supplemental Hazard Statements | : | EUH066 Repeated exposure may cause skin dryness or cracking.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Precautionary statements       | : | <b>Prevention:</b><br>P201 Obtain special instructions before use.<br>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P273 Avoid release to the environment.<br>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.<br><br><b>Response:</b><br>P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.<br>P308 + P313 IF exposed or concerned: Get medical advice/ attention.<br>P331 Do NOT induce vomiting.<br>P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.<br>P391 Collect spillage. |

### Hazardous components which must be listed on the label:

- 64742-95-6 Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified
- 98-82-8 cumene

### Additional Labelling

Restricted to professional users.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0

SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024

Print Date 05.01.2026

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Chemical nature : Combination of high boiling aromatics, ketones, esters and a polydimethylsiloxane

#### Components

| Chemical name                                                                     | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number | Classification                                                                                                                                                            | Concentration<br>(% w/w) |
|-----------------------------------------------------------------------------------|-------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified | 64742-95-6<br>01-2119455851-35                        | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)<br>STOT SE 3; H335<br>(Respiratory system)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 2;<br>H411<br>EUH066 | >= 50 - <= 100           |
| 2,6-dimethylheptan-4-one                                                          | 108-83-8<br>203-620-1<br>01-2119474441-41             | Flam. Liq. 3; H226<br>STOT SE 3; H335<br>(Respiratory system)<br><br>specific concentration<br>limit<br>STOT SE 3; H335<br>>= 10 %<br>STOT SE 3; H335<br>>= 10 %          | >= 10 - < 12,5           |
| ethyl lactate                                                                     | 97-64-3<br>202-598-0<br>01-2119516234-49              | Flam. Liq. 3; H226<br>Eye Dam. 1; H318<br>STOT SE 3; H335<br>(Respiratory system)                                                                                         | >= 1 - < 3               |
| butyl glycollate                                                                  | 7397-62-8<br>230-991-7<br>01-2119514685-36            | Eye Dam. 1; H318<br>Repr. 2; H361                                                                                                                                         | >= 1 - < 3               |
| cumene                                                                            | 98-82-8<br>202-704-5                                  | Flam. Liq. 3; H226<br>Carc. 1B; H350<br>STOT SE 3; H335                                                                                                                   | >= 1 - < 2,5             |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0  
SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024  
Print Date 05.01.2026

|  |  |                                                                         |  |
|--|--|-------------------------------------------------------------------------|--|
|  |  | (Respiratory system)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 2;<br>H411 |  |
|--|--|-------------------------------------------------------------------------|--|

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : May be fatal if swallowed and enters airways.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
May cause cancer.  
Repeated exposure may cause skin dryness or cracking.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0  
SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024  
Print Date 05.01.2026

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0  
SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024  
Print Date 05.01.2026

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components | CAS-No.  | Value type (Form of exposure) | Control parameters | Basis   |
|------------|----------|-------------------------------|--------------------|---------|
| 2,6-       | 108-83-8 | TWA                           | 25 ppm             | GB EH40 |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0

SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024

Print Date 05.01.2026

|                      |                                                                                                                                                                              |      |                     |                  |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|---------------------|------------------|
| dimethylheptan-4-one |                                                                                                                                                                              |      | 148 mg/m3           |                  |
| cumene               | 98-82-8                                                                                                                                                                      | TWA  | 20 ppm<br>100 mg/m3 | 2000/39/EC       |
|                      | Further information: Identifies the possibility of significant uptake through the skin, Indicative                                                                           |      |                     |                  |
|                      |                                                                                                                                                                              | STEL | 50 ppm<br>250 mg/m3 | 2000/39/EC       |
|                      | Further information: Identifies the possibility of significant uptake through the skin, Indicative                                                                           |      |                     |                  |
|                      |                                                                                                                                                                              | TWA  | 25 ppm<br>125 mg/m3 | GB EH40          |
|                      | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |      |                     |                  |
|                      |                                                                                                                                                                              | STEL | 50 ppm<br>250 mg/m3 | GB EH40          |
|                      | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |      |                     |                  |
|                      |                                                                                                                                                                              | TWA  | 10 ppm<br>50 mg/m3  | 2019/1831/E<br>U |
|                      | Further information: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin., Indicative         |      |                     |                  |
|                      |                                                                                                                                                                              | STEL | 50 ppm<br>250 mg/m3 | 2019/1831/E<br>U |
|                      | Further information: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin., Indicative         |      |                     |                  |

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

| Substance name                                                                    | End Use   | Exposure routes | Potential health effects                                             | Value     |
|-----------------------------------------------------------------------------------|-----------|-----------------|----------------------------------------------------------------------|-----------|
| Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified | Workers   | Skin contact    | Long-term exposure, Systemic effects                                 | 25 mg/kg  |
|                                                                                   | Workers   | Inhalation      | Long-term exposure, Systemic effects                                 | 150 mg/m3 |
|                                                                                   | Consumers | Skin contact    | Long-term exposure, Systemic effects                                 | 11 mg/kg  |
|                                                                                   | Consumers | Inhalation      | Long-term exposure, Systemic effects                                 | 32 mg/m3  |
|                                                                                   | Consumers | Ingestion       | Long-term exposure, Systemic effects                                 | 11 mg/kg  |
| 2,6-dimethylheptan-4-one                                                          | Workers   | Inhalation      | Acute systemic effects, Acute local effects, Long-term local effects | 290 mg/m3 |
|                                                                                   | Workers   | Skin contact    | Long-term systemic                                                   | 80 mg/kg  |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0  
SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024  
Print Date 05.01.2026

|                  |           |              |                                                                      |            |
|------------------|-----------|--------------|----------------------------------------------------------------------|------------|
|                  |           |              | effects                                                              |            |
|                  | Workers   | Inhalation   | Long-term systemic effects                                           | 479 mg/m3  |
|                  | Consumers | Inhalation   | Acute systemic effects, Acute local effects, Long-term local effects | 145 mg/m3  |
|                  | Consumers | Skin contact | Long-term systemic effects                                           | 28,5 mg/kg |
|                  | Consumers | Inhalation   | Long-term systemic effects                                           | 171 mg/kg  |
|                  | Consumers | Ingestion    | Long-term systemic effects                                           | 7,14 mg/kg |
| ethyl lactate    | Workers   | Inhalation   | Short-term exposure                                                  | 90 mg/m3   |
|                  | Workers   | Inhalation   | Long-term exposure                                                   | 1,6 mg/m3  |
|                  | Consumers | Inhalation   | Short-term exposure                                                  | 54 mg/m3   |
|                  | Consumers | Inhalation   | Long-term exposure                                                   | 6 mg/m3    |
| butyl glycollate | Workers   | Skin contact | Long-term systemic effects                                           | 34,7 mg/kg |
|                  | Workers   | Inhalation   | Long-term systemic effects                                           | 21,2 mg/m3 |
|                  | Consumers | Ingestion    | Long-term systemic effects                                           | 2 mg/kg    |
|                  | Consumers | Skin contact | Long-term systemic effects                                           | 20,8 mg/kg |
|                  | Consumers | Skin contact | Long-term local effects                                              | 0,28 mg/kg |
|                  | Consumers | Inhalation   | Long-term systemic effects, Long-term local effects                  | 43,5 mg/m3 |

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

| Substance name           | Environmental Compartment | Value        |
|--------------------------|---------------------------|--------------|
| 2,6-dimethylheptan-4-one | Fresh water               | 0,03 mg/l    |
|                          | Marine water              | 0,003 mg/l   |
|                          | Intermittent releases     | 0,3 mg/l     |
|                          | Fresh water sediment      | 0,46 mg/kg   |
|                          | Marine sediment           | 0,046 mg/kg  |
|                          | Sewage treatment plant    | 2,55 mg/l    |
|                          | Soil                      | 0,0746 mg/kg |
| ethyl lactate            | Fresh water               | 3,2 mg/l     |
| butyl glycollate         | Fresh water               | 0,05 mg/l    |
|                          | Soil                      | 0,0112 mg/kg |
|                          | Fresh water sediment      | 0,203 mg/kg  |
|                          | Sewage treatment plant    | 232 mg/l     |

## 8.2 Exposure controls

### Personal protective equipment

Eye/face protection : Eye wash bottle with pure water  
Tightly fitting safety goggles

Hand protection



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0  
SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024  
Print Date 05.01.2026

Material : Nitrile rubber  
Break through time : > 480 min

Remarks : The suitability for a specific workplace should be discussed  
with the producers of the protective gloves.  
Skin and body protection : Impervious clothing  
Choose body protection according to the amount and  
concentration of the dangerous substance at the work place.  
Respiratory protection : In the case of vapour formation use a respirator with an  
approved filter.

### Environmental exposure controls

General advice : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform  
respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid  
Colour : colourless  
Odour : not significant  
Odour Threshold : No data available  
Melting point/freezing point : < 0 °C  
Method: derived  
Initial boiling point and boiling range : 154,00 °C  
Method: derived  
Upper explosion limit / Upper flammability limit : 7,50 %(V)  
Lower explosion limit / Lower flammability limit : 1,00 %(V)  
Flash point : 43,00 °C  
Method: 48 (Abel-Pensky) DIN 51755  
Auto-ignition temperature : > 200 °C  
Method: DIN 51794  
Decomposition temperature : No data available  
pH : 7 (20 °C)  
Concentration: 1 %

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0  
SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024  
Print Date 05.01.2026

Method: Universal pH-value indicator

### Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 1,000 mm<sup>2</sup>/s (20,00 °C)

1,000 mm<sup>2</sup>/s (40,00 °C)

### Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 5 hPa (20,00 °C)  
Method: derived

Relative density : No data available

Density : 0,8700 g/cm<sup>3</sup> (20,00 °C)  
Method: 4 (20°C oscillating U-tube)

Bulk density : Not applicable

Relative vapour density : No data available

## 9.2 Other information

Flammability (liquids) : Sustains combustion

Evaporation rate : No data available

Surface tension : < 25,00 mN/m, ring dynamometer

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0

SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024

Print Date 05.01.2026

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified due to lack of data.

#### Product:

Acute oral toxicity : LD50 (Rat): 3.990,000000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: No data available

#### Components:

##### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : LD50 (Rabbit, male and female): > 3.160 mg/kg  
Method: OECD Test Guideline 402

##### **2,6-dimethylheptan-4-one:**

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 14 mg/l  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
GLP: no

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

##### **ethyl lactate:**

Acute oral toxicity : LD50 (Rat, male and female): > 2.000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0  
SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024  
Print Date 05.01.2026

Acute inhalation toxicity : LC50 (Rat): > 5,4 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
GLP: yes

### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

#### Product:

Species : Rabbit  
Assessment : No skin irritation  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

#### Components:

##### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

##### **2,6-dimethylheptan-4-one:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

##### **butyl glycollate:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

### Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

#### Product:

Species : Rabbit  
Assessment : No eye irritation  
Method : OECD Test Guideline 405  
Result : No eye irritation

Remarks : Vapours may cause irritation to the eyes, respiratory system  
and the skin.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0  
SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024  
Print Date 05.01.2026

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : yes

#### **2,6-dimethylheptan-4-one:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : no

#### **butyl glycollate:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Risk of serious damage to eyes.  
GLP : yes

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified due to lack of data.

#### **Respiratory sensitisation**

Not classified due to lack of data.

### Product:

Remarks : No data available

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Test Type : Maximisation Test  
Exposure routes : Dermal  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.

#### **2,6-dimethylheptan-4-one:**

Test Type : Maximisation Type  
Exposure routes : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Not a skin sensitizer.  
GLP : yes

#### **butyl glycollate:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0  
SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024  
Print Date 05.01.2026

|           |   |                                    |
|-----------|---|------------------------------------|
| Test Type | : | Maximisation Test                  |
| Species   | : | Guinea pig                         |
| Method    | : | OECD Test Guideline 406            |
| Result    | : | Does not cause skin sensitisation. |
| GLP       | : | yes                                |

### Germ cell mutagenicity

Not classified due to lack of data.

#### Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

#### Components:

##### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Germ cell mutagenicity- : Classified based on benzene content < 0.1% (Regulation (EC)  
Assessment 1272/2008, Annex VI, Part 3, Note P)

### Carcinogenicity

May cause cancer.

#### Product:

Remarks : No data available

#### Components:

##### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Carcinogenicity - : Classified based on benzene content < 0.1% (Regulation (EC)  
Assessment 1272/2008, Annex VI, Part 3, Note P)

### Reproductive toxicity

Not classified due to lack of data.

#### Product:

Effects on fertility : Remarks: No data available

Effects on foetal : Remarks: No data available  
development

### STOT - single exposure

May cause respiratory irritation.  
May cause drowsiness or dizziness.

#### Product:

Remarks : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0  
SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024  
Print Date 05.01.2026

### STOT - repeated exposure

Not classified due to lack of data.

#### Product:

Remarks : No data available

### Repeated dose toxicity

#### Product:

Remarks : No data available

### Aspiration toxicity

May be fatal if swallowed and enters airways.

#### Product:

No data available

#### Components:

### Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0  
SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024  
Print Date 05.01.2026

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

##### Components:

##### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Toxicity to fish : LL50 (Fish): 9,2 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3,2 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata): 2,6 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
GLP: yes

##### **2,6-dimethylheptan-4-one:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 30 mg/l  
Exposure time: 96 h  
Test Type: flow-through test  
Method: OECD Test Guideline 203  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 37,2 mg/l  
Exposure time: 48 h  
Test Type: semi-static test  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic plants : (Pseudokirchneriella subcapitata (green algae)): 46,9 mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

##### **ethyl lactate:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 320 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0  
SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024  
Print Date 05.01.2026

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 683 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata): 2.300 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

### 12.2 Persistence and degradability

#### Product:

Biodegradability : Remarks: No data available

#### Components:

##### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F

##### **2,6-dimethylheptan-4-one:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301D  
GLP: no

##### **butyl glycollate:**

Biodegradability : Test Type: aerobic  
Result: Readily biodegradable.  
Method: OECD Test Guideline 301B  
GLP: yes

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0  
SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024  
Print Date 05.01.2026

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR : UN 1993  
RID : UN 1993  
IMDG : UN 1993  
IATA : UN 1993

### 14.2 UN proper shipping name

ADR : FLAMMABLE LIQUID, N.O.S.  
(Solvent naphtha, Diisobutyl ketone)

RID : FLAMMABLE LIQUID, N.O.S.  
(Solvent naphtha, Diisobutyl ketone)

IMDG : FLAMMABLE LIQUID, N.O.S.  
(Solvent naphtha, Diisobutyl ketone)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0  
SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024  
Print Date 05.01.2026

**IATA** : Flammable liquid, n.o.s.  
(Solvent naphtha, Diisobutyl ketone)

### 14.3 Transport hazard class(es)

**ADR** : 3  
**RID** : 3  
**IMDG** : 3  
**IATA** : 3

### 14.4 Packing group

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : D/E

**RID**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Remarks : IMDG Code segregation group - none

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 366  
Packing group : III  
Labels : Flammable Liquids

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### 14.5 Environmental hazards

**ADR**  
Environmentally hazardous : yes

**RID**  
Environmentally hazardous : yes

**IMDG**  
Marine pollutant : yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0

SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024

Print Date 05.01.2026

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

|                                                                                                                                                         |     |                                                                                                                                                                                                                                                                         |
|---------------------------------------------------------------------------------------------------------------------------------------------------------|-----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)              | :   | Conditions of restriction for the following entries should be considered:<br>Number on list 3<br><br>Number on list 28: cumene<br><br>Number on list 72: benzene<br><br>Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor. |
| REACH - List of substances subject to authorisation (Annex XIV)                                                                                         | :   | Not applicable                                                                                                                                                                                                                                                          |
| Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. | E2  | ENVIRONMENTAL HAZARDS                                                                                                                                                                                                                                                   |
|                                                                                                                                                         | P5c | FLAMMABLE LIQUIDS                                                                                                                                                                                                                                                       |

### 15.2 Chemical safety assessment

Not applicable

## SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

### Full text of H-Statements

|      |   |                                               |
|------|---|-----------------------------------------------|
| H226 | : | Flammable liquid and vapour.                  |
| H304 | : | May be fatal if swallowed and enters airways. |
| H318 | : | Causes serious eye damage.                    |
| H335 | : | May cause respiratory irritation.             |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0

SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024

Print Date 05.01.2026

|        |                                                         |
|--------|---------------------------------------------------------|
| H336   | : May cause drowsiness or dizziness.                    |
| H350   | : May cause cancer.                                     |
| H361   | : Suspected of damaging fertility or the unborn child.  |
| H411   | : Toxic to aquatic life with long lasting effects.      |
| EUH066 | : Repeated exposure may cause skin dryness or cracking. |

### Full text of other abbreviations

|                     |                                                                                                                        |
|---------------------|------------------------------------------------------------------------------------------------------------------------|
| Aquatic Chronic     | : Long-term (chronic) aquatic hazard                                                                                   |
| Asp. Tox.           | : Aspiration hazard                                                                                                    |
| Carc.               | : Carcinogenicity                                                                                                      |
| Eye Dam.            | : Serious eye damage                                                                                                   |
| Flam. Liq.          | : Flammable liquids                                                                                                    |
| Repr.               | : Reproductive toxicity                                                                                                |
| STOT SE             | : Specific target organ toxicity - single exposure                                                                     |
| 2000/39/EC          | : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values   |
| 2019/1831/EU        | : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values |
| GB EH40             | : UK. EH40 WEL - Workplace Exposure Limits                                                                             |
| 2000/39/EC / TWA    | : Limit Value - eight hours                                                                                            |
| 2000/39/EC / STEL   | : Short term exposure limit                                                                                            |
| 2019/1831/EU / TWA  | : Limit Value - eight hours                                                                                            |
| 2019/1831/EU / STEL | : Short term exposure limit                                                                                            |
| GB EH40 / TWA       | : Long-term exposure limit (8-hour TWA reference period)                                                               |
| GB EH40 / STEL      | : Short-term exposure limit (15-minute reference period)                                                               |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## BYKETOL-SPECIAL SG

Version 3.0  
SDB\_GB

Revision Date: 14.03.2025

Date of last issue: 04.12.2024  
Print Date 05.01.2026

Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

|                   |      |
|-------------------|------|
| Flam. Liq. 3      | H226 |
| Carc. 1B          | H350 |
| STOT SE 3         | H336 |
| STOT SE 3         | H335 |
| Asp. Tox. 1       | H304 |
| Aquatic Chronic 2 | H411 |

#### Classification procedure:

|                                     |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN