

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CERATIX 8566 N

Version 1.0

SDB_CH

Revision Date: 26.04.2024

Date of last issue: -

Print Date 09.05.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : CERATIX 8566 N
Product code : 000000000000138725

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Wax Additive

1.3 Details of the supplier of the safety data sheet

Company : BYK Netherlands BV
Danzigweg 23
7418 EN Deventer
Telephone : +31 881 220 300

Information : Regulatory Affairs
Telephone : +49 281 670-23532
Telefax : +49 281 670-23533
E-mail address : GHS.BYK@altana.com

1.4 Emergency telephone number

+44 1235 239670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CERATIX 8566 N

Version 1.0

SDB_CH

Revision Date: 26.04.2024

Date of last issue: -

Print Date 09.05.2025

H315 Causes skin irritation.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

- 123-86-4 n-butyl acetate
- 71-36-3 butan-1-ol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Ethylene-Vinyl-Acetate (EVA) Copolymer wax dispersion

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 50 - <= 100

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CERATIX 8566 N

Version 1.0

SDB_CH

Revision Date: 26.04.2024

Date of last issue: -

Print Date 09.05.2025

butan-1-ol	71-36-3 200-751-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	>= 10 - < 12,5
------------	--	---	----------------

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

CERATIX 8566 N

Version 1.0
SDB_CH

Revision Date: 26.04.2024

Date of last issue: -
Print Date 09.05.2025

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

CERATIX 8566 N

Version 1.0
SDB_CH

Revision Date: 26.04.2024

Date of last issue: -
Print Date 09.05.2025

/ national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	TWA	50 ppm 240 mg/m ³	CH SUVA
Further information: National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles, Harm to the unborn child is not to				

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CERATIX 8566 N

Version 1.0

SDB_CH

Revision Date: 26.04.2024

Date of last issue: -

Print Date 09.05.2025

		be expected when the OEL-value is respected		
		STEL	150 ppm 720 mg/m ³	CH SUVA
	Further information: National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles, Harm to the unborn child is not to be expected when the OEL-value is respected			
		STEL	150 ppm 723 mg/m ³	2019/1831/E U
	Further information: Indicative			
		TWA	50 ppm 241 mg/m ³	2019/1831/E U
	Further information: Indicative			
butan-1-ol	71-36-3	TWA	100 ppm 310 mg/m ³	CH SUVA
	Further information: National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles, Harm to the unborn child is not to be expected when the OEL-value is respected			
		STEL	100 ppm 310 mg/m ³	CH SUVA
	Further information: National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles, Harm to the unborn child is not to be expected when the OEL-value is respected			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
butan-1-ol	71-36-3	n-butanol: 10 mg/g creatinine (Urine)	Immediately after exposure or after working hours	CH BAT
		n-butanol: 2 mg/g creatinine (Urine)	Before next shift or 16 hours after last shift	CH BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Acute local effects	600 mg/m ³
	Workers	Inhalation	Long-term local effects	300 mg/m ³
	Consumers	Inhalation	Acute local effects	300 mg/m ³
	Consumers	Inhalation	Long-term local effects	35,7 mg/m ³
	Workers	Dermal	Long-term systemic effects	11 mg/kg
	Workers	Dermal	Acute systemic effects	11 mg/kg
	Consumers	Dermal	Long-term systemic effects	6 mg/kg
	Consumers	Dermal	Acute systemic effects	6 mg/kg
	Consumers	Oral	Long-term systemic effects	2 mg/m ³

CERATIX 8566 N

Version 1.0
SDB_CH

Revision Date: 26.04.2024

Date of last issue: -
Print Date 09.05.2025

	Consumers	Oral	Acute systemic effects	2 mg/m3
butan-1-ol	Workers	Inhalation	Long-term exposure, Local effects	310 mg/m3
	Consumers	Inhalation	Long-term exposure, Local effects	55 mg/m3
	Consumers	Ingestion	Long-term exposure, Systemic effects	3,125 mg/cm2

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-butyl acetate	Fresh water	0,18 mg/l
	Marine water	0,018 mg/l
	Intermittent releases	0,36 mg/l
	Fresh water sediment	0,981 mg/kg
	Marine sediment	0,0981 mg/kg
	Soil	0,0903 mg/kg
	Sewage treatment plant	35,6 mg/l
butan-1-ol	Fresh water	0,082 mg/l
	Marine water	0,0082 mg/l
	Fresh water sediment	0,178 mg/kg
	Marine sediment	0,0178 mg/kg
	Soil	0,015 mg/kg
	Intermittent releases	2,25 mg/l
	Sewage treatment plant	2476 mg/l

8.2 Exposure controls

Personal protective equipment

- Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Hand protection
- Material : Polyvinyl alcohol or nitrile- butyl-rubber gloves
- Rate of permeability : 480 min
- Protective index : Class 6

- Remarks : The information is based on our own tests, on data from literature and information from protective glove producers or is based on data obtained from similar substances. The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.
The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Environmental exposure controls

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CERATIX 8566 N

Version 1.0

SDB_CH

Revision Date: 26.04.2024

Date of last issue: -

Print Date 09.05.2025

General advice	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
----------------	---

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: dispersion
Colour	: white - off-white
Odour	: solvent-like
Odour Threshold	: No data available
Melting point/range	: No data available
Initial boiling point and boiling range	: 118 °C
Upper explosion limit / Upper flammability limit	: 11,3 %(V)
Lower explosion limit / Lower flammability limit	: 1,4 %(V)
Flash point	: 27 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
pH	: insoluble
Viscosity	
Viscosity, dynamic	: ca. 10 mPa.s (20 °C)
Viscosity, kinematic	: 36 mm2/s (40 °C) Method: No information available.
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: 0,875 g/cm3 (20 °C, 1.013 hPa)
Relative vapour density	: No data available

9.2 Other information

Flammability (liquids)	: Sustains combustion
------------------------	-----------------------

CERATIX 8566 N

Version 1.0
SDB_CH

Revision Date: 26.04.2024

Date of last issue: -
Print Date 09.05.2025

Evaporation rate : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong acids and oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

n-butyl acetate:

Acute oral toxicity : LD50 (Rat, male): > 10.000 mg/kg
Method: OECD Test Guideline 423

Acute inhalation toxicity : LC50 (Rat, male and female): > 21,1 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): > 14.000 mg/kg
Method: OECD Test Guideline 402

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CERATIX 8566 N

Version 1.0

SDB_CH

Revision Date: 26.04.2024

Date of last issue: -
Print Date 09.05.2025

butan-1-ol:

Acute oral toxicity : LD50 (Rat, female): 2.292 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit, male): 3.430 mg/kg
Method: OECD Test Guideline 402
GLP: yes

Skin corrosion/irritation

Product:

Remarks : May irritate skin.
May cause skin irritation in susceptible persons.

Components:

n-butyl acetate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

butan-1-ol:

Species : Rabbit
Method : Draize Test
Result : Skin irritation

Serious eye damage/eye irritation

Product:

Remarks : May cause irreversible eye damage.

Components:

n-butyl acetate:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

butan-1-ol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Risk of serious damage to eyes.
GLP : yes

Respiratory or skin sensitisation

Product:

Remarks : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CERATIX 8566 N

Version 1.0

SDB_CH

Revision Date: 26.04.2024

Date of last issue: -

Print Date 09.05.2025

Components:

n-butyl acetate:

Test Type	:	Buehler Test
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	Does not cause skin sensitisation.

butan-1-ol:

Test Type	:	Maximisation Test
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	Does not cause skin sensitisation.
GLP	:	yes

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Product:

Remarks : No data available

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure

Product:

Remarks : No data available

STOT - repeated exposure

Product:

Remarks : No data available

Repeated dose toxicity

Product:

Remarks : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CERATIX 8566 N

Version 1.0

SDB_CH

Revision Date: 26.04.2024

Date of last issue: -

Print Date 09.05.2025

Aspiration toxicity

Product:

No data available

Components:

butan-1-ol:

No aspiration toxicity classification

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Components:

n-butyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 44 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Scenedesmus subspicatus): 675 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CERATIX 8566 N

Version 1.0

SDB_CH

Revision Date: 26.04.2024

Date of last issue: -

Print Date 09.05.2025

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23 mg/l
End point: Reproduction
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

butan-1-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1.376 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.328 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : ErC50 (Selenastrum capricornutum (green algae)): 225 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 4,1 mg/l
End point: Reproduction
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Method: OECD Test Guideline 211
GLP: yes

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

n-butyl acetate:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301D

butan-1-ol:

Biodegradability : Test Type: aerobic
Result: Readily biodegradable.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

CERATIX 8566 N

Version 1.0
SDB_CH

Revision Date: 26.04.2024

Date of last issue: -
Print Date 09.05.2025

Components:

n-butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2,3 (25 °C)
pH: 7
Method: OECD Test Guideline 117
GLP: yes

butan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 1 (25 °C)
pH: 7
Method: OECD Test Guideline 117
GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

CERATIX 8566 N

Version 1.0
SDB_CH

Revision Date: 26.04.2024

Date of last issue: -
Print Date 09.05.2025

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1993
RID : UN 1993
IMDG : UN 1993
IATA : UN 1993

14.2 UN proper shipping name

ADR : FLAMMABLE LIQUID, N.O.S.
(n-Butylacetate, n-Butanol)
RID : FLAMMABLE LIQUID, N.O.S.
(n-Butylacetate, n-Butanol)
IMDG : FLAMMABLE LIQUID, N.O.S.
(BUTYL ACETATE, n-Butanol)
IATA : Flammable liquid, n.o.s.
(Butyl acetate, n-Butanol)

14.3 Transport hazard class(es)

ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : D/E

RID
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)
Packing instruction (cargo aircraft) : 366
Packing group : III

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CERATIX 8566 N

Version 1.0

SDB_CH

Revision Date: 26.04.2024

Date of last issue: -

Print Date 09.05.2025

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355

Packing instruction (LQ) : Y344

Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
Volatile organic compounds (VOC) content: 95,32 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CERATIX 8566 N

Version 1.0

SDB_CH

Revision Date: 26.04.2024

Date of last issue: -
Print Date 09.05.2025

15.2 Chemical safety assessment

Not applicable

SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
EUH066	: Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Eye Dam.	: Serious eye damage
Flam. Liq.	: Flammable liquids
Skin Irrit.	: Skin irritation
STOT SE	: Specific target organ toxicity - single exposure
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
CH BAT	: Switzerland. List of BAT-values
CH SUVA	: Switzerland. Limit values at the work place
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
CH SUVA / TWA	: Time Weighted Average
CH SUVA / STEL	: Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



CERATIX 8566 N

Version 1.0

SDB_CH

Revision Date: 26.04.2024

Date of last issue: -

Print Date 09.05.2025

Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Dam. 1	H318
STOT SE 3	H336

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CH / EN