

FULCAT-22 B

Product code: 000000000000158439

Version

2.0 SDS_REG_UN

Revision Date:

18.11.2022

Date of last issue: 14.11.2018

Date of first issue: 23.12.2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : FULCAT-22 B

Type of Application (Use) : Catalyst

Manufacturer or supplier's details

Company : BYK Additives Ltd.

Address : Moorfield Road
WA8 3AA Widnes

Telephone : +49 281 670-23532

Telefax : +49 281 670-23533

E-mail address : GHS.BYK@altana.com

Emergency telephone number : Europe +44 1235 239670
Middle East/Africa +44 1235 239671
Americas +1 215 207 0061
East/South East Asia +65 3158 1074
(Local India: 000 800 100 7479)**2. HAZARDS IDENTIFICATION****GHS Classification**

Carcinogenicity : Category 1A

Specific target organ toxicity -
repeated exposure : Category 2 (Lungs)**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H350 May cause cancer.
H373 May cause damage to organs (Lungs) through prolonged
or repeated exposure.

Precautionary statements :

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read
and understood.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

FULCAT-22 B

Product code: 000000000000158439

Version
2.0 SDS_REG_UNRevision Date:
18.11.2022Date of last issue: 14.11.2018
Date of first issue: 23.12.2016

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance
Chemical nature : Acid leached phyllosilicate

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO ₂)	14808-60-7	>= 1 - < 3

4. FIRST AID MEASURES

General advice : Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
If breathed in, move person into fresh air.

In case of skin contact : Wash off with soap and water.
Get medical attention if irritation develops and persists.
If on clothes, remove clothes.
Wash contaminated clothing before re-use.

In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

Most important symptoms : No symptoms known or expected.

FULCAT-22 B

Product code: 00000000000158439

Version

2.0 SDS_REG_UN

Revision Date:

18.11.2022

Date of last issue: 14.11.2018

Date of first issue: 23.12.2016

and effects, both acute and delayed

Notes to physician

Irritating to eyes, respiratory system and skin.

: Treat symptomatically.

5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : The product itself does not burn.
Material can be slippery when wet.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.
Keep people away from and upwind of spill/leak.
Material can create slippery conditions.
Only qualified personnel equipped with suitable protective equipment may intervene.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Pick up and arrange disposal without creating dust.
Use approved industrial vacuum cleaner for removal.
High efficiency particulate air filter (HEPA filter)
Clean-up methods - large spillage
Knock down dust with water spray jet.
Shovel into suitable container for disposal.
After cleaning, flush away traces with water.
Clean-up methods - small spillage
Sweep up or vacuum up spillage and collect in suitable container for disposal.
- Neutralize with chalk, alkali solution or ammonia.
Keep in suitable, closed containers for disposal.

FULCAT-22 B

Product code: 000000000000158439

Version

2.0 SDS_REG_UN

Revision Date:

18.11.2022

Date of last issue: 14.11.2018

Date of first issue: 23.12.2016

7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
- Advice on safe handling : Avoid formation of respirable particles.
Do not breathe vapours/dust.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Avoid dust formation.
Keep container tightly closed in a dry and well-ventilated place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO ₂)	14808-60-7	TWA (Respirable fraction)	0,025 mg/m ³ (Silica)	ACGIH

- Engineering measures** : Ensure adequate ventilation.
Maintain air concentrations below occupational exposure standards.
Dust must be extracted directly at the point of origin.

Personal protective equipment

Hand protection

Remarks

- : Use protective skin cream before handling the product.

Eye protection

- : Wear safety glasses with side shields or goggles.
-
- If the work environment or activity involves dusty conditions, mists or aerosols, wear the appropriate goggles.

Skin and body protection

- : Work uniform or laboratory coat.

Hygiene measures

:

9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : powder
- Colour : off-white
- Odour : odourless
- Odour Threshold : Not applicable
- pH : 3
- Melting point/freezing point : Not applicable

FULCAT-22 B

Product code: 000000000000158439

Version

2.0 SDS_REG_UN

Revision Date:

18.11.2022

Date of last issue: 14.11.2018

Date of first issue: 23.12.2016

Boiling point/boiling range	:	Not applicable
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Will not burn
Self-ignition	:	Not applicable
Upper explosion limit	:	Not applicable
Lower explosion limit	:	Not applicable
Vapour pressure	:	Not applicable
Relative vapour density	:	Not applicable
Relative density	:	No data available
Density	:	No data available
Bulk density	:	1.000 kg/m ³
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Ignition temperature	:	Not applicable
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available

10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

FULCAT-22 B

Product code: 00000000000158439

Version

2.0 SDS_REG_UN

Revision Date:

18.11.2022

Date of last issue: 14.11.2018

Date of first issue: 23.12.2016

11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

Acute oral toxicity : LD50(Rat): > 2.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50(Rat): > 50 mg/l
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50(Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation**Product:**

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation
GLP: yes

Serious eye damage/eye irritation**Product:**

Species: Rabbit
Method: OECD Test Guideline 405
Result: No eye irritation
GLP: yes

Respiratory or skin sensitisation**Product:**

Test Type: Mouse Local Lymph Node assay (LLNA)
Exposure routes: Dermal
Species: Mouse
Method: OECD Test Guideline 429
Result: Does not cause skin sensitisation.

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Test Type: reverse mutation assay
Species: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

FULCAT-22 B

Product code: 000000000000158439

Version

2.0 SDS_REG_UN

Revision Date:

18.11.2022

Date of last issue: 14.11.2018

Date of first issue: 23.12.2016

GLP: yes

- : Test Type: Chromosome aberration test in vitro
Species: Human lymphocytes
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative
GLP: yes
- : Test Type: In vitro mammalian cell gene mutation test (mouse lymphoma)

Species: mouse lymphoma cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative
GLP: yes

12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: Immobilization
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50 (activated sludge): > 1.000 mg/l
Exposure time: 3 h
Test Type: Respiration inhibition
Method: OECD Test Guideline 209

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil**Product:**

- Mobility : Remarks: Bentonite is almost insoluble and thus presents a low mobility in most soils

FULCAT-22 B

Product code: 000000000000158439

Version

2.0 SDS_REG_UN

Revision Date:

18.11.2022

Date of last issue: 14.11.2018

Date of first issue: 23.12.2016

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Contact manufacturer.

16. OTHER INFORMATION

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.